



Vehicle Incident Detection software running in the network camera

The Vehicle Incident Detection function detects incidents such as wrong-way driving and stopped vehicles, and then alerts the Traffic Management System. While it is difficult for a single human operator to physically detect vehicle accidents on multiple camera monitors, such monitoring is made possible with the Vehicle Incident Detection system.

The Vehicle Incident Detection function enables the early detection of traffic accidents and the efficiency of traffic control center.

Key Features

- Incident detection: Wrong-way driving, Stopped vehicle with video analytic technology
- Send alarm to Video Management System and/or Traffic Management System for immediate action
- The function is built-in the camera. No additional server is required.



Specifications

Basic Specifications

| | |
|-----------------------------------|--|
| Camera height | 2.5m(8.5ft) - 30.0m(100.0ft) / Auto setup Auto setup function select automatically camera height. |
| Traffic lane setup | Up to four traffic lanes per preset position |
| Detection type | Wrong-way driving, Stopped vehicle, Off |
| Moving direction | Up / Down Select driving direction for normal case |
| Detection time of Stopped Vehicle | 5s - 15s |
| Night mode | Priority to monitoring / Priority to Detection |
| image capture mode | WV-X6531N : 3 mega pixel [4:3](30fps mode) WV-X6511N : 1.3 mega pixel [4:3](30fps mode) |
| Alarm actions | E-mail notification, HTTP alarm notification, Indication on browser, Panasonic alarm protocol output |

Compatible models

40x Intelligent Zoom Stabilization iA PTZ Camera

WV-X6531N, WV-X6511N

Firmware version is V1.20 or later.

Key Features

- Full-HD 1920x1080 60fps : WV-X6531N
- HD 1280x720 60fps : WV-X6511N
- Intelligent Zoom Stabilization with 40x optical zoom
- ClearSight Coating
- Durable Pan/Tilt gear mechanism
- iA (intelligent Auto)
- Extreme Super Dynamic 144dB
- Color night vision
(0.001 to 0.015 lx : WV-X6531N / 0.0007 to 0.011 lx : WV-X6511N)
- IP66, IK10 certified
- Wider operating temperature range -50 °C to +60 °C (-58 °F to +140 °F)



WV-X6531N



WV-X6511N

Trademarks and registered trademarks

- "i-PRO EXTREME" logo is trademarks or registered trademarks of Panasonic Corporation.

Important


- Safety Precaution : Carefully read the Important Information, Installation Guide and operating instructions before using this product.
- Panasonic cannot be responsible for the performance of the network and/or other manufacturers' products used on the network.

• Specifications are subject to change without notice.

DISTRIBUTED BY :

Panasonic

<https://security.panasonic.com>

 <http://www.facebook.com/PanasonicNetworkCamera>

(2A-197L)