

	Function	WV-PM500	WV-S61501-Z1	WV-S61300-ZY/ZYG	WV-S65501-Z1/Z1G	WV-S65300-ZY/ZYG	WV-S65301-Z1/Z1G Z1-1/Z1S	WV-S65302-Z2/Z2G Z2-1	WV-U61300-ZY/ZYG/Z1V	WV-U65300-ZY/ZYG	WV-S65340-Z2N/Z4N/Z1K/Z4K Z2N1/Z2G/Z4G/Z2 Z2N1/Z4/Z4N1	WV-S61302-Z4	WV-S25500-F3L/F6L	WV-S22500-F3L/F6L	WV-S15500-F3L/F6L	WV-U61301-Z1/Z2
WJ-NU101K/KG WJ-NU201K/KG WJ-NU300K/KG WJ-NU301K/KG (V1.60) *20	MJPEG	-	-	yes	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	yes	-	-	-	-	-	-	-
	H.264	-	-	yes	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	yes	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio *32	-	-	yes	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	yes	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX400 (V5.10) *20	Motion detection (VMD)	-	-	yes	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	yes	-	-	-	-	-	-	-
	H.264	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23
WJ-NX300 (V5.10) *20	PTZ	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	yes	-	-	-	-	-	-	-
	H.264	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX200 (V5.10) *20	Audio	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23
	PTZ	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	yes	-	-	-	-	-	-	-
	H.264	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX100 (V5.10) *20	H.265	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23
	PTZ	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	yes	-	-	-	-	-	-	-
WJ-NV300 (V2.30) *14 (Discontinued model)	H.264	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	Audio *8	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	-	-	[S61301]	-	[S61301]	[S61301]	[S61301]	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	-	-	-	-	-	-	-	yes	-	-	-	-	-	-	-
WJ-NV200 (V2.60) *14 (Discontinued model)	MPEG4	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	H.264	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	Audio *8	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
WJ-ND400K (V6.10) *14 (Discontinued model)	MJPEG	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	H.264	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	Audio *8	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
WJ-ND300A (V5.20) *4, *14 (Discontinued model)	Motion detection (VMD)	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	H.264	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
WJ-ND200 (V9.35) *4, *14 (Discontinued model)	PTZ	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	H.264	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes

[substitute model or camera classification] : Register as a substitute model or a camera classification.  
 \*1 : Only for remote PTZ camera.  
 \*2 : Support less than 1920x1080, including 1600x1200, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality:5-9 and the frame rate:up to 5fps.  
 \*3 : Each recorder supports only wireline connection.  
 \*4 : Displaying 16:9 is not supported on a NDR browser.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Support G.726 and 32kbps.  
 \*11 : This function is supported only when playing back.  
 \*12 : Supported up to 30 fps.  
 \*13 : When using WV-SFV481/WV-SFV480 with WJ-NV200, recording stops for about 10 seconds at the time of a screen change in a main monitor.  
 \*14 : Streams of H.265(4) and H.265(9) are not supported.  
 \*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SPV781L, SPV781L, SPV481, SPV480 support will be only 1-8ch.  
 \*17 : The fish-eye dewarp function on the main monitor is supported.  
 \*18 : The fish-eye dewarp function is supported by using the management software(WV-ASM200, WV-ASC370).  
 \*19 : Support maximum bitrate is 14Mbps.  
 \*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 cameras  
 \*21 : Support less than 1280x720 for WV-S6511W  
 \*22 : Transmission format must be switched from H.265(Factory default) to H.264 by connecting from web browser  
 \*23 : Support G.726/32kbps and AAC-LC/64kbps.  
 \*24 : Supported image capture sizes are 402x302(2160), WQHD(2560x1440), HD(1920x1080) and HD(1280x720).  
 \*25 : Support 640x480  
 \*26 : Support 1920x1080, 1280x720 and 1280x660. Supported up to 30 fps  
 \*27 : WV-V1170 additionally supports 3840x2160, 2048x1536, 2560x1920, 4000x3000(15fps).  
 \*28 : Support G.726.  
 \*29 : Support 640x480 and 320x240.  
 \*30 : Support 3840x2160, 1920x1080, 1280x720, 2560x1920, 2048x1536 and 1280x660 for WV-V1170.  
 \*31 : The supported camera firmware is V1.10 or later.  
 \*32 : Only AAC-LC/64kbps is supported.

	Function	WV-U65301-Z1/Z1G	WV-U65302-Z2/Z2G	WV-S61301-Z1/Z2	WV-S71300-F3	WV-S25700-V2L/V2LN/V2LG/V2LN1	WV-S25600-V2L/V2LN/V2LG	WV-S25500-V3L/V3LN/V3LG/V3LN1	WV-S22700-V2L/V2LG/V2L1/V2L1Q	WV-S22600-V2L/V2LG	WV-S22500-V2L/V3LG/V3L1	WV-S15700-V2L/V2LN/V2LK	WV-S15600-V2L/V2LN/	WV-S15500-V3L/V3LN/V3LN1/V3LK	WV-S8573L/S8573LG/S8574L/S8574LG	WV-S8563L/S8563LG/S8564L/S8564LG	
WJ-NU101K/KG WJ-NU201K/KG WJ-NU300K/KG WJ-NU301K/KG (V1.60) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	no
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio *32	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX400 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	no
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23
	PTZ	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX300 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	no
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23
	PTZ	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX200 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23
	PTZ	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX100 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	no
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23
	PTZ	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NV300 (V2.30) *14 (Discontinued model)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio *8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-NV200 (V2.60) *14 (Discontinued model)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio *8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-ND400K (V6.10) *14 (Discontinued model)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio *8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-ND300A (V5.20) *4, *14 (Discontinued model)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-ND200 (V9.35) *4, *14 (Discontinued model)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio *8*11	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

[substitute model or camera classification] : Register as a substitute model or a camera classification.  
 \*1 : Only for remote PTZ camera.  
 \*2 : Support less than 1920x1080, including 1600x1200, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality:5-9 and the frame rate:up to 5fps.  
 \*3 : Each recorder supports only wireline connection.  
 \*4 : Displaying 16:9 is not supported on a NDR browser.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Support G.726 and 32kbps.  
 \*11 : This function is supported only when playing back.  
 \*12 : Supported up to 30 fps.  
 \*13 : When using WV-SFV481/WV-SFV480 with WJ-NV200, recording stops for about 10 seconds at the time of a screen change in a main monitor.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SPV781L, SPV781, SPV481, SPV480 support will be only 1-8ch.  
 \*17 : The fish-eye dewarp function on the main monitor is supported.  
 \*18 : The fish-eye dewarp function is supported by using the management software(WV-ASM200, WV-ASC370).  
 \*19 : Support maximum bitrate is 14Mbps.  
 \*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 cameras  
 \*21 : Support less than 1280x720 for WV-S511N  
 \*22 : Transmission format must be switched from H.265(Factory default) to H.264 by connecting from web browser  
 \*23 : Support G.726/32kbps and AAC-LC/9kbps.  
 \*24 : Supported image capture sizes are 4K(4096x2160), WQHD(2560x1440), HD(1920x1080) and HD(1280x720).  
 \*25 : Support 640x480  
 \*26 : Support 1920x1080, 1280x720 and 1280x960. Supported up to 30 fps  
 \*27 : WV-V1170 additionally supports 3840x2160, 2048x1536, 2560x1920, 4000x3000(15fps).  
 \*28 : Support G.726.  
 \*29 : Support 640x480 and 320x240.  
 \*30 : Support 3840x2160, 1920x1080, 1280x720, 2560x1920, 2048x1536 and 1280x960 for WV-V1170.  
 \*31 : The supported camera firmware is V1.10 or later.

	Function	WV-S8543/S8543G/S8544/S8544L/S8544LG	WV-X8571N/S8531N	WV-X8570N/S8530N	WV-X6533LN/X6533LNS/S6532LN/S6532LNS	WV-X6531N/X6531NS/X6511N	WV-SUD638	WV-S6530N	WV-S6131/S6111/S6130	WV-X4573L/X4573LM	WV-X4171L/X4571L/X4571LM	WV-X4172/X4173	WV-X4170	WV-S4556LM/S4556L/S41156	WV-S4576LM/S4576L/S41176	WV-S4551L/S4551LM/S4151
WJ-NU101K/KG WJ-NU201K/KG WJ-NU300K/KG WJ-NU301K/KG (V1.00) *20	MJPEG	no	no	no	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio *32	yes	yes (for X8571N)	yes (for X8570N)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX400 (V5.10) *20	MJPEG	no	no	no	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes (for X8571N) *23	yes (for X8570N) *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX300 (V5.10) *20	MJPEG	no	no	no	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes (for X8571N) *23	yes (for X8570N) *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX200 (V5.10) *20	MJPEG	no	no	no	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes (for X8571N) *23	yes (for X8570N) *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX100 (V5.10) *20	MJPEG	no	no	no	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes (for X8571N) *23	yes (for X8570N) *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NV300 (V2.30) *14 (Discontinued model)	MJPEG	-	-	-	[X6531/S6530]	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	[X6531/S6530]	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	no	no	no	no	no	no	no	no	no	no	no	no
	Audio *8	-	-	-	[X6531/S6530]	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	[X6531/S6530]	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	-	-	-	[X6531/S6530]	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NV200 (V2.60) *14 (Discontinued model)	MJPEG	-	-	-	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	[SW598] *21*22	[SW598] *21*22	[SW598]	[SW598] *21*22	[SW598]	[SW598] *21*22	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]
	H.265	-	-	-	-	no	no	no	no	no	no	no	no	no	no	no
	Audio *8	-	-	-	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]
	PTZ	-	-	-	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]
	Motion detection (VMD)	-	-	-	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]	[SW598]
WJ-ND400K (V6.10) *14 (Discontinued model)	MJPEG	-	-	-	[X6531/S6530]	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	[X6531/S6530]	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	no	no	no	no	no	no	no	no	no	no	no	no
	Audio *8	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Motion detection (VMD)	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-ND300A (V5.20) *4, *14 (Discontinued model)	MJPEG	-	-	-	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-ND200 (V3.35) *4, *14 (Discontinued model)	MJPEG	-	-	-	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2	[SC385]*2
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio *8*11	-	-	-	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]
	PTZ	-	-	-	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]	[SC385]
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

[substitute model or camera classification] : Register as a substitute model or a camera classification.  
 \*1 : Only for remote PTZ camera.  
 \*2 : Support less than 1920x1080, including 1600x1200, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality:5-9 and the frame rate:up to 5fps.  
 \*3 : Each recorder supports only wireline connection.  
 \*4 : Displaying 16:9 is not supported on a NDK browser.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Support G.726 and 32kbps.  
 \*11 : This function is supported only when playing back.  
 \*12 : Supported up to 30 fps.  
 \*13 : When using WV-SPV481/WV-SPV480 with WJ-NV200, recording stops for about 10 seconds at the time of a screen change in a main monitor.  
 \*14 : Streams of H.265(4) and H.265(4) are not supported.  
 \*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SPV781L, SPV781L, SPV481, SPV480 support will be only 1-8ch.  
 \*17 : The fish-eye dewarp function on the main monitor is supported.  
 \*18 : The fish-eye dewarp function is supported by using the management software(WV-ASM200, WV-ASC370).  
 \*19 : Support maximum bitrate is 14Mbps.  
 \*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 cameras  
 \*21 : Support less than 1280x720 for WV-X6511N  
 \*22 : Transmission format must be switched from H.265(Factory default) to H.264 by connecting from web browser  
 \*23 : Support G.726/32kbps and AAC-LC/8kbps.  
 \*24 : Supported image capture sizes are 4K(UHD/3840x2160), WQHD(2560x1440), HD(1920x1080) and HD(1280x720).  
 \*25 : Support 640x480  
 \*26 : Support 1920x1080, 1280x720 and 1280x960. Supported up to 30 fps  
 \*27 : WV-V1170 additionally supports 3840x2160, 2048x1536, 2560x1920, 4000x3000(15fps).  
 \*28 : Support G.726.  
 \*29 : Support 640x480 and 320x240.  
 \*30 : Support 3840x2160, 1920x1080, 1280x720, 2560x1920, 2048x1536 and 1280x960 for WV-V1170.  
 \*31 : The supported camera firmware is V1.10 or later.

	Function	WV-S4550L/S4550LM/S4150	WV-SFV481/SFN480*7	WV-SW458/SW458MA/SF433/SF448*7	WV-X2571LN/X2271L/X1571LN	WV-S2572L/S2272L/S1572L	WV-S2570L/S2270L/S1570L	WV-SFV781L/SPV781L	WV-X1551LN	WV-S1536L/S1536LN/S1536LTN	WV-S1552L	WV-S1550L	WV-S1531LN/S1531LTN/S1531LNS/S1511LN	WV-U1542L/U1532LA/U1532LAJ	WV-U1542L/U1532L	WV-S1136
WJ-N101K/KG WJ-N1201K/KG WJ-N1300K/KG WJ-N1301K/KG (V1.60) *20	MJPEG	yes	(I-PRO(D, FE))	(I-PRO(B, FE))	yes	yes	no	(I-PRO(D, FIX))	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	(I-PRO(D, FE))	(I-PRO(B, FE))	yes	yes	yes	(I-PRO(D, FIX))	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	-	-	yes	yes	yes	-	yes	yes	yes	yes	yes	yes	yes	yes
	Audio *32	yes	(I-PRO(D, FE))	no	yes	yes	yes	(I-PRO(D, FIX))	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	(I-PRO(D, FE))	(I-PRO(B, FE))	yes	yes	yes	(I-PRO(D, FIX))	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX400 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	no	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes*17,*18,*19	yes*17,*18	yes	yes	yes	yes*19	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	-	-	yes	yes	yes	-	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes *23	yes *8	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	-	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX300 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	no	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes*17,*18,*19	yes*17,*18	yes	yes	yes	yes*19	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	-	-	yes	yes	yes	-	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes *23	yes *8	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	-	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX200 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	no	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes*17,*18,*19	yes*17,*18	yes	yes	yes	yes*19	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	-	-	yes	yes	yes	-	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes *23	yes *8	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	-	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX100 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	no	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes*17,*18,*19	yes*17,*18	yes	yes	yes	yes*19	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	-	-	yes	yes	yes	-	yes	yes	yes	yes	yes	yes	yes	yes
	Audio	yes *23	yes *23	yes *8	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	-	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NV300 (V2.30) *14 (Discontinued model)	MJPEG	yes	yes	yes	-	-	-	(SPV781/SPV781)	yes	-	-	-	(S1531)	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	(S1131)
	H.264	yes	yes*17,*18,*19	yes*17,*18	-	-	-	(SPV781/SPV781)*22,*24	yes	-	-	-	(S1531)	yes	yes	(S1131)
	H.265	-	-	-	-	-	-	no	-	-	-	-	no	-	no	no
	Audio *8	yes	yes	yes	-	-	-	(SPV781/SPV781)	yes	-	-	-	(S1531)	yes	yes	(S1131)
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	-	-	-	(SPV781/SPV781)	yes	-	-	-	(S1531)	yes	yes	(S1131)
WJ-NV200 (V2.60) *14 (Discontinued model)	MJPEG	yes	no*13	yes	-	-	-	-	-	-	-	-	-	(SPW631)	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	no*13	yes	-	-	-	-	-	-	-	-	-	(SPW631)*22	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio *8	-	no*13	yes	-	-	-	-	-	-	-	-	-	-	no	-
	PTZ	-	-	yes	-	-	-	-	-	-	-	-	-	(SPW631)	-	-
	Motion detection (VMD)	-	no*13	yes	-	-	-	-	-	-	-	-	-	-	-	-
WJ-ND400K (V6.10) *14 (Discontinued model)	MJPEG	yes	yes*15	yes	-	-	-	(SPV781/SPV781)	yes	-	-	(S1531)	yes	yes	-	(S1131)
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes*15,*18,*19	yes*18	-	-	-	(SPV781/SPV781)*15,*19	yes*15,*19	-	-	(S1531)	yes	yes	yes	(S1131)
	H.265	yes	-	-	-	-	-	no	-	-	-	no	-	no	-	no
	Audio *8	yes	yes*15	yes	-	-	-	(SPV781/SPV781)	yes	-	-	(S1531)	yes	yes	-	(S1131)
	PTZ	-	yes*15	yes	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes*15	yes	-	-	-	(SPV781/SPV781)	yes	-	-	(S1531)	yes	yes	-	(S1131)
WJ-ND300A (V5.20) *4, *14 (Discontinued model)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	(SP305) *2	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-ND200 (V3.35) *4, *14 (Discontinued model)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	(SP305) *2	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio *8*11	-	-	-	-	-	-	-	-	-	-	-	-	(SP305)	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

[substitute model or camera classification] : Register as a substitute model or a camera classification.  
 \*1 : Only for remote PTZ camera.  
 \*2 : Support less than 1920x1080, including 1600x1200, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality:5-9 and the frame rate:up to 5fps.  
 \*3 : Each recorder supports only wireline connection.  
 \*4 : Displaying 16:9 is not supported on a NDK browser.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Support G.726 and 32kbps.  
 \*11 : This function is supported only when playing back.  
 \*12 : Supported up to 30 fps.  
 \*13 : When using WV-SFV481/WV-SFN480 with WJ-NV200, recording stops for about 10 seconds at the time of a screen change in a main monitor.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SPV781L, SPV781, SFV481, SFN480 support will be only 1-8ch.  
 \*17 : The fish-eye dewarp function on the main monitor is supported.  
 \*18 : The fish-eye dewarp function is supported by using the management software(WM-ASM200, WV-ASC370).  
 \*19 : Support maximum bitrate is 14Mbps.  
 \*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 cameras  
 \*21 : Support less than 1280x720 for WV-X511N  
 \*22 : Transmission format must be switched from H.265(Factory default) to H.264 by connecting from web browser  
 \*23 : Support G.726/32kbps and AAC-LC/64kbps.  
 \*24 : Supported image capture sizes are 4K(3840x2160), WQHD(2560x1440), HD(1920x1080) and HD(1280x720).  
 \*25 : Support 640x480  
 \*26 : Support 1920x1080, 1280x720 and 1280x960. Supported up to 30 fps  
 \*27 : WV-V170 additionally supports 3840x2160, 2048x1536, 2560x1920, 4000x3000(15fps).  
 \*28 : Support G.726.  
 \*29 : Support 640x480 and 320x240.  
 \*30 : Support 3840x2160, 1920x1080, 1280x720, 2560x1920, 2048x1536 and 1280x960 for WV-V1170.  
 \*31 : The supported camera firmware is V1.10 or later.

	Function	WV-S1132/S1131/S1112/S1111	WV-U1142A/U1132A/U1130A	WV-U1142/U1132/U1130	WV-X2551LN/X2251L	WV-S2536L/S2536LN	WV-S2552L/S2252L	WV-S2550L/S2250L	WV-S2531LN/S2531LTN/S2511LN	WV-U2542L/U2540L/U2532L/U2530L	WV-U2542L/U2540L/U2532L/U2530L	WV-S2136/S2136L	WV-S2236L	WV-S2131L/S2131/S2130/S2111L/S21110	WV-S2231L/S2211L	WV-U2142L/U2142LA/U2140L/U2140LA/U2132L/U2130LA
WJ-NU101K/KG WJ-NU201K/KG WJ-NU300K/KG WJ-NU301K/KG (V1.60) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes *31	yes	yes	yes	yes	yes	yes	yes	yes *31	yes	yes	yes	yes
	Audio *32	yes	-	-	-	yes	yes	yes	yes	yes	yes	-	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX400 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes *31	yes	yes	yes	yes	yes	yes	yes	yes *31	yes	yes	yes	yes
	Audio	yes *23	-	-	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	-	-	yes *23	yes *23	yes *23	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX300 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes *31	yes	yes	yes	yes	yes	yes	yes	yes *31	yes	yes	yes	yes
	Audio	yes *23	-	-	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	-	-	yes *23	yes *23	yes *23	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX200 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes *31	yes	yes	yes	yes	yes	yes	yes	yes *31	yes	yes	yes	yes
	Audio	yes *23	-	-	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	-	-	yes *23	yes *23	yes *23	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX100 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes *31	yes	yes	yes	yes	yes	yes	yes	yes *31	yes	yes	yes	yes
	Audio	yes *23	-	-	yes *23	yes *23	yes *23	yes *23	yes *23	yes *23	-	-	yes *23	yes *23	yes *23	yes *23
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NV300 (V2.30) *14  (Discontinued model)	MJPEG	yes	-	-	-	[S2531]	-	yes	yes	yes	yes	-	[S2131]	[S2231]	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	-	-	-	[S2531]	-	yes	yes	yes	yes	-	[S2131]	[S2231]	yes	yes
	H.265	no	-	-	-	-	-	no	no	no	no	-	-	no	no	no
	Audio *8	yes	-	-	-	[S2531]	-	yes	yes	yes	yes	-	[S2131]	[S2231]	yes	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	-	-	-	[S2531]	-	yes	yes	yes	yes	-	[S2131]	[S2231]	yes	yes
WJ-NV200 (V2.60) *14  (Discontinued model)	MJPEG	[SPN631]	-	-	-	-	-	-	[SPN631]	-	-	-	-	[SPN631]	[SPN631]	[SPN631]
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	[SPN631]*22	-	-	-	-	-	-	[SPN631]*22	-	-	-	-	[SPN631]*22	[SPN631]*22	-
	H.265	no	-	-	-	-	-	no	no	no	no	-	-	no	no	no
	Audio *8	[SPN631]	-	-	-	-	-	-	[SPN631]	-	-	-	-	[SPN631]	[SPN631]	[SPN631]
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	[SPN631]	-	-	-	-	-	-	[SPN631]	-	-	-	-	[SPN631]	[SPN631]	[SPN631]
WJ-ND400K (V6.10) *14  (Discontinued model)	MJPEG	yes	-	-	-	[S2531]	-	yes	yes	yes	yes	-	[S2131]	[S2231]	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	-	-	-	[S2531]	-	yes	yes	yes	yes	-	[S2131]	[S2231]	yes	yes
	H.265	no	-	-	-	no	-	no	no	no	no	-	no	no	no	no
	Audio *8	yes	-	-	-	[S2531]	-	yes	yes	yes	yes	-	[S2131]	[S2231]	yes	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	-	-	-	[S2531]	-	yes	yes	yes	yes	-	[S2131]	[S2231]	yes	yes
WJ-ND300A (V5.20) *4, *14  (Discontinued model)	MJPEG	[SP305] *2	-	-	-	-	-	-	[SP305] *2	-	-	-	-	[SP305] *2	[SP305] *2	[SP305] *2
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-ND200 (V3.35) *4, *14  (Discontinued model)	MJPEG	[SP305] *2	-	-	-	-	-	-	[SP305] *2	-	-	-	-	[SP305] *2	[SP305] *2	[SP305] *2
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio *8*11	[SP305]	-	-	-	-	-	-	[SP305]	-	-	-	-	[SP305]	[SP305]	[SP305]
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

[substitute model or camera classification] : Register as a substitute model or a camera classification.  
 \*1 : Only for remote PTZ camera.  
 \*2 : Support less than 1920x1080, including 1600x1200, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality:5-9 and the frame rate:up to 5fps.  
 \*3 : Each recorder supports only wireline connection.  
 \*4 : Displaying 16:9 is not supported on a NDK browser.  
 \*5 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Support G.726 and 32kbps.  
 \*11 : This function is supported only when playing back.  
 \*12 : Supported up to 30 fps.  
 \*13 : When using WV-SPV481/WV-SPN480 with WJ-NV200, recording stops for about 10 seconds at the time of a screen change in a main monitor.  
 \*14 : Streams of H.265(4) and H.265(9) are not supported.  
 \*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SPV781L, SPV781L, SPV481, SPN480 support will be only 1-8ch.  
 \*17 : The fish-eye dewarp function on the main monitor is supported.  
 \*18 : The fish-eye dewarp function is supported by using the management software(WV-ASM200, WV-ASC370).  
 \*19 : Support maximum bitrate is 14Mbps.  
 \*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 cameras  
 \*21 : Support less than 1280x720 for WV-S511N  
 \*22 : Transmission format must be switched from H.265(Factory default) to H.264 by connecting from web browser  
 \*23 : Support G.726/32kbps and AAC-LC/64kbps.  
 \*24 : Supported image capture sizes are 4K(UHD/3840x2160), WQHD(2560x1440), HD(1920x1080) and HD(1280x720).  
 \*25 : Support 640x480  
 \*26 : Support 1920x1080, 1280x720 and 1280x960. Supported up to 30 fps  
 \*27 : WV-V1170 additionally supports 3840x2160, 2048x1536, 2560x1920, 4000x3000(15fps).  
 \*28 : Support G.726.  
 \*29 : Support 640x480 and 320x240.  
 \*30 : Support 3840x2160, 1920x1080, 1280x720, 2560x1920, 2048x1536 and 1280x960 for WV-V1170.  
 \*31 : The supported camera firmware is V1.10 or later.

	Function	WV-U2142L/U2140L/U2132L/U2130L	WV-S3511L	WV-S3511L	WV-S352LM/S3512LM	WV-S3131L	WV-S3111L	WV-V1330LK	WV-V2530LK	WV-V1170	WV-V1330LL/V2530L1	WV-V6430L	WV-SB111M/SB111M	WV-SW598/SW598A/SC588/SC588A	WV-SW397/SW397A/SW397B/SC387/SC387A	WV-SW396A/SW395A		
WJ-N1101K/KG WJ-N1201K/KG WJ-N1301K/KG (V1.60) *20	MJPEG	yes	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	no	
	H.264	-	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
	H.265	yes *31	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	no	
	Audio *32	-	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))
PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
WJ-NX400 (V5.10) *20	Motion detection (VMD)	yes	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
	MJPEG	yes	yes	yes	-	yes	yes	yes *25	yes *25	yes *25	yes *25	yes *25	-	-	-	-	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	no	
	H.264	-	yes	yes	-	yes	yes	yes *26	yes *26	yes *26*27	yes *26	yes *26	-	-	-	-	yes	
	H.265	yes *31	yes	yes	-	yes	yes	yes *26	yes *26	yes *26*27	yes *26	yes *26	-	-	-	-	-	yes
Audio	-	yes *23	yes *23	-	yes *23	yes *23	-	yes *28	yes *28	-	yes *28	-	-	yes *8	yes	-	yes	
PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	
WJ-NX300 (V5.10) *20	Motion detection (VMD)	yes	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
	MJPEG	yes	yes	yes	-	yes	yes	yes *25	yes *25	yes *25	yes *25	yes *25	-	-	-	-	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	no	
	H.264	-	yes	yes	-	yes	yes	yes *26	yes *26	yes *26*27	yes *26	yes *26	-	-	-	-	yes	
	H.265	yes *31	yes	yes	-	yes	yes	yes *26	yes *26	yes *26*27	yes *26	yes *26	-	-	-	-	-	yes
Audio	-	yes *23	yes *23	-	yes *23	yes *23	-	yes *28	yes *28	-	yes *28	-	-	yes *8	yes	-	yes	
PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	
WJ-NX200 (V5.10) *20	Motion detection (VMD)	yes	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
	MJPEG	yes	yes	yes	-	yes	yes	yes *25	yes *25	yes *25	yes *25	yes *25	-	-	-	-	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	no	
	H.264	-	yes	yes	-	yes	yes	yes *26	yes *26	yes *26*27	yes *26	yes *26	-	-	-	-	yes	
	H.265	yes *31	yes	yes	-	yes	yes	yes *26	yes *26	yes *26*27	yes *26	yes *26	-	-	-	-	-	yes
Audio	-	yes *23	yes *23	-	yes *23	yes *23	-	yes *28	yes *28	-	yes *28	-	-	yes *8	yes	-	yes	
PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	
WJ-NV100 (V5.10) *20	Motion detection (VMD)	yes	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
	MJPEG	yes	yes	yes	-	yes	yes	yes *25	yes *25	yes *25	yes *25	yes *25	-	-	-	-	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	no	
	H.264	-	yes	yes	-	yes	yes	yes *26	yes *26	yes *26*27	yes *26	yes *26	-	-	-	-	yes	
	H.265	yes *31	yes	yes	-	yes	yes	yes *26	yes *26	yes *26*27	yes *26	yes *26	-	-	-	-	-	yes
Audio	-	yes *23	yes *23	-	yes *23	yes *23	-	yes *28	yes *28	-	yes *28	-	-	yes *8	yes	-	yes	
PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	
WJ-NV300 (V2.30) *14 (Discontinued model)	Motion detection (VMD)	yes	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
	MJPEG	-	yes	yes	-	yes	yes	yes *29	yes *29	yes *29	yes *29	yes *29	-	-	-	-	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	no	
	H.264	-	yes	yes	-	yes	yes	yes *26	yes *26	yes *26*30	yes *26	yes *26	-	-	-	-	yes	
	H.265	-	no	no	-	no	no	no	no	no	no	no	-	-	-	-	-	yes
Audio *8	-	yes	yes	-	yes	yes	-	yes	yes	-	yes	-	-	yes	yes	-	yes	
PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	
WJ-NV200 (V2.60) *14 (Discontinued model)	Motion detection (VMD)	-	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
	MJPEG	-	(SPV130)	(SPV110)	-	(SPV130)	(SPV110)	(SW558)*29	(SW559)*29	(SPV781L)*29	(SW558)*29	(SW558)*29	-	-	-	-	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	
	H.264	-	(SPV130)*22	(SPV110)*22	-	(SPV130)*22	(SPV110)*22	(SW558)*26	(SW559)*26	(SPV781L)*26	(SW558)*26	(SW558)*26	-	-	yes	yes	-	yes
	H.265	-	no	no	-	no	no	no	no	no	no	no	-	-	-	-	-	yes
Audio *8	-	(SPV130)	(SPV110)	-	(SPV130)	(SPV110)	-	(SW559)	(SPV781L)	-	(SW558)	-	-	yes	yes	-	yes	
PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	(SW558)	-	-	yes	
WJ-ND400K (V6.10) *14 (Discontinued model)	Motion detection (VMD)	-	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
	MJPEG	-	yes	yes	-	yes	yes	(SW558)*25	(SW559)*25	(SPV781L)*25	(SW558)*25	(SW558)*25	-	-	-	-	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	
	H.264	-	yes	yes	-	yes	yes	(SW558)*26	(SW559)*26	(SPV781L)*26*30	(SW558)*26	(SW558)*26	-	-	yes	yes	-	yes
	H.265	-	no	no	-	no	no	no	no	no	no	no	-	-	-	-	-	yes
Audio *8	-	yes	yes	-	yes	yes	-	(SW559)*28	(SPV781L)*28	-	(SW558)*28	-	-	yes	yes	-	yes	
PTZ	-	-	-	-	-	-	-	-	-	-	(SW558)	-	-	yes	yes	-	yes	
WJ-ND300A (V5.20) *4, *14 (Discontinued model)	Motion detection (VMD)	-	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
	MJPEG	-	(SF335)*2	(SF335)*2	-	(SF335)*2	(SF335)*2	-	-	-	-	-	-	-	(SC385)*2	(SC385)	-	(SC385)
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	(SC385)
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	(SC385)
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	(SC385)
Audio	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	(SC385)	
PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	(SC385)	
WJ-ND200 (V9.35) *4, *14 (Discontinued model)	Motion detection (VMD)	-	yes	yes	-	yes	yes	-	-	-	-	-	-	-	-	-	(I-PRO(A, PTZ))	
	MJPEG	-	(SF335)*2	(SF335)*2	-	(SF335)*2	(SF335)*2	-	-	-	-	-	-	-	(SC385)*2	(SC385)	-	(SC385)
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	(SC385)
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	(SC385)
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	(SC385)
Audio *8*11	-	(SF335)	(SF335)	-	(SF335)	(SF335)	-	-	-	-	-	-	-	(SC385)	(SC385)	-	(SC385)	
PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	(SC385)	(SC385)	-	(SC385)	
Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	(SC385)	

[substitute model or camera classification] : Register as a substitute model or a camera classification.  
 \*1 : Only for remote PTZ camera.  
 \*2 : Support less than 1920x1080, including 1600x1080, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality:5-9 and the frame rate:up to 5fps.  
 \*3 : Each recorder supports only wireline connection.  
 \*4 : Displaying 16:9 is not supported on a NDK browser.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Support G.726 and 32kbps.  
 \*11 : This function is supported only when playing back.  
 \*12 : Supported up to 30 fps.  
 \*13 : When using WV-SFV481/WV-SFV480 with WJ-NV200, recording stops for about 10 seconds at the time of a screen change in a main monitor.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SPV781L, SPV781, SPV481, SPV480 support will be only 1-8ch.  
 \*17 : The fish-eye dewarp function on the main monitor is supported.  
 \*18 : The fish-eye dewarp function is supported by using the management software(WV-ASM200, WV-ASC370).  
 \*19 : Support maximum bitrate is 14Mbps.  
 \*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 cameras  
 \*21 : Support less than 1280x720 for WV-S3511L  
 \*22 : Transmission format must be switched from H.265(Factor default) to H.264 by connecting from web browser  
 \*23 : Support G.726/32kbps and AAC-LC/8kbps.  
 \*24 : Supported image capture sizes are 4K(UHD/3840x2160), WQHD(2560x1440), HD(1920x1080) and HD(1280x720).  
 \*25 : Support 640x480  
 \*26 : Support 1920x1080, 1280x720 and 1280x640. Supported up to 30 fps  
 \*27 : WV-V1170 additionally supports 3840x2160, 2048x1536, 2560x1920, 4000x3000(15fps).  
 \*28 : Support G.726.  
 \*29 : Support 640x480 and 320x240.  
 \*30 : Support 3840x2160, 1920x1080, 1280x720, 2560x1920, 2048x1536 and 1280x640 for WV-V1170.  
 \*31 : The supported camera firmware is V1.10 or later.

	Function	WV-SW396/SW395/SC386/SC384	WV-SC385	WV-SPW631L/SPW631L	WV-SPW611L/SPW611	WV-SPW531L/SPW531A	WV-SPW532L/SPW532L	WV-SW316L/SW316	WV-SW314	WV-SPN611/SPN631	WV-SPN531/SPN531A	WV-SPN310/SPN311/SPN310A/SPN311A	WV-SP509	WV-SP508	WV-SP300 series	WV-SP105/SP102	
WJ-NU101K/KG WJ-NU201K/KG WJ-NU300K/KG WJ-NU301K/KG (V1.60) *20	MJPEG	(I-PRO(A, PTZ))	(I-PRO(A, PTZ))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(A, FIX))	(I-PRO(A, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(B, FIX))	(I-PRO(B, FIX))	(I-PRO(A, FIX))	(I-PRO(A, FIX))	
	MPEG4	no	no	-	-	-	-	no	no	-	-	-	-	-	no	-	
	H.264	(I-PRO(A, PTZ))	(I-PRO(A, PTZ))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(A, FIX))	(I-PRO(A, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(B, FIX))	(I-PRO(B, FIX))	(I-PRO(A, FIX))	(I-PRO(A, FIX))	
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Audio *32	no	no	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(A, FIX))	-	-	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	no	-	no	-
	PTZ	(I-PRO(A, PTZ))	(I-PRO(A, PTZ))	-	-	-	-	-	-	-	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	-	-	-	-
	Motion detection (VMD)	(I-PRO(A, PTZ))	(I-PRO(A, PTZ))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(A, FIX))	(I-PRO(A, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(C, FIX))	(I-PRO(B, FIX))	(I-PRO(B, FIX))	(I-PRO(A, FIX))	(I-PRO(A, FIX))
WJ-NX400 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	no	no	-	-	-	-	no	no	-	-	-	-	-	no	-	
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	Audio	yes	yes	yes *23	yes *23	yes *23	-	yes	-	yes *23	yes *23	yes	yes *8	-	yes	-	
	PTZ	yes	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
WJ-NX300 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	no	no	-	-	-	-	no	no	-	-	-	-	-	no	-	
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	Audio	yes	yes	yes *23	yes *23	yes *23	-	yes	-	yes *23	yes *23	yes	yes *8	-	yes	-	
	PTZ	yes	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
WJ-NX200 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	no	no	-	-	-	-	no	no	-	-	-	-	-	no	-	
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	Audio	yes	yes	yes *23	yes *23	yes *23	-	yes	-	yes *23	yes *23	yes	yes *8	-	yes	-	
	PTZ	yes	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
WJ-NX100 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	no	no	-	-	-	-	no	no	-	-	-	-	-	no	-	
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	Audio	yes	yes	yes *23	yes *23	yes *23	-	yes	-	yes *23	yes *23	yes	yes *8	-	yes	-	
	PTZ	yes	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
WJ-NV300 (V2.30) *14 (Discontinued model)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	no	no	-	-	-	-	no	no	-	-	-	-	-	no	-	
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Audio *8	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	PTZ	yes	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
WJ-NV200 (V2.60) *14 (Discontinued model)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	yes	yes	
	H.264	yes	yes	yes*12	yes*12	yes*12	yes*12	yes	yes	yes*12	yes*12	yes*12	yes	yes	yes	yes	
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Audio *8	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	PTZ	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
WJ-ND400K (V6.10) *14 (Discontinued model)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	yes	yes	
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	Audio *8	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	PTZ	yes	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
WJ-ND300A (V5.20) *4, *14 (Discontinued model)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	[SC385]	yes	[SP305] *2	[SP305]	[SP305] *2	[SP305]	[SP305]	[SP102]	[SP305] *2	[SP305]	[SP305] *2	[SP305] *2	[SP305] *2	[SP102] *2	yes	
	H.264	[SC385]	yes	-	-	-	-	[SP305]	[SP305]	-	-	-	-	-	yes	yes	
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Audio	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	PTZ	[SC385]	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
WJ-ND200 (V3.35) *4, *14 (Discontinued model)	MJPEG	[SC385]	yes	[SP305] *2	[SP305]	[SP305] *2	[SP305]	[SP305]	[SP305]	[SP305] *2	[SP305]	[SP305] *2	[SP305] *2	[SP305] *2	[SP305] *2	yes	
	MPEG4	[SC385]	yes	-	-	-	-	[SP305]	[SP305]	-	-	-	-	-	yes	yes	
	H.264	[SC385]	yes	-	-	-	-	[SP305]	[SP305]	-	-	-	-	-	yes	yes	
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Audio *8*11	[SC385]	yes	[SP305]	[SP305]	[SP305]	-	[SP305]	-	[SP305]	[SP305]	[SP305]	[SP305]	[SP305]	yes	-	
	PTZ	[SC385]	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	

[substitute model or camera classification] : Register as a substitute model or a camera classification.  
 \*1 : Only for remote PTZ camera.  
 \*2 : Support less than 1920x1080, including 1600x1200, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality:5-9 and the frame rate:up to 5fps.  
 \*3 : Each recorder supports only wireline connection.  
 \*4 : Displaying 16:9 is not supported on a NDK browser.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Support G.726 and 32kbps.  
 \*11 : This function is supported only when playing back.  
 \*12 : Supported up to 30 fps.  
 \*13 : When using WV-SPV481/WV-SPV480 with WJ-NV200, recording stops for about 10 seconds at the time of a screen change in a main monitor.  
 \*14 : Streams of H.265(4) and H.265(4) are not supported.  
 \*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SPV781L, SPV481, SPV480 support will be only 1-8ch.  
 \*17 : The fish-eye dewarp function on the main monitor is supported.  
 \*18 : The fish-eye dewarp function is supported by using the management software(WV-ASM200, WV-ASC370).  
 \*19 : Support maximum bitrate is 14Mbps.  
 \*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 cameras  
 \*21 : Support less than 1280x720 for WV-MS11W  
 \*22 : Transmission format must be switched from H.265(Factor default) to H.264 by connecting from web browser  
 \*23 : Support G.726/32kbps and AAC-LC/8kbps.  
 \*24 : Supported image capture size are 4K(3840x2160), WQHD(2560x1440), HD(1920x1080) and HD(1280x720).  
 \*25 : Support 640x480  
 \*26 : Support 1920x1080, 1280x720 and 1280x960. Supported up to 30 fps  
 \*27 : WV-V1170 additionally supports 3840x2160, 2048x1536, 2560x1920, 4000x3000(15fps).  
 \*28 : Support G.726.  
 \*29 : Support 640x480 and 320x240.  
 \*30 : Support 3840x2160, 1920x1080, 1280x720, 2048x1536 and 1280x960 for WV-V1170.  
 \*31 : The supported camera firmware is V1.10 or later.

	Function	WV-NP502	WV-SFN611/SFN631L/SFR611L/SFR631L/SFV611L/SFV631L	WV-SFN531/SFR531L/SFV531	WV-SFN311A/SFR310A/SFR311A/SFR310A/SFV311A/SFV310A	WV-SFN311/SFR310/SFN311L/SFR310L/SFV311/SFV310	WV-SW559/SF549/SF539	WV-SW558/SF548/SF538	WV-SW555/SF535/SF346/SF342	WV-SF330 series	WV-NW502S	WV-SFV130/SFV110	WV-SFN130/SFN110	WV-SW158/SF138	WV-SW155/SW152/SW15	WV-SF135/SF132	
WJ-NU101K/KG WJ-NU201K/KG WJ-NU301K/KG (V1.00) *20	MJPEG	(I-PRO(A_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(B_FIX))	(I-PRO(B_FIX))	(I-PRO(A_FIX))	(I-PRO(A_FIX))	(I-PRO(A_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(B_FIX))	(I-PRO(A_FIX))	(I-PRO(A_FIX))	
	MPEG4	-	-	-	-	-	-	-	no	no	-	-	-	-	-	-	
	H.264	(I-PRO(A_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(B_FIX))	(I-PRO(B_FIX))	(I-PRO(A_FIX))	(I-PRO(A_FIX))
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio *32	no	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	no	-	no	no	(I-PRO(C_FIX))	(I-PRO(C_FIX))	no	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(B_FIX))	(I-PRO(B_FIX))	(I-PRO(A_FIX))	(I-PRO(A_FIX))	(I-PRO(A_FIX))	(I-PRO(C_FIX))	(I-PRO(C_FIX))	(I-PRO(B_FIX))	(I-PRO(A_FIX))	(I-PRO(A_FIX))
WJ-NX400 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	-	-	-	-	-	-	-	no	no	-	-	-	-	-	-	
	H.264	yes	-	yes	-	yes	-	yes	-	-	yes	-	yes	-	yes	yes	
	H.265	yes	-	yes	-	yes	-	yes	-	-	yes	-	yes	-	yes	yes	
	Audio	yes *8	yes *23	yes *23	yes	yes	yes *8	-	-	yes	yes *8	yes *23	yes *23	yes *8	-	-	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX300 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	-	-	-	-	-	-	-	no	no	-	-	-	-	-	-	
	H.264	yes	-	yes	-	yes	-	yes	-	-	yes	-	yes	-	yes	yes	
	H.265	yes	-	yes	-	yes	-	yes	-	-	yes	-	yes	-	yes	yes	
	Audio	yes *8	yes *23	yes *23	yes	yes	yes *8	-	-	yes	yes *8	yes *23	yes *23	yes *8	-	-	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX200 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	-	-	-	-	-	-	-	no	no	-	-	-	-	-	-	
	H.264	yes	-	yes	-	yes	-	yes	-	-	yes	-	yes	-	yes	yes	
	H.265	yes	-	yes	-	yes	-	yes	-	-	yes	-	yes	-	yes	yes	
	Audio	yes *8	yes *23	yes *23	yes	yes	yes *8	-	-	yes	yes *8	yes *23	yes *23	yes *8	-	-	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NX100 (V5.10) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	-	-	-	-	-	-	-	no	no	-	-	-	-	-	-	
	H.264	yes	-	yes	-	yes	-	yes	-	-	yes	-	yes	-	yes	yes	
	H.265	yes	-	yes	-	yes	-	yes	-	-	yes	-	yes	-	yes	yes	
	Audio	yes *8	yes *23	yes *23	yes	yes	yes *8	-	-	yes	yes *8	yes *23	yes *23	yes *8	-	-	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NV300 (V2.30) *14 (Discontinued model)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	-	-	-	-	-	-	-	no	no	-	-	-	-	-	-	
	H.264	yes	-	yes	-	yes	-	yes	-	-	yes	-	yes	-	yes	yes	
	H.265	yes	-	yes	-	yes	-	yes	-	-	yes	-	yes	-	yes	yes	
	Audio *8	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-NV200 (V2.60) *14 (Discontinued model)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	yes	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes	
	H.264	yes	yes*12	yes*12	yes*12	yes*12	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Audio *8	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	PTZ	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WJ-ND400K (V6.10) *14 (Discontinued model)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	yes	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes	
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	Audio *8	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
WJ-ND300A (V5.20) *4, *14 (Discontinued model)	MJPEG	yes *2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	
	MPEG4	yes	-	-	-	-	-	-	(SF335)	yes	yes	yes	yes	yes	yes	(SF335)	
	H.264	yes	-	-	-	-	-	-	(SF335)	yes	yes	yes	yes	yes	yes	(SF335)	
	H.265	-	-	-	-	-	-	-	(SF335)	yes	yes	yes	yes	yes	yes	(SF335)	
	Audio	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
WJ-ND200 (V3.35) *4, *14 (Discontinued model)	MJPEG	yes *2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	(SF335)*2	
	MPEG4	yes	-	-	-	-	-	-	(SF335)	yes	yes	yes	yes	yes	yes	(SF335)	
	H.264	yes	-	-	-	-	-	-	(SF335)	yes	yes	yes	yes	yes	yes	(SF335)	
	H.265	-	-	-	-	-	-	-	(SF335)	yes	yes	yes	yes	yes	yes	(SF335)	
	Audio *8*11	yes	(SF335)	(SF335)	(SF335)	(SF335)	(SF335)	(SF335)	(SF335)	yes	yes	(SF335)	(SF335)	(SF335)	(SF335)	(SF335)	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	

[substitute model or camera classification] : Register as a substitute model or a camera classification.  
 \*1 : Only for remote PTZ camera.  
 \*2 : Support less than 1920x1080, including 1600x1200, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality:5-9 and the frame rate:up to 5fps.  
 \*3 : Each recorder supports only wireline connection.  
 \*4 : Displaying 16:9 is not supported on a NDK browser.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Support G.726 and 32kpbs.  
 \*11 : This function is supported only when playing back.  
 \*12 : Supported up to 30 fps.  
 \*13 : When using WV-SFV481/WV-SFN480 with WJ-NV200, recording stops for about 10 seconds at the time of a screen change in a main monitor.  
 \*14 : Streams of H.265(4) and H.265(9) are not supported.  
 \*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SFV781L, SPV781L, SFV481, SFN480 support will be only 1-8ch.  
 \*17 : The fish-eye dewarp function on the main monitor is supported.  
 \*18 : The fish-eye dewarp function is supported by using the management software(WV-ASM200, WV-ASC970).  
 \*19 : Support maximum bitrate is 14Mbps.  
 \*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 cameras  
 \*21 : Support less than 1280x720 for WV-MS11W  
 \*22 : Transmission format must be switched from H.265(Factory default) to H.264 by connecting from web browser  
 \*23 : Support G.726/32kpbs and AAC-LC/9.6kpbs.  
 \*24 : Supported image capture sizes are 4K(3840x2160), WQHD(2560x1440), HD(1920x1080) and HD(1280x720).  
 \*25 : Support 640x480  
 \*26 : Support 1920x1080, 1280x720 and 1280x660. Supported up to 30 fps  
 \*27 : WV-V1170 additionally supports 3840x2160, 2048x1536, 2560x1920, 4000x3000(15fps).  
 \*28 : Support G.726.  
 \*29 : Support 640x480 and 320x240.  
 \*30 : Support 3840x2160, 1920x1080, 1280x720, 2048x1536 and 1280x660 for WV-V1170.  
 \*31 : The supported camera firmware is V1.10 or later.



	Function	WV-SW175/SW172/ST165/ST162	WV-SW174W*3	BB-HCM7 series	BB-HCM5 series	WV-SMR10/SMR10N3	WJ-GXE500	WJ-GXE100
WJ-NU101K/KG WJ-NU201K/KG WJ-NU300K/KG WJ-NU301K/KG (V1.60) *20	MJPEG	[I-PRO(A, PTZ)]	[I-PRO(A, PTZ)]	-	-	-	yes	yes
	MPEG4	-	-	-	-	-	no	-
	H.264	[I-PRO(A, PTZ)]	[I-PRO(A, PTZ)]	-	-	-	yes	yes
	H.265	-	-	-	-	-	-	-
	Audio *8	-	-	-	-	-	no	-
	PTZ	[I-PRO(A, PTZ)]	[I-PRO(A, PTZ)]	-	-	-	yes	yes
WJ-NX400 (V5.10) *20	Motion detection (VMD)	[I-PRO(A, PTZ)]	[I-PRO(A, PTZ)]	-	-	-	yes	yes
	MJPEG	yes	yes	yes	yes	-	yes	yes
	MPEG4	-	-	no	-	-	no	-
	H.264	yes	yes	yes	-	-	yes	yes
	H.265	-	-	-	-	-	-	-
	Audio	yes *8	yes *8	yes *8	-	yes	yes (ch1) *8	-
WJ-NX300 (V5.10) *20	PTZ	yes	yes	yes *1	yes *1	-	yes	yes
	Motion detection (VMD)	yes	yes	-	-	-	yes	yes
	MJPEG	yes	yes	yes	yes	-	yes	yes
	MPEG4	-	-	no	-	-	no	-
	H.264	yes	yes	yes	-	-	yes	yes
	H.265	-	-	-	-	-	-	-
WJ-NX200 (V5.10) *20	Audio	yes *8	yes *8	yes *8	-	yes	yes (ch1) *8	-
	PTZ	yes	yes	yes *1	yes *1	-	yes	yes
	Motion detection (VMD)	yes	yes	-	-	-	yes	yes
	MJPEG	yes	yes	yes	yes	-	yes	yes
	MPEG4	-	-	no	-	-	no	-
	H.264	yes	yes	yes	-	-	yes	yes
WJ-NX100 (V5.10) *20	H.265	-	-	-	-	-	-	-
	Audio	yes *8	yes *8	yes *8	-	yes	yes (ch1) *8	-
	PTZ	yes	yes	yes *1	yes *1	-	yes	yes
	Motion detection (VMD)	yes	yes	-	-	-	yes	yes
	MJPEG	yes	yes	yes	yes	-	yes	yes
	MPEG4	-	-	no	-	-	no	-
WJ-NV300 (V2.30) *14 (Discontinued model)	H.264	yes	yes	yes	-	-	yes	yes
	H.265	-	-	-	-	-	-	-
	Audio *8	yes	yes	yes	-	yes	yes (ch1)	-
	PTZ	yes	yes	yes *1	yes *1	-	yes	yes
	Motion detection (VMD)	yes	yes	-	-	-	yes	yes
	MJPEG	yes	yes	yes	yes	-	yes	yes
WJ-NV200 (V2.60) *14 (Discontinued model)	MPEG4	-	-	yes	yes	-	yes	yes
	H.264	yes	yes	yes	-	-	yes	yes
	H.265	-	-	-	-	-	-	-
	Audio *8	yes	yes	yes	-	yes	yes (ch1)	-
	PTZ	yes	yes	yes *1	yes *1	-	yes	yes
	Motion detection (VMD)	yes	yes	-	-	-	yes	yes
WJ-ND400K (V6.10) *14 (Discontinued model)	MJPEG	yes	yes	yes	yes	-	yes	yes
	MPEG4	-	-	yes	-	-	yes	-
	H.264	yes	yes	yes	-	-	yes	yes
	H.265	-	-	-	-	-	-	-
	Audio *8	yes	yes	yes	-	yes	yes (ch1)	-
	PTZ	yes	yes	yes *1	yes *1	-	yes	yes
WJ-ND300A (V5.20) *4, *14 (Discontinued model)	Motion detection (VMD)	yes	yes	-	-	-	yes	yes
	MJPEG	[SC385]	[SC385]	yes	-	-	yes	[GXE500 ch1]
	MPEG4	-	-	yes	-	-	yes	-
	H.264	[SC385]	[SC385]	yes	-	-	yes	[GXE500 ch1]
	H.265	-	-	-	-	-	-	-
	Audio	[SC385]	[SC385]	yes *1	yes *1	-	yes	[GXE500 ch1]
WJ-ND200 (V3.35) *4, *14 (Discontinued model)	PTZ	[SC385]	[SC385]	yes *1	yes *1	-	yes	[GXE500 ch1]
	Motion detection (VMD)	-	-	-	-	-	-	-
	MJPEG	[SC385]	[SC385]	yes	yes	-	yes	[GXE500 ch1]
	MPEG4	-	-	yes	-	-	yes	-
	H.264	[SC385]	[SC385]	yes	-	-	yes	[GXE500 ch1]
	H.265	-	-	-	-	-	-	-

[substitute model or camera classification] : Register as a substitute model or a camera classification.  
 \*1 : Only for remote PTZ camera.  
 \*2 : Support less than 1920x1080, including 1600x1200, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality:5-9 and the frame rate:up to 5fps.  
 \*3 : Each recorder supports only wireline connection.  
 \*4 : Displaying 16:9 is not supported on a HDR browser.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Support G.726 and 32kbps.  
 \*11 : This function is supported only when playing back.  
 \*12 : Supported up to 30 fps.  
 \*13 : When using WV-SFV481/WV-SFN480 with WJ-NV200, recording stops for about 10 seconds at the time of a screen change in a main monitor.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SPV781L, SPV781, SPV481, SFN480 support will be only 1-8ch.  
 \*17 : The fish-eye dewarp function on the main monitor is supported.  
 \*18 : The fish-eye dewarp function is supported by using the management software(WM-ASM200, WV-ASC370).  
 \*19 : Support maximum bitrate is 14Mbps.  
 \*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 camera  
 \*21 : Support less than 1280x720 for WV-V5511N  
 \*22 : Transmission format must be switched from H.265(Factory default) to H.264 by connecting from web browser  
 \*23 : Support G.726/32kbps and AAC-LC/8kbps.  
 \*24 : Supported image capture sizes are 4K(3840x2160), WQHD(2560x1440), FHD(1920x1080) and HD(1280x720).  
 \*25 : Support 640x480  
 \*26 : Support 1920x1080, 1280x720 and 1280x960. Supported up to 30 fps  
 \*27 : WV-V1170 additionally supports 3840x2160, 2048x1536, 2560x1920, 4000x3000(15fps).  
 \*28 : Support G.726.  
 \*29 : Support 640x480 and 320x240.  
 \*30 : Support 3840x2160, 1920x1080, 1280x720, 2560x1920, 2048x1536 and 1280x960 for WV-V1170.  
 \*31 : The supported camera firmware is V1.10 or later.

	Function	WV-PM500	WV-S61501-Z1	WV-S61300-ZY/ZYG	WV-S65501-Z1/Z1G	WV-S65300-ZY/ZYG	WV-S65301-Z1/Z1G Z1-1/Z1S	WV-S65302-Z2/Z2G Z2-1	WV-U61300- ZY/ZYG/ZYV	WV-U65300-ZY/ZYG	WV-S65340- Z2N/Z4N/Z2K/Z4K /Z2K3/Z2G/Z4G/Z2 Z2N1/Z4/Z4N1	WV-S61302-Z4	WV-S25500-F3L/F6L	WV-S22500-F3L/F6L	WV-S15500-F3L/F6L	WV-U61301-Z1/Z2
WV-ASM300 (V6.00)	MPEG	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	Audio*23	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
Direct connection to camera	PTZ	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	-	-
	RTP over HTTP	-	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASM200 (V5.10) *24	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASM100 (Ver8.00) *5,*14,*24	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASC970 (Ver19.00)	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-GXD400 (Ver2.21) *6,*14,*20	MPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BB-HNP17 (Ver4.06)	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.  
 \*1 : Only for remote PTZ cameras.  
 \*5 : WV-ASM100 does not support displaying 16:9.  
 \*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Supported G.726.  
 \*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*16 : When displaying H.264 streaming of 2892x2992 resolution, please use a 64 bit OS and 4GB or more memory.  
 \*19 : Supported maximum bitrate is 14Mbps.  
 \*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.  
 \*21 : WV-ASM200 does not support wiper function.  
 \*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.  
 \*23 : Supported G.726 or AAC.  
 \*24 : Please connect to the camera from the PC browser and change the authentication method from Digest to Digest or Basic.  
 \*25 : Video display may take some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.  
 \*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh interval(PPEG). Less than 1fps cannot be selected.  
 \*27 : Restrictions is still under study. Will be updated.  
 \*28 : Support G.726 for WV-V2530K/V1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.  
 \*29 : Support WV-CU950/CU980

	Function	WV-U65301-Z1/Z1G	WV-U65302-Z2/Z2G	WV-S61301-Z1/Z2	WV-S71300-F3	WV-S25700-V2L/V2LN/V2LG/V2LN1	WV-S25600-V2L/V2LN/V2LG	WV-S25500-V3L/V3LN/V3LG/V3LN1	WV-S22700-V2L/V2LG/V2L1/V2L1Q	WV-S22600-V2L/V2LG	WV-S22500-V3L/V3LG/V3L1	WV-S15700-V2L/V2LN/V2LK	WV-S15600-V2L/V2LN	WV-S15500-V3L/V3LN/V3LN1/V3LK	WV-S8573L/S8573LG/S8574L/S8574LG	WV-S8563L/S8563LG/S8564L/S8564LG
WV-ASM300 (V6.00)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio*23	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Direct connection to camera	PTZ	-	yes	yes	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASM200 (V5.10) *24	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASM100 (Ver8.00) *5,*14,*24	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASC970 (Ver19.00)	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-GXD400 (Ver2.21) *6,*14,*20	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264*25	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BB-HNP17 (Ver4.06)	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.  
 \*1 : Only for remote PTZ cameras.  
 \*5 : WV-ASM100 does not support displaying 16:9.  
 \*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Supported G.726.  
 \*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*16 : When displaying H.264 streaming of 2992x2992 resolution, please use a 64 bit OS and 4GB or more memory.  
 \*19 : Supported maximum bitrate is 14Mbps.  
 \*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.  
 \*21 : WV-ASM200 does not support wiper function.  
 \*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.  
 \*23 : Supported G.726 or AAC.  
 \*24 : Please connect to the camera from the PC browser and change the authentication method from Digest o Digest or Basic.  
 \*25 : Video display may take some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.  
 \*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh interval(PPEG). Less than 1fps cannot be selected.  
 \*27 : Restrictions is still under study. Will be updated.  
 \*28 : Support G.726 for WV-V2530K/V1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.  
 \*29 : Support WV-CU950/CU980

	Function	WV- S8543/S8543G/S8544/ S8544L/S8544LG	WV- X8571N/S8531N	WV- X8570N/S8530N	WV- X6533LN/X6533LNS/S6 S32LN/S6532LNS	WV- X6531N/X6531NS/ X6511N	WV-SUD638	WV-S6530N	WV- S6131/S6111/S6130	WV- X4573L/X4573LM	WV- X4471L/X4571L/ X4571LM	WV-X4172/X4173	WV-X4170	WV-S4556LM/S4556L/ S4156	WV-S4576LM/ S4576L	WV- S4551L/S4551LM/ S4151
WV-ASM300 (V6.00)	MJPEG	yes	no	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio*23	yes	yes (for X8571N)	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Direct connection to camera	PTZ	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	H.264	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
WV-ASM200 (V5.10) *24	H.265	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	PTZ	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	MJPEG	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
WV-ASM100 (Ver8.00) *5,*14,*24	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	H.265	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	yes*21	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	-	-	-	-	yes	yes	Unverified	Unverified	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	yes	yes	Unverified	Unverified	-	-	-	-	-	-	-
	H.264	-	-	-	-	yes	yes	Unverified	Unverified	-	-	-	-	-	-	-
	H.265	-	-	-	-	yes	yes	Unverified	Unverified	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	Audio*8	-	-	-	-	yes	yes	Unverified	Unverified	-	-	-	-	-	-	-
	PTZ	-	-	-	-	yes	yes	Unverified	Unverified	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	yes	yes	Unverified	Unverified	-	-	-	-	-	-	-
	MJPEG	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
WJ-GXD400 (Ver2.21) *6,*14,*20	H.264	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	H.265	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	Audio*9	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	PTZ	-	-	-	-	yes	yes	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	MJPEG	-	-	-	-	-	yes	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	H.265	-	-	-	-	yes	yes	yes	yes	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	yes	yes	-	-	-	-	-	-	-	-	-
BB-HNP17 (Ver4.06) (Discontinued model)	PTZ	-	-	-	-	-	yes	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	yes	-	-	-	-	-	-	-	-	-
	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264*25	-	-	-	-	-	yes	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.  
 \*1 : Only for remote PTZ cameras.  
 \*5 : WV-ASM100 does not support displaying 16:9.  
 \*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Supported G.726.  
 \*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*16 : When displaying H.264 streaming of 2992x2992 resolution, please use a 64 bit OS and 4GB or more memory.  
 \*19 : Supported maximum bitrate is 14Mbps.  
 \*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.  
 \*21 : WV-ASM200 does not support wiper function.  
 \*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.  
 \*23 : Supported G.726 or AAC.  
 \*24 : Please connect to the camera from the PC browser and change the authentication method from Digest to Digest or Basic.  
 \*25 : Video display may take some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.  
 \*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh interval(PPEG). Less than 1fps cannot be selected.  
 \*27 : Restrictions is still under study. Will be updated.  
 \*28 : Support G.726 for WV-V2530L/V1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.  
 \*29 : Support WV-CU950/CU980

	Function	WV-S4550L/S4550LM/S4150	WV-SF7481/SFN480*7	WV-SW458/SW458MA/SF438/SF448E*7	WV-X2571LN/X2271L	WV-X1571LN	WV-S2572L/S2272L/S1572L	WV-S2570L/S2270L/S1570L	WV-SFV781L/SPV781L	WV-X1551LN	WV-S1536L/S1536LN/S1536LTN	WV-S1552L	WV-S1550L	WV-S1531LN/S1531LTN/S1531LNS	WV-S1511LN	WV-U1542LA/U1532LA
WV-ASM300 (V6.00)	MPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes*17,*18	yes	yes	yes	yes	yes	yes*18	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	-	-	yes	yes	yes	yes	-	yes	yes	yes	yes	yes	yes	yes
	Audio*23	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Direct connection to camera	PTZ	yes	yes	yes	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG	Unverified	yes	yes	-	-	-	-	yes	-	-	-	-	yes	yes	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	Unverified	yes*17,*18	yes	-	-	-	-	yes*18	-	-	-	-	yes	yes	-
WV-ASM200 (V5.10) *24	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	Unverified	yes	yes	-	-	-	-	yes	-	-	-	-	yes	yes	-
	PTZ	Unverified	yes	yes	-	-	-	-	-	-	-	-	-	yes	yes	-
	RTP over HTTP	Unverified	yes	yes	-	-	-	-	yes	-	-	-	-	yes	yes	-
	MPEG	-	-	-	-	-	-	-	yes	-	-	-	-	-	-	-
WV-ASM100 (Ver8.00) *5,*14,*24	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	yes	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	yes	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG	Unverified	yes	yes	-	-	-	-	yes	-	-	-	-	yes	yes	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	Unverified	yes*17,*19	yes	-	-	-	-	yes*19	-	-	-	-	yes	yes	-
	H.265	Unverified	-	-	-	-	-	-	-	-	-	-	-	yes	yes	-
WV-ASC970 (Ver19.00)	Audio*8	Unverified	yes	yes	-	-	-	-	yes	-	-	-	-	yes	yes	-
	PTZ	Unverified	yes	yes	-	-	-	-	-	-	-	-	-	yes	yes	-
	RTP over HTTP	Unverified	yes	yes	-	-	-	-	yes	-	-	-	-	yes	yes	-
	MPEG	-	-	-	-	-	-	-	yes	-	-	-	-	yes	yes	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-GXD400 (Ver2.21) *6,*14,*20	H.264	-	-	-	-	-	-	-	yes	-	-	-	-	yes	yes	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*9	-	-	-	-	-	-	-	yes	-	-	-	-	yes	yes	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	MPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	yes	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	-	-	-	-	yes	-	-	-	-	-	-	-
BB-HNP17 (Ver4.06)	PTZ	-	yes	yes	-	-	-	-	yes*22	-	-	-	-	-	-	-
	RTP over HTTP	-	yes	yes	-	-	-	-	yes	-	-	-	-	-	-	-
	MPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.  
 \*1 : Only for remote PTZ cameras.  
 \*5 : WV-ASM100 does not support displaying 16:9.  
 \*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Supported G.726.  
 \*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*16 : When displaying H.264 streaming of 2992x2992 resolution, please use a 64 bit OS and 4GB or more memory.  
 \*19 : Supported maximum bitrate is 14Mbps.  
 \*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.  
 \*21 : WV-ASM200 does not support wiper function.  
 \*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.  
 \*23 : Supported G.726 or AAC.  
 \*24 : Please connect to the camera from the PC browser and change the authentication method from Digest o Digest or Basic.  
 \*25 : Video display may take some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.  
 \*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh interval(JPEG). Less than 1fps cannot be selected.  
 \*27 : Restrictions is still under study. Will be updated.  
 \*28 : Support G.726 for WV-V2530L/V1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.  
 \*29 : Support WV-CU950/CU980

	Function	WV-U1542L	WV-U1532L	WV-S1136	WV-S1132/S1131	WV-S1112/S1111	WV-U1142A/U1132A/U1130A	WV-U1142	WV-U1132/U1130	WV-X2551LN/X2251L	WV-S2552L/S2252L	WV-S2550L/S2250L	WV-S2531LN/S2531LTN	WV-S2511LN	WV-U2542LA/U2540LA/U2532LA/U2530LA	WV-U2542L/U2540L	
WV-ASM300 (V6.00)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	H.264	-	-	yes	yes	yes	yes	-	-	yes	yes	yes	yes	yes	yes	-	
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio*23	-	-	yes	yes	yes	yes	-	-	yes	yes	yes	yes	yes	yes	-	-
Direct connection to camera	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	MPEG4	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	yes	-	
	H.264	-	-	-	yes	yes	-	-	-	-	-	-	-	yes	-	-	
WV-ASM200 (V5.10) *24	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Audio*8	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	yes	-	-	-	
	RTP over HTTP	-	-	-	yes	yes	-	-	-	-	-	-	yes	-	-	-	
	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
WV-ASM100 (Ver8.00) *5,*14,*24	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	MJPEG	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
	MPEG4	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
	H.264	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
	H.265	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
WV-ASC970 (Ver19.00)	Audio*8	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	yes	yes	-	-	
	RTP over HTTP	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
	MJPEG	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
	MPEG4	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
WJ-GXD400 (Ver2.21) *6,*14,*20	H.264	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
	H.265	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
	Audio*9	-	-	-	yes	yes	-	-	-	-	-	-	yes	yes	-	-	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
BB-HNP17 (Ver4.06)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	H.264*25	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
(Discontinued model)	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	

Discontinued model might have the function which doesn't work.  
 \*1 : Only for remote PTZ cameras.  
 \*5 : WV-ASM100 does not support displaying 16:9.  
 \*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Supported G.726.  
 \*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*16 : When displaying H.264 streaming of 2992x2992 resolution, please use a 64 bit OS and 4GB or more memory.  
 \*19 : Supported maximum bitrate is 14Mbps.  
 \*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.  
 \*21 : WV-ASM200 does not support wiper function.  
 \*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.  
 \*23 : Supported G.726 or AAC.  
 \*24 : Please connect to the camera from the PC browser and change the authentication method from Digest o Digest or Basic.  
 \*25 : Video display may take some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.  
 \*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh interval(PPEG). Less than 1fps cannot be selected.  
 \*27 : Restrictions is still under study. Will be updated.  
 \*28 : Support G.726 for WV-V2530L/V1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.  
 \*29 : Support WV-CU950/CU980

	Function	WV-U2532L/U2530L	WV-S2136/S2136L	WV-S2236L	WV-S2131L/S2131/S2130/S2231L	WV-S2111L/S21110/S2211L	WV-U2142LA/U2140LA/U2132LA/U2130LA	WV-U2142L/U2140L	WV-U2132L/U2130L	WV-S3531L/S3511L	WV-S3532LM/S3512LM	WV-S3131L/S3111L	V series	WV-SBV131M/SBV111M	WV-SW598/SW598A/SC588/SC588A	WV-SW397/SW397A/SC387/SC387A	
WV-ASM300 (V6.00)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes *26	-	yes	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	H.264	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	-	yes	yes	
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes *27	-	yes	yes
	Audio*23	-	yes	yes	yes	yes	yes	-	-	yes	yes	yes	yes	yes *28	-	yes	yes
Direct connection to camera	PTZ	-	-	-	-	-	-	-	-	-	-	-	yes *1*29	-	yes	yes	
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	-	-	yes	yes	
	MJPEG	-	-	-	yes	yes	-	-	-	-	-	-	yes *26	-	yes	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	H.264	-	-	-	yes	yes	-	-	-	-	-	-	-	-	yes	yes	
WV-ASM200 (V5.10) *24	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	Audio*8	-	-	-	yes	yes	-	-	-	-	-	-	yes *28	-	yes	yes	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	yes *1*29	-	yes	yes	
	RTP over HTTP	-	-	-	yes	yes	-	-	-	-	-	-	-	-	yes	yes	
	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
WV-ASM100 (Ver8.00) *5,*14,*24	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	MJPEG	-	-	-	yes	yes	-	-	-	-	-	-	-	-	yes	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	H.264	-	-	-	yes	yes	-	-	-	-	-	-	-	-	yes	yes	
	H.265	-	-	-	yes	yes	-	-	-	-	-	-	-	-	yes	yes	
WV-ASC970 (Ver19.00)	Audio*8	-	-	-	yes	yes	-	-	-	-	-	-	-	-	yes	yes	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	RTP over HTTP	-	-	-	yes	yes	-	-	-	-	-	-	-	-	yes	yes	
	MJPEG	-	-	-	yes	yes	-	-	-	yes	yes	yes	-	-	yes	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
WJ-GXD400 (Ver2.21) *6,*14,*20	H.264	-	-	-	yes	yes	-	-	-	-	-	-	-	-	yes	yes	
	H.265	-	-	-	yes	yes	-	-	-	-	-	-	-	-	yes	yes	
	Audio*9	-	-	-	yes	yes	-	-	-	-	-	-	-	-	yes	yes	
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
(Discontinued model)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	H.264*25	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
(Discontinued model)	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	yes	yes	

Discontinued model might have the function which doesn't work.  
 \*1 : Only for remote PTZ cameras.  
 \*5 : WV-ASM100 does not support displaying 16:9.  
 \*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Supported G.726.  
 \*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*16 : When displaying H.264 streaming of 2992x2992 resolution, please use a 64 bit OS and 4GB or more memory.  
 \*19 : Supported maximum bitrate is 14Mbps.  
 \*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.  
 \*21 : WV-ASM200 does not support wiper function.  
 \*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.  
 \*23 : Supported G.726 or AAC.  
 \*24 : Please connect to the camera from the PC browser and change the authentication method from Digest o Digest or Basic.  
 \*25 : Video display may take some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.  
 \*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh interval(PPEG). Less than 1fps cannot be selected.  
 \*27 : Restrictions is still under study. Will be updated.  
 \*28 : Support G.726 for WV-U2530L/V1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.  
 \*29 : Support WV-CU950/CU980

	Function	WV-SW386/SW395/SC386/SC385/SC384	WV-SPW6311L/SPW631L/SPW611L/SPW611	WV-SPW531AL/SPW311AL	WV-SPW532L/SPW312L	WV-SPW311LH	WV-SW316L/SW316	WV-SW314	WV-SPN611/SPN631	WV-SPN531/SPN531A	WV-SPN310/SPN311/SPN310A/SPN311A	WV-SP509	WV-SP508	WV-SP300 series	WV-SP105/SP102	WV-NP502
WV-ASM300 (V6.00)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	yes	-	-	-	-	yes	yes	-	-	-	-	-	yes	-	yes
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Direct connection to camera	Audio*23	yes	yes	yes	-	yes	yes	-	yes	yes	yes	yes	-	yes	-	yes
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	yes	-	-	-	-	-	-	-	-	-	-	-	yes	-	yes
WV-ASM200 (V5.10) *24	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	yes	yes	yes	-	yes	yes	-	yes	yes	yes	yes	-	yes	-	yes
	PTZ	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WV-ASM100 (Ver8.00) *5,*14,*24	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	yes	-	-	-	-	yes	yes	-	-	-	-	-	yes	-	yes
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	yes	yes	yes	-	yes	yes	-	yes	yes	yes	yes	-	yes	-	yes
Direct connection to camera (Discontinued model)	PTZ	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	yes	-	-	-	-	yes	yes	-	-	-	-	-	yes	-	yes
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WV-ASC970 (Ver19.00)	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	yes	yes	yes	-	yes	yes	-	yes	yes	yes	yes	-	yes	-	yes
	PTZ	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Direct connection to camera (Discontinued model)	MPEG4	yes	-	-	-	-	yes	yes	-	-	-	-	-	yes	-	yes
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*9	yes	yes	yes	-	yes	yes	-	yes	yes	yes	yes	-	yes	-	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-GXD400 (Ver2.21) *6,*14,*20	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	yes	-	-	-	-	yes	yes	-	-	-	-	-	yes	-	yes
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	Audio*9	yes	yes	yes	-	yes	yes	-	yes	yes	yes	yes	-	yes	-	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	yes	yes	yes	yes	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	yes	-	-	-	-	yes	yes	-	-	-	-	-	yes	-	yes
BB-HNP17 (Ver4.06)	H.264*25	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	yes	yes	yes	-	yes	yes	-	yes	yes	yes	yes	-	yes	-	yes
	PTZ	yes	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes

Discontinued model might have the function which doesn't work.  
 \*1 : Only for remote PTZ cameras.  
 \*5 : WV-ASM100 does not support displaying 16:9.  
 \*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Supported G.726.  
 \*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*16 : When displaying H.264 streaming of 2992x2992 resolution, please use a 64 bit OS and 4GB or more memory.  
 \*19 : Supported maximum bitrate is 14Mbps.  
 \*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.  
 \*21 : WV-ASM200 does not support wiper function.  
 \*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.  
 \*23 : Supported G.726 or AAC.  
 \*24 : Please connect to the camera from the PC browser and change the authentication method from Digest o Digest or Basic.  
 \*25 : Video display may take some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.  
 \*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh interval(JPEG). Less than 1fps cannot be selected.  
 \*27 : Restrictions is still under study. Will be updated.  
 \*28 : Support G.726 for WV-V2530K(V1170)/V6430L. "Audio output" is not supported. Only "Mic input" can be used.  
 \*29 : Support WV-CU950/CU980



	Function	WV-SFN611L/SFN631L/SFR611L/SFR631L/SFV611L/SFV631L/SFV631LT	WV-SFN531/SFR531/SFV531	WV-SFN311/SFN310/SFR311L/SFR310/SFV311/SFV310	WV-SFN311A/SFN310A/SFR311A/SFR310A/SFV311A/SFV310A	WV-SW559/SF549/SF539	WV-SW558/SF548/SF538	WV-SW355/SW352/SF346/SF342	WV-SF330 series	WV-NW502S	WV-SFV130(M)/SFV110(M)	WV-SFN130/SFN110	WV-SW158/SF138	WV-SW155/SW155MA/SW152/SF135/SF132/SW115	WV-SW175/SW172/ST165/ST162	WV-SW174W
WV-ASM300 (V6.00)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera	Audio*23	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WV-ASM200 (V5.10) *24	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WV-ASM100 (Ver8.00) *5,*14,*24	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASC970 (Ver19.00)	Audio*8	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*9	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-GXD400 (Ver2.21) *6,*14,*20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*9	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
(Discontinued model)	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264*25	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
BB-HNP17 (Ver4.06)	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.  
 \*1 : Only for remote PTZ cameras.  
 \*5 : WV-ASM100 does not support displaying 16:9.  
 \*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Supported G.726.  
 \*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*16 : When displaying H.264 streaming of 2892x2992 resolution, please use a 64 bit OS and 4GB or more memory.  
 \*19 : Supported maximum bitrate is 14Mbps.  
 \*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.  
 \*21 : WV-ASM200 does not support wiper function.  
 \*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.  
 \*23 : Supported G.726 or AAC.  
 \*24 : Please connect to the camera from the PC browser and change the authentication method from Digest o Digest or Basic.  
 \*25 : Video display may take some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.  
 \*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh interval(JPEG). Less than 1fps cannot be selected.  
 \*27 : Restrictions is still under study. Will be updated.  
 \*28 : Support G.726 for WV-V2530K(V1170)/V6430L. "Audio output" is not supported. Only "Mic input" can be used.  
 \*29 : Support WV-CU950/CU980

	Function	BB-HCM7 series	BB-HCM5 series	WV-SMR10/SMR10N3	WJ-GXE500	WJ-GXE100
WV-ASM300 (V6.00)	MJPEG	-	-	-	yes	yes
	MPEG4	-	-	-	yes	-
	H.264	-	-	-	yes	yes
	H.265	-	-	-	-	-
	Audio*23	-	-	yes	yes (ch1)	-
	PTZ	-	-	-	yes	yes
Direct connection to camera	RTP over HTTP	-	-	-	yes	yes
	MJPEG	-	-	-	yes	yes
	MPEG4	-	-	-	yes	-
	H.264	-	-	-	yes	yes
	H.265	-	-	-	-	-
	Audio*8	-	-	yes	yes (ch1)	-
WV-ASM200 (V5.10) *24	PTZ	-	-	-	yes	yes
	RTP over HTTP	-	-	-	yes	yes
	MJPEG	-	-	-	yes	-
	MPEG4	-	-	-	yes	-
	H.264	-	-	-	yes	-
	H.265	-	-	-	-	-
Direct connection to camera (Discontinued model)	Audio*8	-	-	yes	yes (ch1)	-
	PTZ	-	-	-	yes	-
	RTP over HTTP	-	-	-	-	-
	MJPEG	-	-	-	yes	-
	MPEG4	-	-	-	yes	-
	H.264	-	-	-	yes	-
WV-ASM100 (Ver8.00) *5,*14,*24	H.265	-	-	-	-	-
	Audio*8	-	-	-	yes (ch1)	-
	PTZ	-	-	-	yes	-
	RTP over HTTP	-	-	-	-	-
	MJPEG	-	-	-	yes	-
	MPEG4	-	-	-	yes	-
Direct connection to camera (Discontinued model)	H.264	-	-	-	yes	-
	H.265	-	-	-	-	-
	Audio*8	-	-	-	yes (ch1)	-
	PTZ	-	-	-	yes	-
	RTP over HTTP	-	-	-	-	-
	MJPEG	-	-	-	yes	yes
WV-ASC970 (Ver19.00)	MPEG4	-	-	-	yes	-
	H.264	-	-	-	yes	yes
	H.265	-	-	-	-	-
	Audio*8	-	-	-	yes (ch1)	-
	PTZ	-	-	-	yes	yes
	RTP over HTTP	-	-	-	yes	yes
Direct connection to camera (Discontinued model)	MJPEG	-	-	-	yes	yes
	MPEG4	-	-	-	yes	-
	H.264	-	-	-	yes	yes
	H.265	-	-	-	-	-
	Audio*9	-	-	-	yes (ch1)	-
	PTZ	-	-	-	-	-
WJ-GXD400 (Ver2.21) *6,*14,*20	RTP over HTTP	-	-	-	yes	yes
	MJPEG	yes	yes	-	yes	yes
	MPEG4	yes	yes	-	yes	-
	H.264	yes	-	-	yes	yes
	H.265	-	-	-	-	-
	Audio*9	-	-	-	yes (ch1)	-
(Discontinued model)	PTZ	-	-	-	-	-
	RTP over HTTP	-	-	-	yes	yes
	MJPEG	yes	yes	-	yes	yes
	MPEG4	yes	yes	-	yes	-
	H.264*25	yes	-	-	yes	yes
	H.265	-	-	-	-	-
BB-HNP17 (Ver4.06)	Audio*8	yes	yes	-	yes (ch1)	-
	PTZ	yes *1	yes *1	-	yes	yes
	RTP over HTTP	-	-	-	yes	yes
	MJPEG	yes	yes	-	yes	yes
	MPEG4	yes	yes	-	yes	-
	H.264*25	yes	-	-	yes	yes
(Discontinued model)	H.265	-	-	-	-	-
	Audio*8	yes	yes	-	yes (ch1)	-
	PTZ	yes *1	yes *1	-	yes	yes
	RTP over HTTP	-	-	-	yes	yes
	MJPEG	yes	yes	-	yes	yes
	MPEG4	yes	yes	-	yes	-

Discontinued model might have the function which doesn't work.  
 \*1 : Only for remote PTZ cameras.  
 \*5 : WV-ASM100 does not support displaying 16:9.  
 \*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.  
 \*7 : Support functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.  
 \*8 : Supported G.726.  
 \*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.  
 \*14 : Streams of H.264(3) and H.264(4) are not supported.  
 \*16 : When displaying H.264 streaming of 2992x2992 resolution, please use a 64 bit OS and 4GB or more memory.  
 \*19 : Supported maximum bitrate is 14Mbps.  
 \*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.  
 \*21 : WV-ASM200 does not support wiper function.  
 \*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.  
 \*23 : Supported G.726 or AAC.  
 \*24 : Please connect to the camera from the PC browser and change the authentication method from Digest o Digest or Basic.  
 \*25 : Video display may take some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.  
 \*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1ips to 30ips for Refresh interval(JPEG). Less than 1ips cannot be selected.  
 \*27 : Restrictions is still under study. Will be updated.  
 \*28 : Support G.726 for WV-V2530K(V1170)/V6430L. "Audio output" is not supported. Only "Mic input" can be used.  
 \*29 : Support WV-CU950/CU980

	Function	WJ-NU101K/KG WJ-NU201K/KG WJ-NU300K/KG WJ-NU301K/KG	WJ-NX400	WJ-NX300	WJ-NX200	WJ-NV300	WJ-NV200	WJ-ND400K	WJ-ND300A	WJ- HD616/HD716	WJ-HD300 (Discontinued model)
WV-ASM300 (V6.00)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	-	-
	MPEG4	-	-	-	-	-	yes	yes	yes	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	-
	H.265	yes	yes	yes	yes	yes	-	-	-	-	-
	Original	-	-	-	-	-	-	-	-	-	yes
	Audio	Live/Playback(Receive)(*11)	Live/Playback(Receive)(*10)	Live/Playback(Receive)(*10)	Live/Playback(Receive)(*10)	Live/Playback(Receive)(*8)	Live/Playback(Receive)(*8)	Live/Playback(Receive)(*8)	Live/Playback(Receive)(*8)	Live/Playback(Receive)(*8)	Live/Playback(Receive)(*8)
	PTZ	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
VMD	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	
WV-ASM200 (V5.10)	MJPEG	-	-	-	-	yes	yes	yes	yes	yes	-
	MPEG4	-	-	-	-	-	yes	yes	yes	yes	-
	H.264	-	-	-	-	-	yes	yes	yes	yes	-
	H.265	-	-	-	-	-	yes	yes	yes	yes	-
	Original	-	-	-	-	-	-	-	-	-	yes
	Audio*8	-	-	-	-	Live/Playback(Receive)	Live/Playback(Receive)	Live/Playback(Receive)	-	Live/Playback(Receive)	-
	PTZ	-	-	-	-	yes	yes	yes	yes	yes	yes
VMD	-	-	-	-	yes	yes	yes	yes	yes	yes	
RTP over HTTP	-	-	-	-	yes	yes	yes	yes	yes	yes	
WV-ASM100 (Ver8.00)	MJPEG	-	-	-	-	-	yes	yes	yes	yes	-
	MPEG4	-	-	-	-	-	yes	yes	yes	yes	-
	H.264	-	-	-	-	-	yes	yes	yes	yes	-
	H.265	-	-	-	-	-	-	-	-	-	-
	Original	-	-	-	-	-	-	-	-	-	yes
	Audio*8	-	-	-	-	-	Live/Playback(Receive)	Live/Playback(Receive)	-	Live/Playback(Receive)	-
	PTZ	-	-	-	-	-	yes	yes	yes	yes	yes
VMD	-	-	-	-	-	yes	yes	yes	yes	yes	
RTP over HTTP	-	-	-	-	-	yes	yes	yes	yes	yes	
WV-ASM970 (Ver19.00)	MJPEG	-	yes	-	-	yes	yes	yes	yes	yes (Playback only)	-
	MPEG4	-	-	-	-	-	yes	yes	yes	yes (Playback only)	-
	H.264	-	yes	-	-	yes	yes	yes	yes	yes (Playback only)	-
	H.265	-	-	-	-	-	-	-	-	-	-
	Original	-	-	-	-	-	-	-	-	-	yes
	Audio*8	-	Live/Playback(Receive)	-	-	Live/Playback(Receive)	Playback(Receive)	Playback(Receive)	-	Playback(Receive)	-
	PTZ	-	yes	-	-	yes	yes	yes	yes	yes	yes
VMD	-	yes	-	-	yes	yes	yes	yes	yes	yes	
RTP over HTTP	-	yes	-	-	yes	yes	yes	yes	yes	yes	
WJ-GXD400 (Ver2.21) *6	MJPEG	-	-	-	-	-	-	-	yes (Playback only)	-	-
	MPEG4	-	-	-	-	-	-	-	yes (Playback only)	-	-
	H.264	-	-	-	-	-	-	-	yes (Playback only)	yes	-
	H.265	-	-	-	-	-	-	-	-	-	-
	Original	-	-	-	-	-	-	-	-	-	yes
	Audio*9	-	-	-	-	-	-	Playback(Receive)	-	Playback(Receive)	-
	PTZ	-	-	-	-	-	-	yes	-	yes	yes
VMD	-	-	-	-	-	-	yes	-	yes	yes	
RTP over HTTP	-	-	-	-	-	-	-	-	-	-	

Discontinued model might have the function which doesn't work.  
 \*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.  
 \*8 : Supported only G.726.  
 \*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.  
 \*10 : Supported G.726 or AAC.  
 \*11 : Supported only AAC.

**Symbol description**  
 ○ : Supported  
 x : Non supported  
 — : Non feature