


i-PRO



TRANSIT VIDEO RECORDER | MR-6C-AT-MLXTB-W

MODEL	STORAGE	WI-FI	RAM
MR-6C-AT-ML1TB-W	(1 X 1TB, 2.5" MLC-SSD)	802.11a/b/g/n/ac	4GB
MR-6C-AT-ML2TB-W	(1 X 2TB, 2.5" eTLC-SSD)	802.11a/b/g/n/ac	4GB

• Total usable storage is calculated based on advertised HDD size, not OS recognition.

PRELOADED TRANSIT VIDEO RECORDER – 6 CHANNEL

- Fully Tested and Configured
- Includes VI Enterprise Server License
- Superior US-Based Technical Support
- 3-Year Hardware Warranty*

OPERATING CONDITIONS AND RATINGS

TEMPERATURES

Unit: -30°C-60°C

RELATIVE HUMIDITY

10% to 90% (Non-Condensing)

VIBRATION DURING OPERATION

Operating: MIL-STD-810G, Method 514.6, Category 4, Common Carrier US HWY Vibration Exposure

SHOCK RATING

MIL-STD-810G

Operating Functional Shock=20g

None Operation Functional Shock=75g

CERTIFICATIONS

CE Approval, FCC Class A, E13 Mark

SERVER SPECIFICATIONS

PROCESSOR

Intel Atom| Quad Core| 1.8 GHz Turbo

MEMORY

4GB 1XDDR3L 50-DIMM

I/O SLOTS

USB | 1 X USB 3.0 Type A

GPIO

3 X Input, 3 X Output

NETWORK PORTS

6 X PoE RJ45

POE CAPACITY

Max. 60W

DRIVE BAY

1 X 2.5inch

EMBEDDED NIC

1000 BASE-T Dual Port LOM (LAN on Motherboard)

POWER SOURCE

Auto Ranging (9V-36V DC)

OPERATING SYSTEM

Windows 10 IoT

GRAPHICS CARD

Intel Onboard Graphics

VIDEO OUTPUT

1 X HDMI

DIMENSIONS

(W) 7.1" X (D) 7.1" X (H) 3"

WARRANTY

Standard 3-Year Warranty

MONITOR

Not Included

SOFTWARE LICENSING

IPSVC-UL

3rd Party Camera License for VI / Transit Solution: Not Needed if Using i-PRO or Advitia Cameras

IPSVS-AD-TRANS-UL

Software Needed per Mobile Recorder Unit to: Activates GPS Positioning Data & Wi-Fi Video Offloading Capabilities with VI IP Server

ACCESSORIES

MR-POW-3P

AC Adapter 120W 3-Pin: Alternative Power Supply (NOT FOR DEPLOYMENT | ONLY FOR TESTING)