

## Camera/Recorder Compatibility

	Function	WV-X86530-Z2/Z2-1 WV-X86531-Z2/Z2-1	WV-S85702-F3L/ F3L1	WV-S85402-V2L/ V2L1	WV-U85402-V2L/ V2L1	WV-PM500	WV-S61501-Z1	WV-S65501-Z1/Z1G	WV-S61300-ZY/ZYG	WV-S65300-ZY/ZYG	WV-S65301-Z1/Z1G Z1-1/Z1S	WV-S65302-Z2/Z2G Z2-1	WV-U61300- ZY/ZYG/ZYV	WV-U65300-ZY/ZYG	WV-S65340- Z2N/ZAN/Z2K/Z4K /Z2K1/Z2G/Z4G/Z2 Z2N1/Z4/Z4N1	WV-S61302-Z4
WJ-HU10/K/XG WJ-HU20K/XG WJ-HU30K/XG WJ-HU30K/XG (*V1.10) *20	MJPEG MPEG4 H.264 H.265 Audio *32 PTZ	no no yes yes yes yes	no no yes yes yes yes	no no yes yes yes yes	- - - - -	- - - - -	yes yes yes yes yes	yes yes yes yes yes								
WJ-NX400 (*V5.20) *20	MJPEG MPEG4 H.264 H.265 Audio PTZ	no no yes yes yes yes	no no yes yes yes yes	no no yes yes yes yes	- - - - -	- - - - -	- - - - -	- - - - -	- - - - -	- - - - -	- - - - -	- - - - -	- - - - -			
WJ-NX300 (*V5.20) *20	MJPEG MPEG4 H.264 H.265 Audio PTZ	no no yes yes yes yes	no no yes yes yes yes	no no yes yes yes yes	- - - - -	- - - - -	yes yes yes yes yes yes									
WJ-NX200 (*V5.20) *20	MJPEG MPEG4 H.264 H.265 Audio PTZ	no no yes yes yes yes	no no yes yes yes yes	no no yes yes yes yes	- - - - -	- - - - -	yes yes yes yes yes yes									
WJ-NX100 (*V5.20) *20	MJPEG MPEG4 H.264 H.265 Audio PTZ	no no yes yes yes yes	no no yes yes yes yes	no no yes yes yes yes	- - - - -	- - - - -	yes yes yes yes yes yes									
WJ-NV300 (*V2.30) *14 (Discontinued model)	MJPEG MPEG4 H.264 H.265 Audio *8 PTZ	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -		
WJ-NV200 (*V2.60) *14 (Discontinued model)	MJPEG MPEG4 H.264 H.265 Audio *8 PTZ	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -		
WJ-ND400K (*V6.10) *14 (Discontinued model)	MJPEG MPEG4 H.264 H.265 Audio *8 PTZ	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -		
WJ-ND300A (*V5.20) *4, *14 (Discontinued model)	MJPEG MPEG4 H.264 H.265 Audio PTZ	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -		
WJ-ND200 (*V3.35) *4, *14 (Discontinued model)	MJPEG MPEG4 H.264 H.265 Audio *8*11 PTZ	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -		

[substitute model or camera classification] : Register as a substitute model or a camera classification.

\*1 : Only for remote PTZ camera.

\*2 : Support less than 1920x1080 including 1600x1200, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality 5-9 and the frame rate up to 5fps.

\*3 : Each recorder supports only wireless connection.

\*4 : Displaying 16:9 is not supported on a NOR browser.

\*5 : Substituted models are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.

\*8 : Support G.726 and 32kps.

\*11 : This function is supported only when playing back.

\*12 : Supported up to 30 ips.

\*13 : When using H.264(3) and H.264(4) are not supported.

\*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SPV781L, SPV781L, SPV481, SFN480 support will be only 1-8ch.

\*17 : The fish-eye dewarp function on the main monitor is supported.

\*18 : The fish-eye dewarp function is supported by using the management software(WV-ASM200, WV-ASC970).

\*19 : Support maximum bitrate is 149Mbps.

\*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 cameras.

\*21 : Support less than 1280x720 via WV-XEN.

\*22 : Support 64Mbps for maximum motion detection from H.265(factory default) to H.264 by connecting from web browser.

\*23 : Support G.726/32kps and AAC-LC/64kbs.

\*24 : Supported image capture sizes are 4KUHD(3840x2160), WQHD(2560x1440), FHD(1920x1080) and HD(1280x720).

\*25 : Support 64Mbps.

\*26 : Support 1080x1200, 1280x720 and 1280x640. Supported up to 30 ips.

\*27 : WV-V1170 additionally supports 3840x2160, 2048x1536, 2560x1520, 4000x3000(15fps).

\*28 : Support G.726.

\*29 : Support 64Mbps and 32Mbps.

\*30 : Support 3840x2160, 1920x1080, 1280x720, 2560x1920, 2048x1536 and 1280x960 for WV-V1170.

\*31 : The supported camera firmware is V1.10 or later.

\*32 : Only AAC-LC/64kbs is supported.













## Camera/Recorder Compatibility

	Function	WV-SP509	WV-SP508	WV-SP300 series	WV-SP105/SP102	WV-NP502	WV-SFN611L/SFN631L/SFR611L/SFR631L/SFV611L/SFV631L/SFV631L	WV-SFN531/SFR531/SFV531	WV-SFN311/SFN310/SFR311/SFR310/SFV311A/SFV310A	WV-SFN311/SFN310/SFR311/SFR310/SFV311A/SFV310A	WV-SW559/SF549/SF539	WV-SW558/SF548/SF538	WV-SW355/SW352/SF346/SF342	WV-SF330 series	WV-NW502S	WV-SFV130/SFV110
WJ-HU10/K/G WJ-HU20/K/G WJ-HU30K/G WJ-HU30L/K/G (V1.10) *20	MJPEG MPEG4 H.264 H.265 Audio *32 PTZ	[i-PRO(B_FIX)] [i-PRO(A_FIX)] [i-PRO(C_FIX)] no	[i-PRO(B_FIX)] [i-PRO(A_FIX)] [i-PRO(C_FIX)]	[i-PRO(A_FIX)] [i-PRO(B_FIX)] [i-PRO(C_FIX)]	[i-PRO(A_FIX)] [i-PRO(B_FIX)] [i-PRO(C_FIX)]	[i-PRO(C_FIX)] [i-PRO(A_FIX)] [i-PRO(B_FIX)]	[i-PRO(C_FIX)] [i-PRO(A_FIX)] [i-PRO(B_FIX)]	[i-PRO(C_FIX)] [i-PRO(A_FIX)] [i-PRO(B_FIX)]	[i-PRO(C_FIX)] [i-PRO(A_FIX)] [i-PRO(B_FIX)]	[i-PRO(C_FIX)] [i-PRO(A_FIX)] [i-PRO(B_FIX)]	[i-PRO(B_FIX)] [i-PRO(A_FIX)] [i-PRO(C_FIX)]	[i-PRO(C_FIX)] [i-PRO(A_FIX)] [i-PRO(B_FIX)]	[i-PRO(B_FIX)] [i-PRO(A_FIX)] [i-PRO(C_FIX)]	[i-PRO(A_FIX)] [i-PRO(B_FIX)] [i-PRO(C_FIX)]	[i-PRO(A_FIX)] [i-PRO(B_FIX)] [i-PRO(C_FIX)]	
WJ-NX400 (V5.20) *20	MJPEG MPEG4 H.264 H.265 Audio PTZ	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -
WJ-NX300 (V5.20) *20	MJPEG MPEG4 H.264 H.265 Audio PTZ	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -
WJ-NX200 (V5.20) *20	MJPEG MPEG4 H.264 H.265 Audio PTZ	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -
WJ-NX100 (V5.20) *20	MJPEG MPEG4 H.264 H.265 Audio PTZ	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -
WJ-NV300 (V2.30) *14 (Discontinued model)	MJPEG MPEG4 H.264 H.265 Audio *8 PTZ	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -
WJ-NV200 (V2.60) *14 (Discontinued model)	MJPEG MPEG4 H.264 H.265 Audio *8 PTZ	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -
WJ-ND400K (V6.10) *14 (Discontinued model)	MJPEG MPEG4 H.264 H.265 Audio *8 PTZ	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -	yes -
WJ-ND300A (V5.20) *4, *14 (Discontinued model)	MJPEG MPEG4 H.264 H.265 Audio PTZ	[SP305]*2 -	[SP102]*2 -	yes -	yes -	yes -	yes -	yes -	[SF335]*2 -	[SF335]*2 -	[SF335]*2 -	[SF335]*2 -	[SF335]*2 -	[SF102]*2 -	[SF335]*2 -	[SF335]*2 -
WJ-ND200 (V3.35) *4, *14 (Discontinued model)	MJPEG MPEG4 H.264 H.265 Audio *9*11 PTZ	[SP305]*2 -	[SP305]*2 -	yes -	yes -	yes -	yes -	yes -	[SF335]*2 -	[SF335]*2 -						

[substitute model or camera classification] : Register as a substitute model or a camera classification.

\*1 : Only for remote PTZ cameras.

\*2 : Support less than 1920x1080, including 1600x1200, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality:5~9 and the frame rate:up to 5fps.

\*3 : Each recorder supports only wireless connection.

\*4 : Displaying 16:9 is not supported on a NOR browser.

\*5 : Configuration parameters are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.

\*8 : Support G.726 and 32kps.

\*11 : This function is supported only when playing back.

\*12 : Supported up to 30fps.

\*13 : Stream of H.264(3) and H.264(4) are not supported.

\*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SFV71L, SFV781, SFV481, SFN480 support will be only 1-8ch.

\*17 : The fish-eye dewarp function on the main monitor is supported.

\*18 : The multi-camera function is supported by using the management software(WV-ASM200, WV-ASC970).

\*19 : Support maximum bitrate is 140Mbps.

\*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 cameras

\*21 : Support less than 1280x720 and WV-X651N.

\*22 : Support 640x480, 320x240 and 160x120.

\*23 : Support G.726/32kps and AAC-LC/64kbs.

\*24 : Supported image capture sizes are 4K(UHD)(3840x2160), WQHD(2560x1440), FHD(1920x1080) and HD(1280x720).

\*25 : Support 1920x1080, 1280x720 and 1280x640.

\*26 : WV-V1170 additionally supports 3840x2160, 2048x136, 2560x1280, 4000x3000(15fps).

\*28 : Support G.726.

\*29 : Support 640x480 and 320x240.

\*30 : Support 3840x2160, 1920x1080, 1280x720, 2560x1920, 2048x136 and 1280x960 for WV-V1170.

\*31 : The supported camera firmware is V1.10 or later.

## Camera/Recorder Compatibility

	Function	WV-SFN130/SFN110	WV-SF158/SF138	WV-SW155/SW152/SW115	WV-SF135/SF132	WV-SW175/SW172/SI165/SI162	WV-SW174W *3	BB-HCM7 series	BB-HCM5 series	WV-SMR10/SMR10N3	WJ-GXE500	WJ-GXE100
WJ-NU01K/KG WJ-NU201K/KG WJ-NU300K/KG WJ-NU301K/KG (V1.10) *20	MJPEG	[i-PRO C FIX]	[i-PRO B FIX]	[i-PRO A FIX]	[i-PRO(A FIX)]	[i-PRO(A PTZ)]	[i-PRO(A PTZ)]	-	-	-	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	no	-
	H.264	[i-PRO(C FIX)]	[i-PRO(B FIX)]	[i-PRO(A FIX)]	[i-PRO(A PTZ)]	[i-PRO(A PTZ)]	[i-PRO(A PTZ)]	-	-	-	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-
	Audio *32	[i-PRO(C FIX)]	no	-	-	no	no	-	-	-	no	-
	PTZ	-	-	-	-	[i-PRO(A PTZ)]	[i-PRO(A PTZ)]	-	-	-	yes	yes
	Motion detection (VMD)	[i-PRO(C FIX)]	[i-PRO(B FIX)]	[i-PRO(A FIX)]	[i-PRO(A FIX)]	[i-PRO(A PTZ)]	[i-PRO(A PTZ)]	-	-	-	yes	yes
	WJ-NX400 (V5.20) *20	MJPEG	yes	yes	yes	yes	yes	yes	yes	-	-	yes
	MPEG4	-	-	-	-	-	-	-	-	-	no	-
	H.264	yes	yes	yes	yes	yes	yes	-	-	-	yes	yes
WJ-NX300 (V5.20) *20	H.265	-	-	-	-	-	-	-	-	-	-	-
	Audio	yes *23	yes *8	-	-	yes *8	yes *8	yes *8	-	-	yes (ch1) *8	-
	PTZ	-	-	-	-	yes	yes	yes *1	yes *1	-	-	yes
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	-	-	-	yes	yes
	WJ-NX200 (V5.20) *20	H.264	yes	yes	yes	yes	yes	yes	yes	-	-	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-
	Audio	yes *23	yes *8	-	-	yes *8	yes *8	yes *8	-	-	yes (ch1) *8	-
	PTZ	-	-	-	-	yes	yes	yes *1	yes *1	-	-	yes
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	-	-	-	yes	yes
	WJ-NX100 (V5.20) *20	H.264	yes	yes	yes	yes	yes	yes	yes	-	-	yes
(Discontinued model) WJ-NV300 (V2.30) *14	H.265	-	-	-	-	-	-	-	-	-	-	-
	Audio *8	yes	yes	yes	yes	yes	yes	yes	yes	-	-	yes
	PTZ	-	-	-	-	yes	yes	yes *1	yes *1	-	-	yes
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	-	-	-	yes	yes
	WJ-NV200 (V2.60) *14	H.264	yes	yes	yes	yes	yes	yes	yes	-	-	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-
	Audio *8	yes	yes	-	-	yes	yes	yes	-	-	yes (ch1)	-
	PTZ	-	-	-	-	yes	yes	yes *1	yes *1	-	-	yes
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	-	-	-	yes	yes
	WJ-ND400K (V6.10) *14	H.264	yes	yes	yes	yes	yes	yes	yes	-	-	yes
(Discontinued model) WJ-ND300A (V5.20) *4, *14	H.265	-	-	-	-	-	-	-	-	-	-	-
	Audio *8	yes	yes	-	-	yes	yes	yes	yes	-	-	yes
	PTZ	-	-	-	-	yes	yes	yes *1	yes *1	-	-	yes
	Motion detection (VMD)	yes	yes	yes	yes	yes	yes	-	-	-	yes	yes
	WJ-ND300A (V5.20) *4, *14	H.264	-	-	[SF335]*2	[SF335]*2	[SF335]	[SP102]	[SC385]	[SC385]	yes	[GXE500 ch1]
	H.265	-	-	-	-	-	-	-	-	-	yes	-
	Audio	-	-	-	-	[SF335]	[SF335]	[SC385]	[SC385]	-	-	[GXE500 ch1]
	PTZ	-	-	-	-	-	-	-	-	-	-	-
	Motion detection (VMD)	-	-	-	-	-	[SC385]	[SC385]	[SC385]	yes *1	yes *1	[GXE500 ch1]
	WJ-ND200 (V3.35) *4, *14	H.264	-	-	[SF335]*2	[SF335]*2	[SF335]	[SC385]	[SC385]	[SC385]	yes	[GXE500 ch1]
(Discontinued model) WJ-ND200 (V3.35) *4, *14	H.265	-	-	-	-	-	-	-	-	-	yes	[GXE500 ch1]
	Audio *8*11	-	[SF335]	[SF335]	-	-	[SC385]	[SC385]	[SC385]	yes	-	yes (ch1)
	PTZ	-	-	-	-	-	[SC385]	[SC385]	[SC385]	yes *1	yes *1	yes [GXE500 ch1]
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-
	WJ-ND200 (V3.35) *4, *14	H.264	-	-	[SF335]	[SF335]	[SC385]	[SC385]	[SC385]	yes	-	[GXE500 ch1]
	H.265	-	-	-	-	-	-	-	-	-	yes	[GXE500 ch1]
	Audio *8*11	-	[SF335]	[SF335]	-	-	[SC385]	[SC385]	[SC385]	yes	-	yes (ch1)
	PTZ	-	-	-	-	-	[SC385]	[SC385]	[SC385]	yes *1	yes *1	yes [GXE500 ch1]
	Motion detection (VMD)	-	-	-	-	-	-	-	-	-	-	-

[substitute model or camera classification] : Register as a substitute model or a camera classification.

\*1 : Only for remote PTZ cameras.

\*2 : Support less than 1920x1080, including 1600x1200, 1920x1080 and 1600x1200 are not supported SD memory card backup and can be set the image quality:5-9 and the frame rate:up to 5fps.

\*3 : Each recorder supports only wireless connection.

\*4 : Displaying 16:9 is not supported on a NOR browser.

\*5 : Operating conditions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.

\*8 : Support G.726 and 32kps.

\*11 : This function is supported only when playing back.

\*12 : Supported up to 30 fps.

\*13 : Stream of H.264(3) and H.264(4) are not supported.

\*15 : When using over 6Mbps for bitrate, please use the "4K resolution" mode. SFV781L, SFV781L, SFV481, SFN480 support will be only 1-8ch.

\*16 : The maximum frame rate is limited by using the management software(WV-ASM200, WV-ASC970).

\*19 : Support maximum bitrate is 149Mbps.

\*20 : 3rd stream and 4th stream of H.264 are supported, only when using H.265 cameras

\*21 : Support less than 1280x720 for WV-X500N.

\*22 : Support 640x480 and 320x240.

\*23 : Support G.726/32kps and AAC-LC/64kbs.

\*24 : Supported image capture sizes are 4K/UHD(3840x2160), WQHD(2560x1440), FHD(1920x1080) and HD(1280x720).

\*25 : Support 4K/UHD(3840x2160), 1280x720 and 1280x480. Supported up to 30 fps.

\*27 : WV-V1170 additionally supports 3840x2160, 2048x136, 2560x1520, 4000x3000(15fps).

\*28 : Support G.726.

\*29 : Support 640x480 and 320x240.

\*30 : Support 3840x2160, 1920x1080, 1280x720, 2560x1920, 2048x136 and 1280x960 for WV-V1170.

\*31 : The supported camera firmware is V.10 or later.

	Function	WV-X86530-Z2-Z2-1 WV-X86531-Z2/Z2-1	WV-S85702-F3L/ F3L1	WV-S85402-V2L /V2L1	WV-U85402-V2L /V2L1	WV-PM500	WV-S61501-Z1	WV-S65501-Z1/Z1G	WV-S61300-ZY/ZYG	WV-S65300-ZY/ZYG	WV-S65301-Z1/Z1G Z1-1/Z1S	WV-S65302-Z2/Z2G Z2-1	WV-U61300- ZY/ZYG/ZYV	WV-S65340- Z2N/ZAN/Z2K/Z4K /Z2KJ/Z2G/Z4G/Z2 Z2N1/Z2/ZN1	WV-S61302-Z4
Direct connection to camera	MJPEG	yes	yes	yes	-	-	-	-	-	-	-	-	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	-	-	-	-	-	-	-	-	yes	yes	yes
	H.264*	yes	yes	yes	-	-	-	-	-	-	-	-	yes	yes	yes
	Audio*8	yes	yes	yes	-	-	-	-	-	-	-	-	yes	yes	yes
	PTZ	yes	-	-	-	-	-	-	-	-	-	-	yes	yes	yes
	RTP over HTTP	yes	yes	yes	yes	-	-	-	-	-	-	-	yes	yes	yes
Direct connection to camera (Discontinued model)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASH100 (Ver8.00) *5,*14,*24	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASC970 (Ver19.00)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-GX400 (Ver2.21) *6,*14,*20	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264*	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*9	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BB-HNP17 (Ver4.06)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264*2	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.

\*1 : Only for remote PTZ cameras.

\*5 : WV-ASH100 displaying 16:9.

\*6 : Supported resolutions of WJ-GX400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.

\*7 : Supported functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.

\*8 : Supported G.726

\*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.

\*14 : Streams of H.264(3) and H.264(4) are not supported.

\*16 : H.264 streams of 1280x960 resolution, please use a 64 bit OS and 4GB or more memory.

\*19 : Supported maximum bitrate is 14Mbps.

\*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.

\*21 : Only for remote PTZ cameras.

\*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.

\*23 : Supported G.726 or AAC.

\*24 : Remote connection to the cameras from the PC browser and change the authentication method from Digest or Digest or Basic.

\*25 : Video may move at some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.

\*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh Interval(JPEG). Less than 1fps cannot be selected.

\*27 : Restrictions is still under study. Will be updated.

\*28 : Support G.726 for WV-V230LV/V1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.

\*29 : Support WV-CU950/CU980

	Function	WV-S25500-F3L/F6L	WV-S22500-F3L/F6L	WV-S15500-F3L/F6L	WV-U61301-Z1/Z2	WV-U65301-Z1/Z1G	WV-U65302-Z2/Z2G	WV-S61301-Z1/Z2	WV-S71300-F3	WV-S25700-V2L/V2LN/V2LG/V2LM	WV-S25600-V2L/V2LN/V2LG	WV-S25500-V3L/V3LN/V3LG/V3LN	WV-S22700-V2L/V2LG/V2L1/V2L1	WV-S22600-V2L/V2LG	WV-S22500-V3L/V3LG/V3LN	WV-S15700-V2L/V2LN/V2LK
Direct connection to camera	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio*8	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	yes	yes	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
(Discontinued model)	WV-ASH200 (VS.10)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	WV-ASH100 (Ver8.00) *5,*14,*24	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	WV-ASC970 (Ver19.001)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	WJ-GX400 (Ver2.21) *6,*14,*20	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	BB-HNP17 (Ver4.06)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	WV-CU950 (CU980)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.

\*1 : Only for remote PTZ cameras.

\*5 : WV-ASH100 does not support displaying 16:9.

\*6 : Supported resolutions of WV-GX400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.

\*7 : Supported functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.

\*8 : Supported G.726

\*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.

\*14 : Streams of H.264(3) and H.264(4) are not supported.

\*16 : Maximum resolution of 1280x960 resolution, please use a 64 bit OS and 4GB or more memory.

\*19 : Supported maximum bitrate is 14Mbps.

\*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.

\*21 : Only for remote PTZ cameras.

\*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.

\*23 : Supported G.726 or AAC.

\*24 : Remote control to the cameras from the PC browser and change the authentication method from Digest or Digest or Basic.

\*25 : Video may move at some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.

\*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh Interval(JPEG). Less than 1fps cannot be selected.

\*27 : Restrictions is still under study. Will be updated.

\*28 : Support G.726 for WV-V230LVN/V1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.

\*29 : Support WV-CU950 (CU980)

	Function	WV-S15600-V2L/V2M	WV-S1550-K/V3L/V3LN/V3LN1/V3L	WV-S8573L/S8573LG/S8S74L/S8574LG	WV-S8563L/S8563LG/S8S64L/S8564LG	WV-S8543/S8543G/S8544/S8544LG	WV-X8571N/S8531N	WV-X8570N/S8530N	WV-X6533LN/X6533LNS/S6532LN/S6532LNS	WV-X6531N/X6531NS/X6511N	WV-SUD638	WV-S6530N	WV-S6131/S6111/S6130	WV-X4573L/X4573LM	WV-X4171/X4571L/X4571LM	WV-X4172/X4173
WV-ASH300 (VS.10)	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	yes -	yes yes yes yes yes	yes yes yes yes yes	yes yes yes yes yes	no yes yes yes yes	yes yes yes yes yes	yes yes yes yes yes	yes yes yes yes yes	yes yes yes yes yes	yes yes yes yes yes	yes yes yes yes yes	yes yes yes yes yes	yes yes yes yes yes		
Direct connection to camera	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WV-ASH200 (VS.10) *24	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASH100 (Ver8.00) *5,*14,*24	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASC970 (Ver19.00)	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-GX4040 (Ver2.21) *6,*14,*20	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BB-HNP17 (Ver4.06)	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.

\*1 : Only for remote PTZ cameras.

\*2 : WV-ASH100 does not support displaying 16:9.

\*6 : Supported resolutions of WJ-GX4040 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.

\*7 : Supported bitrates are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.

\*8 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.

\*14 : Streams of H.264(3) and H.264(4) are not supported.

\*16 : When using multiple streams, 1280x960 resolution, please use a 64 bit OS and 4GB or more memory.

\*19 : Supported maximum bitrate is 14Mbps.

\*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.

\*21 : Only for remote PTZ cameras.

\*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.

\*23 : Supported G.726 or AAC.

\*24 : Remote control to the cameras from the PC browser and change the authentication method from Digest or Digest or Basic.

\*25 : Video may move at some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.

\*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh Interval(JPEG). Less than 1fps cannot be selected.

\*27 : Restrictions is still under study. Will be updated.

\*28 : Support G.726 for WV-V230LV/KV1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.

\*29 : Support WV-CU950/CU980

	Function	WV-X4170	WV-S4556LM/S4556L/ S4156	WV-S4576LM/ S4576L	WV-S4551LM/ S4151	WV-S4550L/S4550LM/ S4150	WV-SF481/SFN480 *7	WV-SW458/SW458MA/ SF438/SF448E *7	WV-X2571LN/X2271L	WV-X1571LN	WV-S2572L/S2272L/ S1572L	WV-S2570L/S2270L/S1570L	WV-SFV781L/SPV781L	WV-X1551LN	WV-S1536L/S1536LN/ S1536LTN/S1536LT	WV-S1552L
Direct connection to camera	MJPEG	yes	yes	yes	-	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes*17,*18	yes	yes	yes	yes	yes*18	yes	yes	yes	yes
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio*8	-	-	-	-	-	-	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	-	-	-	-	-	yes	yes	yes	-	-	-	-	-	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	-	yes	yes	yes	yes	yes	yes	yes	yes
WV-ASH200 (VS.10) *24	MJPEG	-	-	-	-	-	Unverified	yes	yes	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	Unverified	yes*17,*18	yes	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	Unverified	yes	yes	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	Unverified	yes	yes	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	Unverified	yes	-	-	-	-	-	-	-	-
WV-ASH100 (Ver8.00) *5,*14,*24	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model) WV-ASC970 (Ver19.00)	MJPEG	-	-	-	-	-	Unverified	yes	yes	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	Unverified	yes*17,*19	yes	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	Unverified	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	Unverified	yes	yes	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	Unverified	yes	yes	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	Unverified	yes	-	-	-	-	-	-	-	-
WJ-GX400 (Ver2.21) *6,*14,*20	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model) BB-HNP17 (Ver4.06)	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.

<sup>1</sup>\* Only for remote PTZ cameras.<sup>5</sup>\* WV-ASH100 does not support displaying 16:9.<sup>6</sup>\* Supported resolutions of WJ-GX400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.<sup>7</sup>\* Supported functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.<sup>8</sup>\* Supported G.726<sup>9</sup>\* Supported G.726 as an Audio and MPEG4/H.264 as a Video.<sup>10</sup>\* Streams of H.264(3) and H.264(4) are not supported.<sup>11</sup>\* When using multiple streams, 1280x960 resolution, please use a 64 bit OS and 4GB or more memory.<sup>12</sup>\* Supported maximum bitrate is 14Mbps.<sup>13</sup>\* Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.<sup>14</sup>\* Only for remote PTZ cameras.<sup>22</sup>\* Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.<sup>23</sup>\* Supported G.726 or AAC.<sup>24</sup>\* Remote control to the cameras from the PC browser and change the authentication method from Digest or Digest or Basic.<sup>25</sup>\* Video may move at some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.<sup>26</sup>\* Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh Interval(JPEG). Less than 1fps cannot be selected.<sup>27</sup>\* Restrictions is still under study. Will be updated.<sup>28</sup>\* Support G.726 for WV-V230LV/V1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.<sup>29</sup>\* Support WV-CU950/CU960

	Function	WV-S1550L	WV-S1531LN/S1531LTN/ S1531LNS	WV-S1511LN	WV-U1542LA/U1532LA	WV-U1542L	WV-U1532L	WV-S1136	WV-S1132/S1131	WV-S1112/S1111	WV-U1142A/U1132A/ U1130A	WV-U1142	WV-U1132/U1130	WV-X2551LN/X2251L	WV-S2552L/S2252L	WV-S2550L/S2250L
WV-ASH300 (VS.10)	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	yes -	yes yes yes yes yes	yes yes yes yes yes	yes -	yes yes	yes -	yes yes yes yes yes	yes yes yes yes yes	yes -	yes yes yes yes yes	yes -	yes yes yes yes yes	yes -	yes yes yes yes yes	
Direct connection to camera	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WV-ASH200 (VS.10) *24	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASH100 (Ver8.00) *5,*14,*24	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASC970 (Ver19.00)	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Direct connection to camera (Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WJ-GX4040 (Ver2.21) *6,*14,*20	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BB-HNP17 (Ver4.06)	MJPEG MPEG4 H.264 H.265 Audio*8 PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.

\*1 : Only for remote PTZ cameras.

\*5 : WV-ASH100 does not support displaying 16:9.

\*6 : Supported resolutions of WJ-GX4040 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.

\*7 : Supported functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.

\*8 : Supported G.726.

\*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.

\*14 : Streams of H.264(3) and H.264(4) are not supported.

\*16 : When using multiple streams, 1280x960 resolution, please use a 64 bit OS and 4GB or more memory.

\*19 : Supported maximum bitrate is 14Mbps.

\*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.

\*21 : Only for remote PTZ cameras.

\*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.

\*23 : Supported G.726 or AAC.

\*25 : Please connect to the cameras from the PC browser and change the authentication method from Digest or Digest or Basic.

\*25 : Video may take some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.

\*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh Interval(JPEG). Less than 1fps cannot be selected.

\*27 : Restrictions is still under study. Will be updated.

\*28 : Support G.726 for WV-V2530LV/V1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.

\*29 : Support WV-CU950/CU980

	Function	WV-S2531LN/S2531LTN	WV-S2511LN	WV-U2542LA/U2540LA/U2532LA/U2530LA	WV-U2542L/U2540L/U2532L/U2530L	WV-S2136/S2136L	WV-S2236L	WV-S2131L/S2131/S2130L	WV-S2111L/S2110L/S2211L	WV-U2142LA/U2140LA/U2132LA/U2130LA	WV-U2142L/U2140L	WV-U2132L/U2130L	WV-S3531L/S3511L	WV-S3532LM/S3512LM	WV-S3131L/S3111L	V series
Direct connection to camera	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes *26
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	-	yes	yes	yes	yes	-	-	yes	yes	yes	yes	-
	H.265	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes *27
	Audio*8	yes	yes	-	-	yes	yes	yes	yes	-	-	yes	yes	yes	yes	yes *28
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	yes *1*29
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	-
Direct connection to camera (Discontinued model)	MJPEG	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	-	yes *26
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	-	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	-	yes *28
	PTZ	-	-	-	-	-	-	yes	-	-	-	-	-	-	-	yes *1*29
	RTP over HTTP	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	-	-
WV-ASH100 (Ver8.00) *5,*14,*24	MJPEG	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WV-ASC970 (Ver19.001) Direct connection to camera (Discontinued model)	MJPEG	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	-	-
	H.265	-	yes	-	-	-	-	yes	yes	-	-	-	-	-	-	-
	Audio*8	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	-	-
WJ-GX4040 (Ver2.21) *6,*14,*20 (Discontinued model)	MJPEG	yes	yes	-	-	-	-	yes	yes	-	-	yes	yes	yes	yes	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	-	-	-	-	yes	yes	-	-	yes	yes	yes	yes	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	yes	yes	-	-	-	-	yes	yes	-	-	yes	yes	yes	yes	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	-	-	-	-	yes	yes	-	-	yes	yes	yes	yes	-
BB-HNP17 (Ver4.06) (Discontinued model)	MJPEG	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	-	-
	MPEG4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	-	-	-	-	yes	yes	-	-	-	-	-	-	-
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.

<sup>1</sup> Only for remote PTZ cameras.<sup>5</sup> WV-ASH100 does not support displaying 16:9.<sup>6</sup> Supported resolutions of WJ-GX4040 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.<sup>7</sup> Supported functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.<sup>8</sup> Supported G.726.<sup>9</sup> Supported G.726 as an Audio and MPEG4/H.264 as a Video.<sup>14</sup> : Streams of H.264(3) and H.264(4) are not supported.<sup>15</sup> : When displaying the stream of 1280x960 resolution, please use a 64 bit OS and 4GB or more memory.<sup>19</sup> : Supported maximum bitrate is 14Mbps.<sup>20</sup> : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.<sup>21</sup> : Only for remote PTZ cameras.<sup>22</sup> : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.<sup>23</sup> : Supported G.726 or AAC.<sup>24</sup> : Please connect to the cameras from the PC browser and change the authentication method from Digest or Digest or Basic.<sup>25</sup> : Video may move at some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.<sup>26</sup> : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh Interval(JPEG). Less than 1fps cannot be selected.<sup>27</sup> : Restrictions is still under study. Will be updated.<sup>28</sup> : Support G.726 for WV-V230LV/V1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.<sup>29</sup> : Support WV-CU950/CU980

	Function	WV-SBV131M/SBV111M	WV-SW598/SW598A/SCS8/SCS8A	WV-SW397/SW397A/SW397B/SC387/SC387A	WV-SW396/SW395/SC386/SC385/SC384	WV-SPW631LT/SPW631L	WV-SPW531AL/SPW531AL	WV-SPW532L/SPW532L	WV-SPW311LH	WV-SW316/SW316	WV-SW314	WV-SPN611/SPN631	WV-SPN531/SPN531A	WV-SPN310/SPN311/SPN310A/SPN311A	WV-SP509	WV-SP508
Direct connection to camera	MJPEG	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	yes	-	-	-	yes	-	-	-	-	-	-	-
	H.264	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	yes	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	yes	yes	yes	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
(Discontinued model)	WV-ASH200 (Ver5.10) *24	MJPEG	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	yes	-	-	-	-	yes	-	-	-	-	-	-
	H.264	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	yes	yes	yes	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	WV-ASH100 (Ver8.00) *5,*14,*24	MJPEG	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	yes	-	-	-	-	yes	yes	yes	yes	yes	yes	yes
	H.264	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	yes	yes	yes	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	WV-ASC970 (Ver19.00)	MJPEG	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	yes	-	-	-	-	yes	-	-	-	-	-	-
	H.264	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	yes	yes	yes	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	WJ-GX400 (Ver2.21) *6,*14,*20	MJPEG	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	yes	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	yes	yes	yes	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model)	BB-HNP17 (Ver4.06)	MJPEG	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	-	-	-	yes	-	-	-	-	-	-	-	-	-	-	-
	H.264	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	PTZ	-	yes	yes	yes	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.

\*1 : Only for remote PTZ cameras.

\*2 : WV-AS970 does not support displaying 16:9.

\*6 : Supported resolutions of WJ-GX400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.

\*7 : Supported functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.

\*8 : Supported G.726

\*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.

\*14 : Streams of H.264(3) and H.264(4) are not supported.

\*16 : H.265 streams of 1920x1080 resolution, please use a 64 bit OS and 4GB or more memory.

\*19 : Supported maximum bitrate is 14Mbps.

\*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.

\*21 : Only for remote PTZ cameras.

\*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.

\*23 : Supported G.726 or AAC.

\*24 : Remote control to the cameras from the PC browser and change the authentication method from Digest or Digest or Basic.

\*25 : Video may move at some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.

\*26 : Support "VGA/40x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh Interval(JPEG). Less than 1fps cannot be selected.

\*27 : Restrictions is still under study. Will be updated.

\*28 : Support G.726 for WV-V230LV/KV1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.

\*29 : Support WV-CU390/CU390

	Function	WV-SP300 series	WV-SP105/SP102	WV-NP502	WV-SFN611/SFN631L/SFR611L/SFR631L/SFV611L/SFV631L/SFV631LT	WV-SFN531/SFR531/SFV531	WV-SFN311/SFN310/SFR311/SFR310/SFV311/SFV310	WV-SFN311A/SFN310A/SFR311A/SFR310A/SFV311A/SFV310A	WV-SW559/SF549/SF539	WV-SW558/SF548/SF538	WV-SW355/SW352/SF346/SF342	WV-SF330 series	WV-NW502S	WV-SFV130(M)/SFV110(M)	WV-SFN130/SFN110	WV-SW158/SF138
Direct connection to camera	MJPEG	yes	-	yes	-	yes	-	yes	-	yes	-	yes	-	yes	-	yes
	MPEG4	yes	-	yes	-	yes	-	yes	-	yes	-	yes	-	yes	-	yes
	H.264	yes	yes	yes	-	yes	-	yes	-	yes	-	yes	-	yes	-	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
(Discontinued model) WV-ASH200 (Ver5.10) *24	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	yes	-	yes	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
(Discontinued model) WV-ASH100 (Ver8.00) *5,*14,*24	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	yes	-	yes	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model) WV-ASC970 (Ver19.00)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	yes	-	yes	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model) WJ-GX4040 (Ver2.21) *6,*14,*20	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	yes	-	yes	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Discontinued model) BB-HNP17 (Ver4.06)	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	MPEG4	yes	-	yes	-	-	-	-	-	-	-	-	-	-	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	H.265	*25	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	Audio*8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	PTZ	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.

\*1 : Only for remote PTZ cameras.

\*2 : WV-AS6100 does not support displaying 16:9.

\*6 : Supported resolutions of WJ-GX4040 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.

\*7 : Supported functions are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.

\*8 : Supported G.726

\*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.

\*14 : Streams of H.264(3) and H.264(4) are not supported.

\*16 : H.264 streams of 1920x1080 resolution, or H.265 streams of 1920x992 resolution, please use a 64 bit OS and 4GB or more memory.

\*19 : Supported maximum bitrate is 14Mbps.

\*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.

\*21 : Only for remote PTZ cameras.

\*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.

\*23 : Supported G.726 or AAC.

\*24 : Remote connection to the cameras from the PC browser and change the authentication method from Digest or Digest + Basic.

\*25 : Video may move at some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.

\*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh Interval(JPEG). Less than 1fps cannot be selected.

\*27 : Restrictions is still under study. Will be updated.

\*28 : Support G.726 for WV-V230LV/KV1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.

\*29 : Support WV-CU950/CU980

	Function	WV-SW155/SW155MA/SW152/SF135/SF132/SW115	WV-SW175/SW172/SI165/SI162	WV-SW174W	BB-HCM7 series	BB-HCM5 series	WV-SMR10/SMR10N3	WJ-GXE500	WJ-GXE100
Direct connection to camera	MJPEG	yes	yes	-	-	-	-	yes	yes
	MPEG4	-	-	-	-	-	-	yes	-
	H.264	yes	yes	yes	-	-	-	yes	yes
	H.265	-	-	-	-	-	-	-	-
	Audio*8	-	-	-	-	-	-	-	-
	PTZ	-	yes	yes	-	-	-	yes	yes
	RTP over HTTP	yes	yes	-	-	-	-	yes	yes
Direct connection to camera (Discontinued model)	MJPEG	yes	yes	yes	-	-	-	yes	yes
	MPEG4	-	-	-	-	-	-	yes	-
	H.264	yes	yes	yes	-	-	-	yes	yes
	H.265	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	-	-	yes (ch1)	-	-
	PTZ	-	yes	yes	-	-	-	yes	-
	RTP over HTTP	yes	yes	-	-	-	-	-	-
WV-AS100 (Ver8.00) *5,*14,*24 (Discontinued model)	MJPEG	yes	yes	-	-	-	-	yes	yes
	MPEG4	-	-	-	-	-	-	yes	-
	H.264	yes	yes	yes	-	-	-	yes	-
	H.265	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	-	-	-	-	-
	PTZ	-	yes	yes	-	-	yes (ch1)	-	-
	RTP over HTTP	-	-	-	-	-	-	-	-
WV-ASC970 (Ver19.001) (Discontinued model)	MJPEG	yes	yes	-	-	-	-	yes	yes
	MPEG4	-	-	-	-	-	-	yes	-
	H.264	yes	yes	yes	-	-	-	yes	yes
	H.265	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	-	-	-	yes (ch1)	-
	PTZ	-	yes	yes	-	-	-	yes	-
	RTP over HTTP	yes	yes	-	-	-	-	yes	yes
WJ-GXD400 (Ver2.21) *6,*14,*20 (Discontinued model)	MJPEG	yes	yes	yes	-	-	-	yes	yes
	MPEG4	-	-	-	-	-	-	yes	-
	H.264	yes	yes	yes	-	-	-	yes	yes
	H.265	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	-	-	-	yes (ch1)	-
	PTZ	-	yes	yes	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	yes	yes
BB-HNP17 (Ver4.06) (Discontinued model)	MJPEG	yes	yes	yes	yes	yes	-	yes	yes
	MPEG4	-	-	-	-	-	-	yes	-
	H.264	yes	yes	yes	-	-	-	yes	yes
	H.265	-	-	-	-	-	-	-	-
	Audio*8	-	yes	yes	yes	yes	-	yes (ch1)	-
	PTZ	-	yes	yes	-	-	-	-	-
	RTP over HTTP	-	-	-	-	-	-	yes	yes

Discontinued model might have the function which doesn't work.

\*1 : Only for remote PTZ cameras.

\*5 : WV-AS100 does not support displaying 16:9.

\*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.

\*7 : Supported frame rate are different depending on the "Image capture mode". For details on "Image capture mode", please refer to the operating instructions.

\*8 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.

\*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.

\*10 : Streams of H.264(3) and H.264(4) are not supported.

\*11 : H.264 streams of 1280x960 resolution, please use a 64 bit OS and 4GB or more memory.

\*19 : Supported maximum bitrate is 14Mbps.

\*20 : Supported maximum bitrate is 8Mbps. Supported maximum resolution is 1280x960.

\*21 : WV-ASC970 only.

\*22 : Pan/Tilt button can use, only when the capture mode is cropping of H.264 stream. Zoom button cannot use.

\*23 : Supported G.726 or AAC.

\*24 : Remote control to the cameras from the PC browser and change the authentication method from Digest or Basic.

\*25 : Video output may take some time depending on the frame rate used. Also, depending on the camera model, video may be delayed.

\*26 : Support "VGA/640x360 and QVGA. Auto is not supported. Supported from 1fps to 30fps for Refresh Interval(JPEG). Less than 1fps cannot be selected.

\*27 : Restrictions is still under study. Will be updated.

\*28 : Support G.726 for WV-V230LV/KV1170/V6430L. "Audio output" is not supported. Only "Mic input" can be used.

\*29 : Support WV-CU950/CU980

	Function	WJ-NU101K/KG WJ-NU201K/KG WJ-NU300K/KG WJ-NU301K/KG	WJ-NX400	WJ-NX300	WJ-NX200	WJ-NV300	WJ-NV200	WJ-ND400K	WJ-ND300A	WJ-HD616/HD716	WJ-HD300 (Discontinued model)
Via Recorder	MJPEG	yes	yes	yes	yes	yes	yes	yes	yes	-	-
	MPEG4	-	-	-	-	-	yes	yes	yes	-	-
	H.264	yes	yes	yes	yes	yes	yes	yes	yes	yes	-
	H.265	yes	yes	yes	yes	-	-	-	-	-	-
	Original	-	-	-	-	-	-	-	-	-	yes
	Audio	Live/Playback(Receive)*11	Live/Playback(Receive)*10	Live/Playback(Receive)*10	Live/Playback(Receive)*10	Live/Playback(Receive)*8	Live/Playback(Receive)*8	Live/Playback(Receive)*8	-	Live/Playback(Receive)*8	-
	PTZ	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
	VMD	yes	yes	yes	yes	yes	yes	-	-	yes	-
	RTP over HTTP	yes	yes	yes	yes	yes	yes	-	-	yes	-
Via Recorder (Discontinued model)	MJPEG	-	-	-	-	yes	yes	yes	yes	-	-
	MPEG4	-	-	-	-	-	yes	yes	yes	-	-
	H.264	-	-	-	-	yes	yes	yes	yes	yes	-
	H.265	-	-	-	-	-	-	-	-	-	-
	Original	-	-	-	-	-	-	-	-	-	yes
	Audio*8	-	-	-	-	Live/Playback(Receive)	Live/Playback(Receive)	Live/Playback(Receive)	-	Live/Playback(Receive)	-
	PTZ	-	-	-	-	yes	yes	yes	yes	yes	yes
Via Recorder (Discontinued model)	VMD	-	-	-	-	yes	yes	-	-	yes	-
	RTP over HTTP	-	-	-	-	yes	yes	-	-	yes	-
WV-ASM100 (Ver8.00)	MJPEG	-	-	-	-	-	yes	yes	yes	-	-
	MPEG4	-	-	-	-	-	yes	yes	yes	-	-
	H.264	-	-	-	-	-	yes	yes	yes	yes	-
	H.265	-	-	-	-	-	-	-	-	-	-
	Original	-	-	-	-	-	-	-	-	-	yes
	Audio*8	-	-	-	-	-	Live/Playback(Receive)	Live/Playback(Receive)	-	Live/Playback(Receive)	-
	PTZ	-	-	-	-	-	yes	yes	yes	yes	yes
WV-ASM970 (Ver19.00)	VMD	-	-	-	-	-	yes	yes	-	-	-
	RTP over HTTP	-	-	-	-	-	yes	yes	-	-	-
(Discontinued model)	MJPEG	-	yes	-	-	yes	yes	yes	yes (Playback only)	-	-
	MPEG4	-	-	-	-	-	yes	yes	yes (Playback only)	-	-
	H.264	-	yes	-	-	yes	yes	yes	yes (Playback only)	-	-
	H.265	-	-	-	-	-	-	-	-	-	-
	Original	-	-	-	-	-	-	-	-	-	yes
	Audio*8	-	Live/Playback(Receive)	-	-	Live/Playback(Receive)	Playback(Receive)	Playback(Receive)	-	Playback(Receive)	-
	PTZ	-	yes	-	-	yes	yes	-	-	yes	yes
WJ-GXD400 (Ver2.21) *6	VMD	-	yes	-	-	yes	yes	-	-	yes	-
	RTP over HTTP	-	yes	-	-	yes	yes	-	-	yes	-
(Discontinued model)	MJPEG	-	-	-	-	-	-	yes	yes (Playback only)	-	-
	MPEG4	-	-	-	-	-	-	yes	yes (Playback only)	-	-
	H.264	-	-	-	-	-	-	yes	yes (Playback only)	-	-
	H.265	-	-	-	-	-	-	yes	yes (Playback only)	yes	-
	Original	-	-	-	-	-	-	-	-	-	yes
	Audio*9	-	-	-	-	-	-	Playback(Receive)	-	Playback(Receive)	-
	PTZ	-	-	-	-	-	-	yes	-	yes	yes
WJ-GXD400 (Discontinued model)	VMD	-	-	-	-	-	-	yes	-	yes	-
	RTP over HTTP	-	-	-	-	-	-	-	-	-	-

Discontinued model might have the function which doesn't work.

\*6 : Supported resolutions of WJ-GXD400 are only 1280x960, VGA and QVGA. Supported maximum bitrate is 8Mbps.

\*8 : Supported only G.726.

\*9 : Supported G.726 as an Audio and MPEG4/H.264 as a Video.

\*10 : Supported G.726 or AAC.

\*11 : Supported only AAC.

**Symbol description**

○ : Supported

x : Non supported

- : Non feature