

advidia



PRODUCT LINEUP



Network Camera

The advidia line of IP network video surveillance cameras provides a wide range of affordable IP camera models that are perfect for video surveillance projects of any size.



Dome Camera

IP Dome Cameras are the universal video surveillance camera. They include different features including built-in Mics, fixed, or motorized lens



PTZ Camera

The advidia PTZ network camera delivers unparalleled image quality, versatility, and 25x optical zoom control.



Bullet Camera

Bullet cameras are a cost-effective video surveillance solution. Perfect for indoor and outdoor applications. Bullet Cameras deliver crisp, clear images.

Network Video Recorder

The advidia network video recorder has high quality genes to ensure the reliability of devices and the whole system, focusing on user experience to simplify every operation process. It is embedded with the PoE function for better usability, reliability, and capability.



Network Video Recorder has 8/16 channel input and independent PoE network interfaces to support different demands and needs



Network Video Recorder has 32/64 channels input to support different demands and needs



YouTube

advidia NVR
unboxing video



2MP Camera



MODEL		M-26-FW-V2	M-26-V-V2
TYPE		DOME	DOME
Resolution		2MP	2MP
Environmental Type		Indoor Outdoor	Indoor Outdoor
Sensor		1/2.8" progressive Scan CMOS	1/2.7" progressive Scan CMOS
Video Codec		H.265 / H.264 / MJPEG	H.265 / H.264 / MJPEG
Max. Resolution		1920 x 1080	1920 x 1080
Max. FPS @ Max. Resolution	H.265 / H.264 / JPEG	30fps @ (1920 x 1080)	30fps @ (1920 x 1080)
WDR		120dB	120dB
Day/Night ICR / IR		Yes	Yes
ABF (Auto Back Focus) / Auto Focus		Fixed	Auto Focus
Min. Illumination	Color	0.003Lux (F1.6, AGC ON)	0.01Lux (F2.0, AGC ON)
	B/W	0 Lux with IR	0 Lux with IR
Lens		f= 2.8 mm, F2.0	2.8 to 12mm
Horizontal field of view	16: 9	103.6° to 33.4°	112.9°
Adjusting Angle	Pan	3° to 360°	8° to 360°
	Tilt	0° to 70°	0° to 68°
Optical Zoom		-	4.2 x
ONVIF		G, S, T	G, S, T
Built-in IR LED		Yes (30 m)	Yes (40 m)
Image Stabilizer		-	-
Corridor Mode		Yes	Yes
VMD (Video Motion Detection)		Yes	Yes
Analytics		Motion detection, Ultra motion detection, Tampering alarm, Audio detection, Cross line, Intrusion (based on human body detection)	Cross Line, Intrusion, (Based on Human Body detection), Motion Detection, Tampering Alarm, Audio Detection
Max. Connection		6 Mbps	6 Mbps
Audio	In (Line) / Out	Yes	-
	In (Built-in MIC)	Yes	Yes
	Codec	G.711U, G.711A	G.711U, G.711A
SD memory Card	Slot	Micro SD, up to 512GB	Micro SD, up to 512GB
External I/O		-	Yes
Monitor Out		-	-
Vandal Resistant		IK10	IK10
Water and Dust Resistance		IP67	IP67
Temperature		-30°C to +60°C	-30°C to +60°C
Power Source		DC12V±25%, PoE 802.3af Power consumption: Max 3.5W	DC12V±25%, PoE 802.3af Power consumption: Max 8W

For model and stock availability, please reach out to your regional Sales Representative.

advidia

2MP Camera



MODEL		M-29-FW-V2	M-29-V-V2
TYPE		BULLET	BULLET
Resolution		2MP	2MP
Environmental Type		Indoor Outdoor	Indoor Outdoor
Sensor		1/2.8" progressive Scan CMOS	1/2.7" progressive Scan CMOS
Video Codec		H.265 / H.264 / MJPEG	H.265 / H.264 / MJPEG
Max. Resolution		1920 x 1080	1920 x 1080
Max. FPS @ Max. Resolution	H.265 / H.264 / JPEG	30fps @ (1920 x 1080)	30fps @ (1920 x 1080)
WDR		120dB	120dB
Day/Night ICR / IR		Yes	Yes
ABF (Auto Back Focus) / Auto Focus		Fixed	Fixed
Min. Illumination	Color	0.01Lux (F2.0, AGC ON)	0.003Lux (F1.6, AGC ON)
	B/W	0 Lux with IR	0 Lux with IR
Lens		f= 2.8 mm, F2.0	2.8 to 12mm
Horizontal field of view	16: 9	112.9°	103.6° to 33.4°
Adjusting Angle	Pan	0° to 360°	0° to 360°
	Tilt	0° to 90°	0° to 90°
Optical Zoom		-	4.2 x
ONVIF		G, S, T	G, S, T
Built-in IR LED		Yes (30 m)	Yes (50 m)
Image Stabilizer		-	-
Corridor Mode		Yes	Yes
VMD (Video Motion Detection)		Yes	Yes
Analytics		Motion detection, Ultra motion detection, Tampering alarm, Audio detection, Cross line, Intrusion (Based on Human Body detection)	Motion detection, Ultra motion detection, Tampering alarm, Audio detection, Cross line, Intrusion (based on human body detection)
Max. Connection		6 Mbps	6 Mbps
Audio	In (Line) / Out	-	Yes
	In (Built-in MIC)	Yes	Yes
	Codec	G.711U, G.711A	G.711U, G.711A
SD memory Card	Slot	Micro SD, up to 512GB	Micro SD, up to 512GB
External I/O		-	Yes
Monitor Out		-	-
Vandal Resistant		-	-
Water and Dust Resistance		IP67	IP67
Temperature		-30°C to +60°C	-30°C to +60°C
Power Source		DC12V±25%, PoE 802.3af Power consumption: Max 3.5W	DC12V±25%, PoE 802.3af Power consumption: Max 9.6W

For model and stock availability, please reach out to your regional Sales Representative.

4MP Camera



MODEL		M-46-FW-V3	M-46-V-V2
TYPE		DOME	
Resolution		4MP	4MP
Environmental Type		Indoor Outdoor	Indoor Outdoor
Sensor		1/2.7" progressive Scan CMOS	1/3" progressive Scan CMOS
Video Codec		H.265 / H.264 / MJPEG	H.265 / H.264 / MJPEG
Max. Resolution		2688 x 1520	2688 x 1520
Max. FPS @ Max. Resolution	H.265 / H.264 / JPEG	25fps @ (2688 x 1520)	25fps @ (2688 x 1520)
True WDR		True WDR @ 120dB	True WDR @ 120dB
Day/Night ICR / IR		Yes	Yes
ABF (Auto Back Focus) / Auto Focus		Fixed	Auto Focus
Min. Illumination	Color	0.003Lux (F1.6, AGC ON)	0.003Lux (F1.6, AGC ON)
	B/W	0 Lux with IR	0 Lux with IR
Lens		f= 2.8 mm, F1.6	2.8mm to 12mm
Horizontal field of view	16: 9	110.0° x 58.7°	86.3° to 35.2°
Adjusting Angle	Pan	8° to 360°	3° to 360°
	Tilt	0° to 68°	0° to 70°
Optical Zoom		-	4.2 x
ONVIF		G, S, T	G, S, T
Built-in IR LED		Yes (30 m)	Yes (40 m)
Image Stabilizer		-	-
Corridor Mode		Yes	Yes
VMD (Video Motion Detection)		Yes	Yes
Analytics		Crossline, Intrusion (Based on Human Body Detection), Motion Detection, Ultra motion detection, Tampering Alarm, Audio Detection	Cross line, Intrusion (Based on Human Body Detection), Motion Detection, Tampering Alarm, Audio detection
Max. Connection		6 Mbps	6Mbps
Audio	In (Line) / Out	-	Yes
	In (Built-in MIC)	Yes	Yes
	Codec	G.711U, G.711A	G.711U
SD memory Card	Slot	Micro SD, up to 512GB	Micro SD, up to 256GB
External I/O		-	1 in / 1 out
Monitor Out		-	-
Vandal Resistant		IK10	IK10
Water and Dust Resistance		IP67	IP67
Temperature		-30°C to +60°C	-30°C to +60°C
Power Source		DC12V±25%, PoE 802.3af Power consumption: Max 4.4W	DC12V±25%, PoE 802.3af Power consumption: Max 8.0W

For model and stock availability, please reach out to your regional Sales Representatives.

4MP Camera



MODEL		M-49-FW-V2	M-49-V-V2
TYPE		BULLET	BULLET
Resolution		4MP	4MP
Environmental Type		Indoor Outdoor	Indoor Outdoor
Sensor		1/2.7" progressive Scan CMOS	1/3" progressive Scan CMOS
Video Codec		H.265 / H.264 / MJPEG	H.265 / H.264 / MJPEG
Max. Resolution		2688 x 1520	2688 x 1520
Max. FPS @ Max. Resolution	H.265 / H.264 / JPEG	25fps @ (2688 x 1520)	25fps @ (2688 x 1520)
True WDR		True WDR @ 120dB	True WDR @ 120dB
Day/Night ICR / IR		Yes	Yes
ABF (Auto Back Focus)/ Auto Focus		Fixed	Auto Focus
Min. Illumination	Color	0.003Lux (F1.6, AGC ON)	0.003Lux (F1.6, AGC ON)
	B/W	0 Lux with IR	0 Lux with IR
Lens		f= 2.8 mm, F1.6	2.8mm to 12mm
Horizontal field of view	16: 9	110.0°	86.3° to 35.2°
Adjusting Angle	Pan	0° to 360°	0° to 360°
	Tilt	0° to 90°	0° to 90°
Optical Zoom		-	4.2 x
ONVIF		G, S, T	G, S, T
Built-in IR LED		Yes (50 m)	Yes (50 m)
Image Stabilizer		-	-
Corridor Mode		Yes	Yes
VMD (Video Motion Detection)		Yes	Yes
Analytics		Crossline, Intrusion (Based on Human Body Detection) Motion Detection, Ultra Motion Detection Tampering Alarm, Audio detection	Crossline, Intrusion (Based on Human Body Detection) Motion Detection, Ultra Motion Detection Tampering Alarm, Audio detection
Max. Connection		6 Mbps	6Mbps
Audio	In (Line) / Out	-	Yes
	In (Built-in MIC)	Yes	Yes
	Codec	G.711U, G.711A	G.711U, G.711A
SD memory Card	Slot	Micro SD, up to 512GB	Micro SD, up to 256GB
External I/O		-	Yes (1in / 1out)
Monitor Out		-	-
Vandal Resistant		-	-
Water and Dust Resistance		IP67	IP67
Temperature		-30°C ~ +60°C	-30°C ~ +60°C
Power Source		DC12V±25%, PoE 802.3af Power consumption: Max 5.6W	DC12V±25%, PoE 802.3af Power consumption: Max 9.6W

For model and stock availability, please reach out to your regional Sales Representatives.

advidia

4K Camera



MODEL		M-87-V
TYPE		DOME
Resolution		8MP (4K)
Environmental Type		Indoor Outdoor
Sensor		1/2.8" progressive Scan CMOS
Video Codec		H.265 / H.264 / MJPEG
Max. Resolution		3840 x 2160
Max. FPS @ Max. Resolution	H.265 / H.264 / JPEG	20fps @ (3840 x 2160)
True WDR		True WDR @ 120dB
Day/Night ICR / IR		Yes
ABF (Auto Back Focus) / Auto Focus		Auto Focus
Min. Illumination	Color	0.003Lux (F1.6, AGC ON)
	B/W	0 Lux with IR
Lens		2.8 to 12mm
Horizontal field of view	16: 9	107.4° to 29.2°
Adjusting Angle	Pan	0° to 355
	Tilt	0° to 80°
Optical Zoom		4.2 x
ONVIF		G, S, T
Built-in IR LED		Yes (40 m)
Image Stabilizer		-
Corridor Mode		Yes
VMD (Video Motion Detection)		Yes
Analytics		Cross Line, Intrusion, Enter Area, Leave Area Detection, Motion Detection, Tampering Alarm, Audio Detection
Max. Connection		16 Mbps
Audio	In (Line) / Out	1/1
	In (Built-in MIC)	Yes
	Codec	G.711
SD memory Card	Slot	Micro SD, up to 256GB
External I/O		-
Monitor Out		-
Vandal Resistant		IK10
Water and Dust Resistance		IP67
Temperature		-30°C to +60°C
Power Source		DC12V±25%, PoE 802.3af Power consumption: Max 9W

For model and stock availability, please reach out to your regional Sales Representative.

PTZ Camera



MODEL	M-400-P	
TYPE	PTZ	
Resolution	4MP	
Environmental Type	Indoor Outdoor	
Sensor	1/2.8" progressive Scan CMOS	
Video Codec	H.265/H.264/MJPEG	
Max. Resolution	2688 x 1520	
Max. FPS @ Max. Resolution	H.265 / H.264 / JPEG	30fps @ (2688 x 1520)
True WDR	True WDR @ 120dB	
Day/Night ICR / IR	Yes (ICR)	
ABF (Auto Back Focus) / Auto Focus	Auto Focus	
Min. Illumination	Color	0.003Lux (F1.5, AGC ON)
	B/W	0 Lux with IR
Lens	4.8mm to 120mm	
Horizontal field of view	16: 9	52.2° to 2.74°
	Pan	360° Endless
Adjusting Angle	Tilt	-15 to +90 deg. Auto flip
	Optical Zoom	25X
Digital Zoom	16X	
ONVIF	G, S, T	
Built-in IR LED	Yes (100m)	
Image Stabilizer	-	
Corridor Mode	-	
VMD (Video Motion Detection)	Yes	
Analytics	Motion detection, Audio detection, Tampering Alarm Support false alarm filtering: Line crossing detection, Intrusion detection, Enter Area detection, Leave Area detection	
Max. Connection	16 Mbps	
Audio	In (Line) / Out	1/1
	In (Built-in MIC)	-
	Codec	G.711U/G.711A
SD memory Card	Slot	Micro SD, up to 256GB
External I/O	Yes (2in / 1out)	
Monitor Out	1 BNC	
Vandal Resistant	IK10	
Water and Dust Resistance	IP67	
Temperature	-40°C ~ +70°C	
Power Source	DC12V±25% 3A, PoE+ 802.3af Power consumption: Max 21.0W	

For model and stock availability, please reach out to your regional Sales Representative.

advidia

NVR



MODEL		M-NVR-8CH-8POE	M-NVR-16CH-16POE-V2
Video / Audio Input	IP Video Input	8-ch	16-ch
	Two-way Audio Input	-	1-ch, RCA
	HDMI/VGA Output	HDMI:3840x2160/30Hz, 1920x1080p/60Hz,1920x1080p/50Hz, 1600x1200/60Hz,1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz,1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	HDMI: 4K (3840x2160)/30Hz, 1920X1080/60Hz,1920X1080/50Hz, 1600X1200/60Hz,1280X1024/60Hz, 1280X720/60Hz, 1024X768/60Hz VGA: 1920X1080/60Hz, 1920X1080/50Hz, 1280X1024/60Hz,1280X720/60Hz, 1024X768/60Hz
	Recording Resolution	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Audio Output	1-ch, RCA	1-ch, RCA
Network	Incoming / Outgoing Bandwidth	64Mbps / 48Mbps	320Mbps / 160MBPS
	Protocols	HTTP, RTSP, SMTP, DNS, DDNS, FTP, P2P, UPnP, NTP, DHCP, PPPoE	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, RTSP, IPv6, IPv4
ONVIF	Profile	G, S, T	G, S, T
Decoding	Decoding Format	H.265/H.264	H.265/H.264
	Live view/Playback	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF/CIF
Hard Disk	SATA	1 SATA interface	2 SATA interfaces
	Capacity	Up to 6TB	up to 16TB for each disk
Video Analytics	VCA Detection	Motion detection, Tampering detection, Intrusion detection, Cross line detection, Human body detection, Audio detection, Face detection	Motion detection, Tampering detection, Intrusion detection, Cross line detection, Audio detection, Face detection, Auto tracking
External Interface	Network Interface	1x 10BASE-T / 100BASE-TX (RJ45)	1x 10BASE-T / 100BASE-TX /
	USB Interface	Rear panel: 2 x USB2.0	Front panel: 1 x USB2.0 Rear panel: 2 x USB3.0
	Alarm in / Alarm Out	-	8-ch / 2-ch
POE	Max Power	Max 30W for single port Max 75W in total	Max 30W for single port Max 240W in total
	Supported Standard	IEEE 802.3at, IEEE 802.3af	IEEE 802.3at, IEEE 802.3af
	Interface	8x 10BASE-T / 100BASE-TX (RJ45)	16x 10BASE-T / 100BASE-TX (RJ45)
General	Power Supply	52V DC Power Consumption: ≤9 W (without HDD)	100-240V AC Power Consumption: ≤10 W (without HDD)
	Working Environment	-10°C~+ 55°C, Humidity ≤ 90% RH (non-condensing)	-10°C~+ 55°C, Humidity ≤ 90% RH (non-condensing)
	Dimensions (WxD×H)	260mm ×240mm × 46 mm (10.2" × 9.4" × 1.8")	380mm × 322mm × 53mm (15.0"12.7"2.1")
	Weight (without HDD)	≤1.1kg (2.43lb)	≤2.6kg (5.73lb)

For model and stock availability, please reach out to your regional Sales Representative.

advidea

NVR




















MODEL		M-NVR-32CH-V2	M-NVR-64CH
Video / Audio Input	IP Video Input	32-ch	64-ch
	Two-way Audio Input	1-ch, RCA	1-ch, RCA
	HDMI/VGA Output	HDMI 1 / HDMI 2 4K (3840x2160)/60Hz 4K (3840x2160)/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz VGA 1/ VGA 2: 1920x1080/60Hz, 1920x1080/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz, 1600x1200/60Hz	HDMI 1/ HDMI 2 4K(3840x2160)/60Hz, 4K(3840x2160)/30Hz, 1920X1080/60Hz, 1920X1080/50Hz, 1600X1200/60Hz, 1280X1024/60Hz, 1280X720/60Hz, 1024X768/60Hz VGA 1/ VGA 2: 1920X1080/60Hz, 1920X1080/50Hz, 1600X1200/60Hz, 1280X1024/60Hz, 1280X720/60Hz, 1024X768/60Hz
	Recording Resolution	32MP/16MP/12MP/8MP/6MP/5MP/4MP/ 3MP/1080p/960p/720p/D1/2CIF/CIF	32MP/16MP/12MP/8MP/6MP/5MP/4MP/ 3MP/1080p/960p/720p/D1/2CIF/CIF
Network	Audio Output	2-ch, RCA	2-ch, RCA
	Incoming / Outgoing Bandwidth	384Mbps/384Mbps	384Mbps/384Mbps
ONVIF	Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS, RTSP, 802.1x, IPv6, IPv4	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS, RTSP, 802.1x, IPv6, IPv4
	Profile	G, S, T	G, S, T
Decoding	Decoding Format	H.265/H.264	H.265/H.264
	Live view/Playback	32MP/16MP/12MP/8MP/6MP/5MP/4MP/ 3MP/1080p/960p/720p/D1/2CIF/CIF	32MP/16MP/12MP/8MP/6MP/5MP/4MP/ 3MP/1080p/960p/720p/D1/2CIF/CIF 13MP/1080P/960P/720P/D1/2CIF/CIF
Hard Disk	SATA	8 SATA interfaces	8 SATA interfaces
	Capacity	Up to 16TB for each disk	Up to 16TB for each disk
Disk Array	Array Type	RAID 0, 1, 5, 6, 10	RAID 0, 1, 5, 6, 10
Video Analytics	VCA Detection	Motion detection, Tampering detection, Intrusion detection, Crossline detection, Audio detection, Face detection, Auto tracking	Motion detection, Tampering detection, Intrusion detection, Crossline detection, Audio detection, Face detection, Auto tracking
Eternal Interface	Network Interface	2 RJ45 10M/100M/1000M	2 RJ45 10M/100M/1000M
	USB Interface	Front panel: 2 x USB2.0 Rear panel: 1 x USB3.0	Front panel: 2 x USB2.0 Rear panel: 2 x USB3.0
	Alarm in / Alarm Out	16-ch / 10-ch	16-ch / 10-ch
POE	Interface	-	-
	Max Power	-	-
	Supported Standard	-	-
General	Power Supply	100 ~ 240 V AC Power Consumption: ≤50W (without HDD)	100 ~ 240 V AC Power Consumption: ≤50W (without HDD)
	Working Environment	-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non- condensing)	-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non- condensing)
	Dimensions (WxD×H)	442mm x448mm× 93mm (17.4" x17.6" × 3.7")	442mm x448mm× 93mm (17.4" x17.6" × 3.7")
	Weight (without HDD)	≤6.0kg (13.23lb)	≤6.0kg (13.23lb)









For model and stock availability, please reach out to your regional Sales Representative

advitia

Optional Accessories









 M-46-FW-V3	JUNCTION BOX	 M-JB-MINI
 M-26-FW-V2	WALL	 M-WM-JB-MINI-V2 OR  M-WM-MINI
	DOME COVER (clear)	M-QDC46FC
	POLE	 M-WM-JB-MINI-V2 OR  M-WM-MINI +  M-PM-B-V2
	PENDANT	 M-JB-MINI +  M-Pendant















 M-49-FW-V2	JUNCTION BOX	 M-JB-MINI-B
 M-49-V-V2		
 M-29-FW-V2	POLE	 M-JB-MINI-B +  M-PM-B-V2
 M-29-V-V2		

 M-46-V-V2	JUNCTION BOX	 M-JB-T
 M-26-V-V2	WALL	 M-WM-T-V2
	DOME COVER (clear)	M-QDC46VC
	POLE	 M-WM-T-V2 +  M-PM-B-V2
	PENDANT	 M-JB-T +  M-Pendant

advidia

Optional Accessories



 M-87-V	JUNCTION BOX	 M-JB
	WALL	 M-WM-JB-V2
	POLE	 M-WM-JB-V2 +  M-PM-B-V2
	PENDANT	 M-JB +  M-Pendant
	CEILING	 M-FM
	DOME COVER (clear)	M-QDC87VC

 M-400-P	WALL	 M-PTZ-WM +  M-PTZ-JB  M-Parapet
	POLE	 M-PTZ-WM +  M-PTZ-JB +  M-PTZ-PM
	CORNER	 M-PTZ-WM +  M-PTZ-JB +  M-PTZ-CNR
	PENDANT	 M-CM +  M-PTZ Pendant-EX-L
		 M-CM OR  M-PTZ Pendant

advidia


advidia Guard (Management Software)

- The FOC software supports up to 64 local devices (cameras directly added to advidia Guard) or up to 512 local channels (total number of cameras connected to NVRs)
- Device management, Live View, PTZ Control, Sequence Display, Recording & Playback, Behaviour Search, E-Map, Audio, Alarm Configuration, Operation Log
- Easy to deploy and operate
- For small and medium-size application



advidia Viewer



- Mobile App allows you to see the video surveillance in anywhere at any time.
- Enhance security by remote monitoring on the go.
- Easy access to the live view and playback on mobile devices.
- Instant Alarm notification



advidia

advidia Player

This video software can be used to play recording files that are saved on your computer and play video streams from the network. It can also be used to verify videos by watermark detection.



advidia Guard

This software is a tool used to manage and configure devices on a local area network (LAN) including network camera and NVR. Major functions include

	Function
Device Configuration	Configure the device name, system time, DST, network, DNS, port of an IPC or NVR. Besides, Change Device Password and Change Device IP Address are also included.
Channel Configuration	Configure channel settings including image, encoding, OSD, audio and motion detection.
Upgrade Device	Local Upgrade: Upgrade device(s) using an upgrade file on your computer. Online Upgrade: Check the device firmware version, download upgrade files and upgrade the device with Internet connection.
Maintenance	Includes Configuration Import/Export, Export Diagnosis Info, Restart Device, and Restore Default Settings.
NVR Channel Management	Includes adding NVR channel and deleting NVR channel.

ii·PRO
The Power of Truth



LATAM website

advidia