Panasonic

WV-V1330LK

2 Megapixel 1080p Weatherproof Box type Camera Equipped with IR LED
















Key Features

- High-performance CMOS image sensor.
- Focal length: 3.6 mm
- H.265 / H.264 & MJPEG triple-stream encoding
- 60fps@1080P(1920 ×1080).
- Support Day / night (ICR) for day time and night time
- Max. IR LEDs length 30 m {98 ft 5-3/32 inches}.
- IP66 rated water and dust resistant.
- PoE. (IEEE802.3af compliant)

Appearance

75mm{2-15/16}



Specifications

| Camera | |
|---|--|
| Image Sensor | Approx. 1/2.8 type CMOS image sensor |
| Min Illumination | 0.2 lx / F2.0 (color)*, 0 lx / F2.0 (IR on)*1 |
| Gain | Auto/ Manual |
| Back light compensation | OFF/ BLC/ HLC/ WDR |
| Shutter speed | Auto/ Manual, 1/3(4) sec~1/100000 sec |
| Day / Night | Auto(ICR) / Color/ Black & White |
| IR LED Light | Irradiation distance: 30 m {98 ft 5-3/32 inches} |
| White Balance | Auto/ Natural/ Street Lamp/ Outdoor/Manual |
| Digital Noise Reduction | 3DNR ON/ OFF |
| Privacy masking | Up to 4 areas |
| Video Motion Detection | Off/ On (4 Zone, Rectangle) |
| Tampering Detection | On/ Off |
| Lens | |
| Focal Length *1 | 3.6 mm {5/32 inches} |
| Angular Field of View *1 | H: 87° V: 48° |
| Network | |
| Network | 10BASE-T/ 100BASE-TX, RJ45 connector |
| Resolution | 1080P(1920x1080) / 1.3 M (1280x960) / 720P (1280x720) / 640x480 / 640x360 / 320x240 |
| Image compression method | H.265/ H.264/MJPEG |
| Frame Rate | 1 to 50/60 fps |
| Protocol | IPv4/ IPv6, HTTP, HTTPS, SSL, TCP/ IP, UDP, UPnP, ICMP, IGMP,SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, DDNS, FTP, QoS, 802.1x |
| Maximum concurrent access number | 20 users (Number of sessions that can connect to cameras at the same time) |
| General | |
| Power source | 12 V DC, PoE (IEEE802.3af compliant) |
| Power Consumption | 12 V DC: 1 A / Approx. 12 W PoE 48 V DC: 100 mA / Approx. 4.8 W (Class 0 device) |
| Ambient Operating Temperature / Humidity | -30 °C to +60 °C {-22 °F to 140 °F} 10 % to 90 % (no condensation) |
| Water and Dust Resistance | Main body: IP66 |
| Dimensions | 75 mm(W) \times 71 mm (H) \times 165 mm {ø2-15/16 inches (W) \times 2-25/32 inches (H) \times 6-1/2 inches (D)} |
| Weight (approx.) | Approx. 380 g {0.84 lbs} |

^{*1} Depending on the product, the value may vary.

Important

- Safety Precaution: Carefully read the operating instruction manual before using this product.
- Panasonic cannot be responsible for the performance of the network and/or other manufacturers'
- All pictures are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.

DISTRIBUTED BY: