

Overview:






- 5MP
- 1.4mm lens
- Built-in Mic
- True WDR 120dB
- IR up to 10m
- IP66 rated



Technical Specifications

Device	
Image Sensor:	1/2.8", progressive scan, 5.0 megapixel, CMOS
Min Illumination:	Colour: 0.01 Lux (F2.0, AGC ON) 0 Lux with IR
Shutter Time:	Auto/Manual, shutter time: 1~1/100000 s
Lens:	1.4mm@F2.0
WDR:	120dB
Angle of View :	360°
Angle Adjustment:	–
3-Axis Adjustment :	–
Day & Night:	IR-cut filter for day & night function
IR Range:	UP to 10m (33ft)
Compression Standard	
Video Compression:	Ultra 265, H.265, H.264, MJPEG
Video Bit Rate:	128 Kbps~16 Mbps
Tri-Stream:	Yes
Analytics:	Motion detection, tampering alarm, audio detection
Image	
Max. Image Resolution:	30fps @ (2592 x 1944)
Frame Rate:	Main Stream: 5MP (2592*1944): Max.30fps; Sub Stream: 1080P (1920*1080): Max.30fps; 720P (1280*720), Max 30fps; Third Stream: D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;
ROI Codec:	Up to 8 areas
Image Setting:	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser

Technical Specifications

Network	
Alarm Channels:	1 Channel In 1 Channel Out
Protocols:	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSH
Interface	
Communication Interface:	1 RJ45 10M/100M Base-TX Auto-adaptive Ethernet
System Compatibility:	ONVIF (Profile S, Profile G, Profile T), API, SDK
Local Storage:	Micro SD up to 256GB
Audio:	Input: impedance 35 kΩ; amplitude 2 V [p-p] Output: impedance 600 Ω; amplitude 2 V [p-p]
General	
Operating Conditions:	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Power Consumption:	Max. 8.5W
Power Supply:	DC12V±25%, PoE (IEEE 802.3af)
Weather Proof Rating:	IP66
Vandal Resistant:	IK10
Dimensions:	Φ125 × 43.7 mm (Φ4.9" × 1.7")
Weight:	0.36kg (0.79lb)
Software:	Includes Video Insight VMS License
Accessories	
Accessories	<div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <p>M-JB-T</p>  </div> <div style="text-align: center;"> <p>M-Pendant</p>  </div> <div style="text-align: center;"> <p>M-Pendant-Ex</p>  </div> </div> <div style="display: flex; justify-content: space-around; align-items: flex-start; margin-top: 20px;"> <div style="text-align: center;"> <p>M-WM-T</p>  </div> <div style="text-align: center;"> <p>M-PM</p>  </div> </div>

R120622 | Product specifications and availability are subject to change without notice.

© i-PRO Co., Ltd. All Rights Reserved. i-PRO, Viewnetcam.com, Advidia, VideoInsight, CloUDE, and Unified Digital Evidence are registered trademarks or trademarks of i-PRO Co., Ltd. or i-PRO Americas Inc. in various jurisdictions. All other trademarks are the property of their respective owners.