

advidia M-89-F-L 8MP Fixed Bullet IP Camera

TECHNICAL SPECIFICATIONS

This specification is intended for use by the design/construction professional and any user of advidia Security products to assist in developing project specifications for security and video surveillance systems.

advidia M-89-F-L 8MP Fixed Bullet IP Camera

A. GENERAL CHARACTERISTICS

1. The network IR camera shall deliver H.265 stream, H.264 stream and MJPEG.
2. The network IR camera shall produce a resolution of 3840 x 2160 at up to 20 fps with a 16:9 aspect ratio.
3. The network IR camera shall utilize an approximate 1/2.7", 8.0-megapixel, progressive scan, CMOS.
4. The network IR camera shall be equipped with 4.0mm@F2.0 Lens.
5. The network IR camera shall feature an IR-Cut Filter with Auto Switch (ICR).
6. The network IR camera shall feature a 120dB wide dynamic range.
7. The network IR camera shall produce a color image with a minimum illumination 0.01Lux (F2.0, AGC ON) and monochrome image with 0Lux.
8. The network IR camera shall offer a built-in IR illumination to produce a clear monochrome image in zero lux conditions with up to 30m (98 ft).
9. The network IR camera shall transmit up to three (3) video streams simultaneously which can be selected to H.265 (Main profile) or H.264 (High profile).
10. A user shall be able to view video on a PC using a browser.
11. A user shall be able to view video on a smartphone and tablet using viewer software for iPhone and Android.
12. The network IR camera shall offer Cross Line, Intrusion, Enter Area, Leave Area Detection, Motion Detection, Tampering Alarm, Audio Detection.
13. The network IR camera shall have a micro-SD memory card slot that supports up to 256GB.
14. The network IR camera shall have a built-in microphone and speaker.
15. The network IR camera shall have an alarm light.
16. The network IR camera shall support IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS, SSH protocols.
17. NDAA Compliant.
18. The Camera shall conform to the ONVIF G / S / T.

B. CAMERA

1. Image Sensor 1/2.7", 8.0-megapixel, progressive scan, CMOS
2. Scanning Mode Progressive
3. Minimum Illumination
 - a. Color 0.01Lux (F2.0, AGC ON)
 - b. B/W 0Lux with IR
 - c. Day & Night IR-Cut Filter with Auto Switch (ICR)
4. Dynamic Range 120dB

C. LENS

1. Focal Length 4.0mm@F2.0
2. Angular Field of View H: 86.5°, V: 44.1°, O: 112.5°
3. Aspect ratio (16:9)

D. VIDEO

1. Compression Format H.265, H.264, MJPEG
2. Image Resolution
 - a. 16:9 aspect ratio (8 mega pixel mode)
3840 X 2160 (20fps)
3072 X 1720 / 1920 x 1080 / 1280 x 720 / 640 x 360 / 704 X 288 / 352 X 288 (25/30fps)
3. H.265 / H.264
 - a. Transmission Mode Constant bit rate / VBR, Frame rate / Best effort
 - b. Frame Rate 1 / 2 / 3 / 4 / 5 / 6 / 8 / 10 / 12 / 15 / 16 / 18 / 20 fps for 3840X2160
1 / 2 / 3 / 4 / 5 / 6 / 8 / 10 / 12 / 15 / 16 / 18 / 20 / 22 / 25 / 30 fps for 3072X1728
 - c. Bit Rate/Client 64 / 128 / 256 / 384 / 512 / 768 / 1,024 / 1,536 / 2,048 / 3,072 / 4,096 / 6,144 / 8,192 / 10,240 / 12,288 / 14,336 / 16,384 / 20,480 / 24,576 / 30,720 / 40,960 / Custom kbps (Max 16,384 kbps)
 - d. Image Quality
 - i. Constant bit rate
 - ii. VBR
 - e. Transmission type Unicast, Multicast
4. MJPEG
 - a. Image quality
 - b. Transmission type Pull, Push

E. AUDIO

- a. Audio Compression G.711U
- b. Audio Mode OFF / Mic input / Audio output / Interactive (Half duplex) / Interactive (Full duplex)

F. OPERATION

1. White Balance
2. Smart IR
3. Flip
4. Shutter speed Auto/Manual, 1 ~ 1/100000s
5. Day & Night IR-Cut Filter with Auto Switch (ICR)
6. Video Motion Detection On / Off
7. Intelligent Video Motion Detection
Cross Line, Intrusion, Enter Area, Leave Area Detection, Motion

- 8. Privacy Zone Detection, Tampering Alarm, Audio Detection
On / Off
- 9. Camera Title (OSD) Up to 20 characters

G. NETWORK

- 1. Network Interface 1 RJ45 10M/100M Base-TX Ethernet
- 2. IP IPv4
- 3. Supported Protocols
 - a. IPv4 IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, SNMP
- 4. Max. User access Up to 6 users
- 5. Mobile Terminal Compatibility iPad, iPhone(OS 4.2.1 or later) , Android™ mobile terminals

H. INTERFACE

- 1. SD memory card slot 1 slot, micro-SD card

I. ELECTRICAL

- 1. Power Source DC 12V±25%, PoE (IEEE 802.3af)
- 2. Power Consumption Max 10.5W

J. SAFETY / EMC

- 1. Safety UL (IEC62368-1), CE, IEC62368-1
- 2. EMC FCC (Part15 ClassA), EN55032 ClassB, EN55024

K. MECHANICAL

- 1. Dimensions (D x H) 91 × 75 × 74mm (7.5" × 3.0" × 2.9")
- 2. Weight 0.41kg (0.90lb)

L. ENVIRONMENTAL

- 1. Ingress resistance IP67
- 2. Operating Temperature -30°C ~ 60°C (-22°F ~ 140°F),,
- 3. Operating Humidity ≤95% RH (Non-Condensing)