




## Overview

- Support H.265/H.264 video formats
- 32-channel input
- Support 2-ch HDMI, 1-ch VGA. HDMI1 and HDMI2 up to 4K (3840x2160) resolution Up to 4K resolution recording
- Support RAID 0, 1,5, 6, 10
- 8 SATA HDDs, up to 10TB for each HDD
- Support N+1 Hot spare
- ANR technology to enhance the storage reliability when the network is disconnected
- NDAA Compliant
- Support mainstream camera of ONVIF conformance(Profile G, S, T) and RTSP protocols






Synchronous Playback
----------------------



Multiscreen Mode	Normal Mode: 4/6/8/9/16/25/36 Corridor Mode: 3/4/5/7/9/10/12/16/32 Web Client: 4/6/8/9/10/13/16
Decoding	
Decoding format	H.265/H.264
Live view/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	2 x 12MP@30fps, 4 x 4K@30fps, 8x 4MP@30fps, 9 x 4MP@30fps, 16 x 1080P@30fps, 32 x 720P@30fps
SATA	8 SATA interfaces
Capacity	Up to 10TB for each disk
eSATA	1 eSATA interface
Disk Array	
Array Type	RAID 0, 1, 5, 6, 10
External Interface	
Network Interface	2 x RJ45 10M/100M/1000M self-adaptive Ethernet Interfaces
Serial Interface	1 x RS232, 1 x RS485
USB Interface	Front panel: 2 x USB2.0, Rear panel: 1 x USB3.0
Alarm In	16-ch
Alarm Out	4-ch
General	
Power Supply	100~240 VAC Power Consumption: ≤ 25 W (without HDD)
Dimensions (W×D×H)	442m ×426mm× 89mm (17.4" × 16.8"× 3.5")
Weight (without HDD)	≤5.7kg (12.57lb)



## M-NVR-32CH 32ch Network Video recorder





© i-PRO Co., Ltd. All Rights Reserved. i-PRO, Viewnetcam.com, advidia, VideoInsight, CloUDE, and Unified Digital Evidence are registered trademarks or trademarks of i-PRO Co., Ltd. or i-PRO Americas Inc. in various jurisdictions. All other trademarks are the property of their respective owners.