

# WV-S22500-F6L

5MP Vandal Resistant Indoor Dome Network Camera

## S-series High resolution Network camera with AI engine



- 5MP
- Intelligent Auto (with AI Engine)
- Super Dynamic 132dB
- Color night vision (0.08 to 0.11 lx)
- Smart Coding (with AI Engine)
- Built-in IR LED
- IK10 Vandal Resistant
- Built-in FIPS 140-2 Level 3 Certified Secure Element  
(EdgeLock® SE050F NXP® Semiconductors)
- NDAA Compliant

# SPECIFICATIONS

| Camera  |  |
|---|--|
| Image Sensor                                    | Approx. 1/2.8 type CMOS image sensor   |
| Scanning Area                                   | 5.12 mm (H)×3.84 mm (V)<br>{3/16 inches (H) × 5/32 inches (V)}   |
| Minimum Illumination                            | Color : 0.08 lx (30IRE, F1.6, 1/30s)<br>Color : 0.11 lx (50IRE, F1.6, 1/30s)<br>BW : 0.07 lx (50IRE, F1.6, 1/30s)<br>BW : 0 lx (50IRE, F1.6, 1/30s with IR LED)  |
| White Balance                                   | ATW1 / ATW2 / AWC  |
| Shutter Speed                                   | [30fps/15fps mode] 1/30 Fix to 1/10000 Fix<br>[25fps/12.5fps mode] 1/25 Fix to 1/10000 Fix   |
| Intelligent Auto                                | On / Off   |
| Super Dynamic                                   | On / Off,<br>The level can be set in the range of 0 to 31.   |
| Dynamic Range                                   | Max.132 dB (Super Dynamic : On, Level 31)  |
| Adaptive Black Stretch                          | The level can be set in the range of 0 to 255.   |
| Back Light Compensation/High Light Compensation | BLC (Back light compensation) / HLC (High light compensation) / Off<br>(only when Super dynamic / Intelligent Auto : Off)  |
| Fog Compensation                                | On / Off<br>(only when Intelligent auto / auto contrast adjust : Off)  |
| Maximum Gain (AGC)                              | The level can be set in the range of 0 to 11.  |
| Color/BW (ICR)                                  | Off / On (IR Light Off) / On (IR Light On) / Auto1 (IR Light Off) / Auto2 (IR Light On) / Auto3 (SCC)  |
| IR LED Light                                    | High / Middle / Low / Off,<br>Maximum irradiation distance : 35 m {Approx. 115 ft} (30IRE) , 25 m {Approx. 82 ft} (50IRE)  |
| Digital Noise Reduction                         | The level can be set in the range of 0 to 255.   |
| Video Motion Detection (VMD)                    | On / Off,<br>4 areas available   |
| Scene Change Detection (SCD)                    | On / Off,<br>1 areas available   |
| Audio Detection                                 | On / Off   |
| AI Sound Classification                         | Gunshot, Yell, Vehicle horn, Glass break   |
| AI Analytics                                    | AI Video Motion Detection, AI Privacy Guard, AI Face Detection,<br>AI People Detection, AI Vehicle Detection,<br>AI Non mask Detection, AI Occupancy Detection, AI Scene Change Detection<br><br>For details :<br><a href="https://i-pro.com/products_and_solutions/en/surveillance/products/analytics-software">https://i-pro.com/products_and_solutions/en/surveillance/products/analytics-software</a><br>3rd party applications are also available.<br><a href="https://i-pro.com/products_and_solutions/en/surveillance/solutions/edge-ai-platform/application-list">https://i-pro.com/products_and_solutions/en/surveillance/solutions/edge-ai-platform/application-list</a> |
| Privacy Zone                                    | On / Off,<br>Up to 8 zones available   |
| VIQS  | On / Off,<br>Up to 8 zones available   |

|                    |  |
|--------------------|--|
| Image Rotation     | 0 ° / 90 ° / 180 ° / 270 °                                     |
| Camera Title (OSD) | On / Off, Up to 40 characters (alphanumeric characters, marks) |
| Focus Adjustment   | Auto focus   |

## Lens

|                        |  |
|------------------------|--|
| Optical zoom           | 1 x  |
| Extra zoom             | 1x - 3x (when resolution is 640 x 360)   |
| Focal length           | 6.1 mm {1/4 inches}  |
| Angular Field of View  | [16 : 9 mode] Horizontal : 48°, Vertical : 27°<br>[ 4 : 3 mode] Horizontal : 48°, Vertical : 36° |
| Maximum Aperture Ratio | 1 : 1.6  |
| Focus range            | 1.0 m {39-3/8 inches} – ∞  |

## DORI

|                            |                   |
|----------------------------|-------------------|
| Detect (25ppm / 8ppf)      | 138 m / 452.7 ft  |
| Observe (62.5ppm / 19ppf)  | 55.2 m / 181.1 ft |
| Recognize (125ppm / 38ppf) | 27.6 m / 90.5 ft  |
| Identify (250ppm / 76ppf)  | 13.8 m / 45.3 ft  |

## System on Chip (SoC)

|                      |                |
|----------------------|----------------|
| System on Chip (SoC) | Ambarella CV22 |
|----------------------|----------------|

## Adjusting Angle

|                 |   |
|-----------------|---|
| Adjusting Angle | Horizontal : -240 to +120°, Vertical : -30 to +85°, Yaw : ±100° |
|-----------------|---|

## Browser GUI

|                           |  |
|---------------------------|--|
| Camera Control            | Brightness, AUX On / Off   |
| Audio                     | Mic (Line) Input : On / Off Volume adjustment : Low / Middle / High<br>Audio Output : On / Off Volume adjustment : Low / Middle / High |
| GUI / Setup Menu Language | English, Italian, French, German, Spanish, Portuguese, Russian, Chinese, Japanese  |
| Browser                   | Microsoft Edge, Firefox, Google Chrome   |

## Network

|                                       |  |
|---------------------------------------|--|
| Network IF                            | 10Base-T / 100Base-TX, RJ45 connector  |
| Resolution H.265/ H.264/ JPEG (MJPEG) | [16:9 mode (30 fps mode)][16:9 mode (25 fps mode)]<br>3072x1728/2560x1440/1920x1080/1280x720/640x360/320x180<br>[4:3 mode (30 fps mode)][4:3 mode (25 fps mode)]<br>3072x2304/2560x1920/1280x960/800x600/VGA/400x300/320x240   |
| H.265/H.264                           | [Transmission Mode]<br>Constant bit rate / VBR / Frame rate / Best effort<br>[Transmission Type]<br>Unicast port (AUTO) / Unicast port (MANUAL) / Multicast  |
| JPEG                                  | [Image Quality]<br>10 steps  |
| Smart Coding                          | GOP (Group of pictures) control:<br>Off/ Low (Variable GOP 1s-8s)/ Mid (Variable GOP 4s-16s)/<br>Advanced(Fixed GOP 60s w/1s key-frame)/<br>Frame rate control (Variable GOP 4s-16s with frame rate control)<br>*Advanced and Frame rate control are only available with H.265.<br>Smart VIQS: On(High)/On(Low)/Off, Smart P-picture control: On/Off |

|                               |   |
|-------------------------------|---|
| Audio Compression             | G.726 (ADPCM) : 16 kbps / 32 kbps<br>G.711 : 64 kbps<br>AAC-LC : 64 kbps / 96 kbps / 128 kbps   |
| Audio Transmission Mode       | Off / Mic (Line) input / Audio output / Interactive (Half duplex) / Interactive (Full duplex)   |
| Supported Protocol            | IPv6: TCP/IP, UDP/IP, HTTP, HTTPS, SSL/TLS, SMTP, DNS, NTP, SNMPv1/v2/v3, DHCPv6, RTP, MLD, ICMP, ARP, IEEE 802.1X, DiffServ, SFTP, MQTT, LLDP<br>IPv4: TCP/IP, UDP/IP, HTTP, HTTPS, SSL/TLS, RTSP, RTP, RTP/RTCP, SMTP, DHCP, DNS, DDNS, NTP, SNMPv1/v2/v3, UPnP, IGMP, ICMP, ARP, IEEE 802.1X, DiffServ, SRTP, SFTP, MQTT, LLDP   |
| No. of Simultaneous Users     | Up to 14 users (Depends on network conditions)  |
| Secure                        | FIPS 140-2 level 3 Certified Secure Element (NXP® EdgeLock® SE050F), Device Certificate GlobalSign® pre-installed,<br>User authentication, Host authentication, HTTPS, 802.1X Support, Data encryption  |
| SDXC/SDHC/SD Memory Card      | H.265 / H.264 recording :<br>Manual REC / Alarm REC (Pre/Post) / Schedule REC / Backup upon network failure<br>JPEG recording :<br>Manual REC / Alarm REC (Pre/Post) / Backup upon network failure<br>Compatible SDXC/SDHC/SD Memory Card :<br>microSDXC memory card: 64 GB, 128 GB, 256 GB, 512 GB<br>microSDHC memory card: 4 GB, 8 GB, 16 GB, 32 GB<br>microSD memory card: 2 GB |
| Mobile Terminal Compatibility | iPad, iPhone (iOS 8.0 or later), Android™ terminals   |
| ONVIF® Profile                | G / M / S / T   |

## Alarm

|               |  |
|---------------|--|
| Alarm Source  | 3 terminals input, VMD alarm, Command alarm, Audio detection alarm   |
| Alarm Actions | SDXC/SDHC/SD memory recording, E-mail notification, HTTP alarm notification Indication on browser, TCP alarm notification output |

## Input/Output

|                                 |  |
|---------------------------------|--|
| Monitor Output (for Adjustment) | VBS : 1.0 V [p-p] / 75 Ω, composite, Pin jack<br>An NTSC or PAL signal can be outputted from camera  |
| Audio input                     | ø3.5 mm stereo mini jack<br>For microphone input : Recommended applicable microphone : Plug-in power type (Sensitivity of microphone : -51 dB to -38 dB (0 dB=1 V/Pa, 1 kHz))<br>Input impedance : Approx. 2 kΩ (unbalanced)<br>Supply voltage : 2.5 V ±0.5 V<br>For line input : Input level: Approx. -10 dBV |
| Audio Output                    | ø3.5 mm stereo mini jack (monaural output)<br>Output impedance : Approx. 600 Ω (unbalanced)<br>Output level : -20 dBV  |
| External I/O Terminals          | ALARM IN 1 (Alarm input 1/ Black & white input/ Auto time adjustment input) (x1)<br>ALARM IN 2 (Alarm input 2/ ALARM OUT) (x1)<br>ALARM IN 3 (Alarm input 3/ AUX OUT) (x1)   |

## General

|                                    |  |
|------------------------------------|--|
| Safety                             | UL (UL62368-1), c-UL (CSA C22.2 No.62368-1), CE, IEC62368-1  |
| EMC                                | FCC (Part15 ClassA), ICES-003 ClassA, EN55032 ClassA, EN55035  |
| Power Source and Power Consumption | DC power supply : DC12 V 880 mA, Approx. 10.6 W<br>PoE (IEEE802.3af compliant) Device : DC48 V 220 mA, Approx. 10.6 W (Class 0 device) |
| Ambient Operating Temperature      | -10 °C to +50 °C (14 °F to 122 °F)<br>(Power On range: 0 °C to 50 °C{32°F to 122 °F})  |
| Shock Resistance                   | IK10 (IEC 62262)   |
| Ambient Operating Humidity         | 10 to 90 % (no condensation)   |

|                |  |
|----------------|--|
| Dimensions     | ø129.5 mm x 102.5 mm (H) {ø5-3/32 inches x 4-1/32 inches (H)}<br>Dome radius 41.5 mm {1-5/8 inches}  |
| Mass (approx.) | 800 g {1.77 lbs.}  |
| Finish         | Main body : Aluminum die cast, i-PRO white<br>Outer fixing screws : Stainless steel (Corrosion-resistant treatment)<br>Dome cover : Polycarbonate resin, Clear |

## NOTES

### Important

- Safety Precautions : Carefully read the Basic Information, Installation Guide and Operating Instructions before using this product.
- i-PRO Co., Ltd. cannot be held responsible for the performance of the network and/or other manufacturers' products used on the network.
- Masses and dimensions are approximate. Specifications are subject to change without notice.

### Trademarks and registered trademarks

- iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. - Android is a trademark of Google LLC.
- ONVIF is a trademark of ONVIF, Inc.
- All other trademarks identified herein are the property of their respective owners

©i-PRO Co., Ltd All rights reserved / November 2022

## OPTIONAL ACCESSORIES

Select a compatible accessory

[Accessory Selector \(i-pro.com\)](http://i-pro.com).



WV-QWL501-W  
Mount Bracket



WV-QWL500-W  
Mount Bracket



WV-QSR501-W  
Mount Bracket



WV-QPL500-W  
Mount Bracket



WV-QJB500-W  
Mount Bracket



WV-QEM100-W  
Mount Bracket



WV-QCN500-W  
Mount Bracket



WV-QCL501-W  
Mount Bracket



WV-QCL101-W  
Mount Bracket



WV-QCL100-W  
Mount Bracket



WV-QAT501-W  
Attachment Pipe  
Bracket



WV-QAT500-W  
Attachment pipe



WV-Q105A  
Mount Bracket



PAPM4W  
Pole Mount Bracket



PACA4W  
Corner Mount Adapter  
Bracket




WV-CR1S  
Dome Cover





WV-PM500  
Compact microphone  
unit for surveillance  
cameras

# APPEARANCE




| Model number   | Dome type  | Color       | Lower cover coating |
|----------------|------------|-------------|---------------------|
| WV-S22500-V3L  | Clear dome | i-PRO white | No                  |
| WV-S22500-V3LJ | Clear dome | i-PRO white | No                  |
| WV-S22500-V3L1 | Clear dome | Black       | Black               |
| WV-S22500-V3L6 | Smoke dome | i-PRO white | No                  |
| WV-S22600-V2L  | Clear dome | i-PRO white | No                  |
| WV-S22600-V2L6 | Smoke dome | i-PRO white | No                  |
| WV-S22700-V2L  | Clear dome | i-PRO white | No                  |
| WV-S22700-V2L1 | Clear dome | Black       | Black               |
| WV-S22700-V2L6 | Smoke dome | i-PRO white | No                  |
| WV-S22500-F3L  | Clear dome | i-PRO white | No                  |
| WV-S22500-F6L  | Clear dome | i-PRO white | No                  |



Mass : Approx. 800 g [1.77 lbs]



Lens type : 5M\_FIX




Lens type : 5M\_6M\_4K



Template for mounting



DetailA (2:1)




Without Enclosure


| Model number   | Lens type |
|----------------|-----------|
| WV-S22500-V3L  | 5M        |
| WV-S22500-V3LJ |           |
| WV-S22500-V3L1 |           |
| WV-S22500-V3L6 | 6M        |
| WV-S22500-V2L  |           |
| WV-S22500-V2L6 |           |
| WV-S22700-V2L  | 4K        |
| WV-S22700-V2L1 |           |
| WV-S22700-V2L6 |           |
| WV-S22500-F3L  | 5M FIX    |
| WV-S22500-F6L  |           |




金具との組み合わせ例  
Example of combination with bracket




Attach to WV-QWL500-W




Attach to WV-QCL100-W



Attach to WV-QEM100-W




Attach to WV-Q105A



Attach to WV-QSR501-W



Attach to WV-QSR501F-W



Attach to WV-QSR501M-W

Model number  
 WV-S22500-V3L  
 WV-S22500-V3LJ  
 WV-S22500-V3L1  
 WV-S22500-V3L6  
 WV-S22600-V2L  
 WV-S22600-V2L6  
 WV-S22700-V2L  
 WV-S22700-V2L1  
 WV-S22700-V2L6  
 WV-S22500-F3L  
 WV-S22500-F6L