

WV-SUD638

Anti-severe weather PTZ network outdoor camera with wiper and defroster

Aero PTZ Network Camera

The AeroPTZ is an environmentally rugged camera designed to meet extreme weather conditions.



- 2MP (1080p) (1080p) 60fps, 30x zoom lens
- Built-in wiper and Auto defroster
- Wind load durability 60 m/s (135 mph) (operation), 80 m/s (180 mph) (non-destructive)
- Video SAS (Stability Augment System) for high-class image stabilization
- “Sphere vision” provides 360° 3D viewing
- Temperature -50 °C to +60 °C (-58 °F to +140 °F)
- IP67, IP66, IK10 certified
- Optional IR LED light
- Heavy salt damage resistance specifications (ISO 14993 compliant)
- Smart Coding mode for additional compression
- NDAA Compliant

Precautions for heavy salt damage resistance

SPECIFICATIONS

Camera	
Image Sensor	Approx. 1/3 type MOS image sensor
Minimum Illumination	Color : 0.06 lx (F1.6, Maximum shutter : Off(1/30 s), AGC : High) 0.004 lx (F1.6, Maximum shutter : max. 16/30 s, AGC : High)* BW : 0.02 lx (F1.6, Maximum shutter : Off(1/30 s), AGC : High) 0.001 lx (F1.6, Maximum shutter : max. 16/30 s, AGC : High)* 0 lx (F1.6, Maximum shutter : Off(1/30 s), AGC : High, when the IR LED (Optional) is lit) * Converted value
Super Dynamic	Dynamic Range 105 dB typ.
Image Settings	Gain (AGC), White balance
Image Compression	Adaptive black stretch, Back light compensation (BLC), Fog compensation, High light compensation (HLC), Digital noise reduction
Shutter Speed	[2 mega pixel [16 : 9] (60 fps mode)] Off(1/60) to 1/10000 Other than [2 mega pixel [16 : 9] (60 fps mode)] Off(1/30) to 1/10000
Day/Night (ICR)	Off / On / Auto1(Normal) / Auto2(IR Light) / Auto3(SCC)
IR LED Light (Optional)	Off / Auto (High / Mid / Low) irradiation distance : 150 m (500 feet)
Image Stabilization	On / Off *Hybrid image stabilizer
Privacy Zone	Gray / Mosaic / Off (up to 32 zones available)
Camera Title on Screen	Up to 20 characters (alphanumeric characters, marks)
Video Motion Detection (VMD)	On / Off, 4 areas available
Lens	
Zoom Ratio	30x / 45x with HD extra optical zoom (at 1280 x 720) (Motorized zoom / Auto Focus)
Digital (Electronic) Zoom	x1, x2, x4
Focal Length	4.3 mm - 129 mm {3/16 inches - 5-3/32 inches}
Maximum Ratio Aperture	1 : 1.6 (WIDE) - 1 : 4.7 (TELE)
Focus Range	2.0 m - ∞
Aperture Range	F1.6 (WIDE) - Close
Angular Field of View	[16 : 9 mode] Horizontal : 2.3° (TELE) - 64° (WIDE) Vertical : 1.3° (TELE) - 38° (WIDE) [4 : 3 mode] Horizontal : 1.8° (TELE) - 50° (WIDE) Vertical : 1.3° (TELE) - 38° (WIDE)
Pan/tilt unit	
Panning Range	360° endless
Panning Speed	Manual : approx. 0.065°/s to 100°/s Preset : up to approx. 200°/s (Except when IR LED Unit is equipped, forward tilt mount, frozen.)

Tilting Range	Upright : -45° to +90° Forward tilt : -90° to +90° Hanging : -90° to +30°
Tilting Speed	Manual : approx. 0.065°/s to 100°/s Preset : up to approx. 200°/s (Except when IR LED Unit is equipped, forward tilt mount, frozen.)
Preset Positions	256 positions
Auto Mode	Auto track / Auto pan / Preset sequence / 360 map-shot / Preset map-shot / Patrol
Self Return	10 s to 60 min
Tilt Flip	On / Off
Map Shot	360° map shot / preset map shot

Network

Network IF	10Base-T / 100Base-TX, RJ45 connector
Image Resolution	•2 mega pixel [16 : 9] (60 fps mode / 30 fps mode) H.264 : Maximum 1,920 x 1080 JPEG : Maximum 1,920 x 1080 •1.3 mega pixel [4 : 3] (30 fps mode) H.264 : Maximum 1,280 x 960 JPEG : Maximum 1,280 x 960
Image Compression Method	H.264 Transmission Mode : Constant bit rate / Variable bit rate / Frame rate priority / Best effort / Advanced VBR Transmission type : Unicast / Multicast JPEG Image Quality : 10 steps Multiple streams individually configurable
Intelligent Compression	Smart coding, VIQS (ROI)
Audio Compression	G.726 (ADPCM) : 16 kbps / 32 kbps G.711 : 64 kbps AAC-LC : 64 kbps, AAC-LC(High quality) : 64 kbps / 96 kbps / 128 kbps
Protocol	IPv6 : TCP/IP, UDP/IP, HTTP, HTTPS, FTP, SMTP, DNS, NTP, SNMP, DHCPv6, RTP, MLD, ICMP, ARP, DiffServ IPv4 : TCP/IP, UDP/IP, HTTP, HTTPS, RTSP, RTP, RTCP, FTP, SMTP, DHCP, DNS, DDNS, NTP, SNMP, UPnP, IGMP, ICMP, ARP, DiffServ
Maximum Concurrent Access Number	Up to 14 users (Depends on network conditions)
Mobile Terminal Compatibility	iPad, iPhone, iPod touch (iOS 4.2.1 or later) Android™ mobile terminals

Environment

Water and Dust Resistance	Main body : IP66, IP67, IEC60529 measuring standard compatible, Type 4X(UL50), NEMA 4X compliant Waterproof RJ45 connector, Waterproof power connector, Waterproof I/O connector
Shock Resistance	Compliant with IK10 (IEC 62262)
Salt Damage Resistance	ISO14993 compliant
Resistance to Wind	Upright 216 km/h (135 mph) (Operation) / 288 km/h (180 mph) (non-destructive) Forward tilt 50 m (112 mph) (Operation) / 80 m (180 mph) (non-destructive)

General

Safety	UL (UL60950-1), c-UL (CSA C22.2 No.60950-1), CE, IEC60950-1
--------	---

EMC	FCC (Part15 ClassA), ICES003 ClassA, EN55032 ClassA, EN55035
Power Source	AC100 to 240 V, 50 Hz / 60 Hz Tested PoE Injector* (60 W) *with limitations
Operating Environment	Ambient operating temperature : AC100 to 240 V : -50 °C to +60 °C {-58 °F to 140 °F} (Power On range : -30 °C to +60 °C {-22 °F to 140 °F}) When using the tested PoE injector : -30 °C to +60 °C {-22 °F to 140 °F} When using the tested PoE injector and IR LED unit at the same time: -20 °C to +55 °C {-4 °F to 131 °F}) *The upper limit value of ambient operating temperature indicates the use of WV-SUD638 (natural silver). In cases of products with other body colors, the upper limit value is +55 °C {131 °F}. *When WV-SUD6FRL1 (IR LED unit) is attached, the upper limit value of ambient operating temperature is +55 °C {131 °F}. Ambient operating humidity : 10 % to 100 %
External I/O Terminals	ALARM IN 1(DAY/NIGHT IN, Auto time adjustment), ALARM IN 2(ALARM OUT), ALARM IN 3(AUX OUT), Relay connection (x1 for each)
Line Input	ø3.5 mm monaural mini jack Input impedance : Approx. 2 kΩ (unbalanced) For line input Input level : Approx. -10 dBV
Audio Output	ø3.5 mm stereo mini jack (monaural output) Output impedance : Approx. 600 Ω (unbalanced) Using Amplifier built-in external speaker Output level : -20 dBV
Monitor Output	-
Dimensions	220 mm (W) x 450 mm (H) x 266 mm (D) {8-21/32 inches (W) x 1ft 5-23/32 inches (H) x 10-15/32 inches (D)}
Mass (Approx.)	Approx. 8.5 kg {18.7 lbs}
Finish	Main body : Glass Fiber Reinforced Plastics WV-SUD638 : Natural Silver WV-SUD638-H : Gray (N7) WV-SUD638-T : Brown (Environmental color) Front glass : Glass, Clear

NOTES

Important

- Safety Precautions : Carefully read the Basic Information, Installation Guide and Operating Instructions before using this product.
- i-PRO Co., Ltd. cannot be held responsible for the performance of the network and/or other manufacturers' products used on the network.
- Masses and dimensions are approximate.
- Specifications are subject to change without notice.

Trademarks and registered trademarks

- iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. - Android is a trademark of Google LLC.
- ONVIF is a trademark of ONVIF, Inc.
- All other trademarks identified herein are the property of their respective owners

©i-PRO Co., Ltd All rights reserved / November 2022

OPTIONAL ACCESSORIES

Select a compatible accessory

[Accessory Selector \(i-pro.com\)](http://i-pro.com).



WV-SUD6FRL1
Unit



WJ-PU201
60W Single Port Power
over Ethernet

APPEARANCE

WV-SUD638 APPEARANCE

Technical drawings of the WV-SUD638 urinal, showing various views and dimensions:

- Top view showing dimensions: 200 (width), 190 (depth), and 150 (height).
- Side view showing dimensions: 267 (width), 190 (depth), and 150 (height).
- Front view showing dimensions: 130 (width), 112 (height), and 71.8 (width).
- Bottom view showing dimensions: 130 (width), 112 (height), and 71.8 (width).
- Isometric view showing the urinal with its lid open.
- Isometric view showing the urinal with its lid closed.
- Isometric view showing the urinal with its lid open and a callout for the 5-V CHIP MODEL (WV-SUD638P/638H).
- Isometric view showing the urinal with its lid open and a callout for the 5-V CHIP MODEL (WV-SUD638P/638H).

製品品番	製品色	品種ロゴ
WV-SUD638	シルバー	WV-SUD638
WV-SUD638PJ	シルバー	
WV-SUD638-T	茶色 (環境色)	
WV-SUD638-H	N7 Gray	
WV-SUD638H	シルバー	
WV-SUD638B	シルバー	WV-SUD638B

Model	Color	Model No. LOGO
WV-SUD638	Silver	WV-SUD638
WV-SUD638PJ	Silver	
WV-SUD638-T	Brown (Environment color)	
WV-SUD638-H	N7 Gray	
WV-SUD638H	Silver	
WV-SUD638B	Silver	WV-SUD638B

No.	Part name	Material	Process/Remark
1	TOP CHIP MODEL		
2	CAMERA UNIT		
3	SENSOR UNIT		
4	WATER UNIT		
5	NOZZLE UNIT		
6	WATER UNIT		
7	WATER UNIT		
8	WATER UNIT		
9	WATER UNIT		
10	WATER UNIT		
11	WATER UNIT		
12	WATER UNIT		
13	WATER UNIT		
14	WATER UNIT		
15	WATER UNIT		
16	WATER UNIT		
17	WATER UNIT		
18	WATER UNIT		
19	WATER UNIT		
20	WATER UNIT		
21	WATER UNIT		
22	WATER UNIT		
23	WATER UNIT		
24	WATER UNIT		
25	WATER UNIT		
26	WATER UNIT		
27	WATER UNIT		
28	WATER UNIT		
29	WATER UNIT		
30	WATER UNIT		
31	WATER UNIT		
32	WATER UNIT		
33	WATER UNIT		
34	WATER UNIT		
35	WATER UNIT		
36	WATER UNIT		
37	WATER UNIT		
38	WATER UNIT		
39	WATER UNIT		
40	WATER UNIT		
41	WATER UNIT		
42	WATER UNIT		
43	WATER UNIT		
44	WATER UNIT		
45	WATER UNIT		
46	WATER UNIT		
47	WATER UNIT		
48	WATER UNIT		
49	WATER UNIT		
50	WATER UNIT		
51	WATER UNIT		
52	WATER UNIT		
53	WATER UNIT		
54	WATER UNIT		
55	WATER UNIT		
56	WATER UNIT		
57	WATER UNIT		
58	WATER UNIT		
59	WATER UNIT		
60	WATER UNIT		
61	WATER UNIT		
62	WATER UNIT		
63	WATER UNIT		
64	WATER UNIT		
65	WATER UNIT		
66	WATER UNIT		
67	WATER UNIT		
68	WATER UNIT		
69	WATER UNIT		
70	WATER UNIT		
71	WATER UNIT		
72	WATER UNIT		
73	WATER UNIT		
74	WATER UNIT		
75	WATER UNIT		
76	WATER UNIT		
77	WATER UNIT		
78	WATER UNIT		
79	WATER UNIT		
80	WATER UNIT		
81	WATER UNIT		
82	WATER UNIT		
83	WATER UNIT		
84	WATER UNIT		
85	WATER UNIT		
86	WATER UNIT		
87	WATER UNIT		
88	WATER UNIT		
89	WATER UNIT		
90	WATER UNIT		
91	WATER UNIT		
92	WATER UNIT		
93	WATER UNIT		
94	WATER UNIT		
95	WATER UNIT		
96	WATER UNIT		
97	WATER UNIT		
98	WATER UNIT		
99	WATER UNIT		
100	WATER UNIT		

品名	投影面積 (mm ²)
WV-SUD638 (Top-view)	0.073 (m ²)
WV-SUD638 (Side-view)	0.071 (m ²)